NovoTech MACHINE TOOLS Inc.

PRODUCT CATALOGUE 2026

NOVOTECH VALUE LINE · BUILT IN CHINA TO NORTH AMERICAN STANDARDS · SOLD & SERVICED IN CANADA BY NOVOTECH

HYDRAULIC PRESS BRAKES

CNC PRESS BRAKES 55 – 331 US TONS · HEAVY-DUTY AND TANDEM TO 1,323 TONS · NC TORSION-BAR PRESS BRAKES 33 – 441 TONS







China
MADE IN CHINA

5
MACHINE FAMILIES

1-year
WARRANTY

Canada
PARTS & TECHNICAL SUPPORT

VALUE-LINE HYDRAULIC PRESS BRAKES

CONTENTS

CNC HYDRAULIC PRESS BRAKES

CNC hydraulic press brakes, 55 – 149 US tons × 4 – 13.5 ft WAD-50T/1300 – WAD-135T/4100 · 9 models 04

CNC hydraulic press brakes, 187 – 331 US tons × 10 – 20 ft WAD-170T/3200 – WAD-300T/6000 · 16 models 06

Heavy-duty CNC press brakes, 441 – 1,323 US tons × 13 – 26 ft, and tandems WAD-400T/4000 – WAD-1200T/8000 · 21 models · tandem to 60 ft 09

NC HYDRAULIC PRESS BRAKES — TORSION BAR

NC hydraulic press brakes, 33 – 138 US tons × 5 – 20 ft — torsion bar WC67K-30t/1600 – WC67K/E-125t/6000 · 13 models 13

NC hydraulic press brakes, 176 – 441 US tons × 8 – 20 ft — torsion bar WC67K/E-160t/2500 – WC67K/E-400T/6000 · 21 models 16

Specifications subject to change without notice. Imperial values are converted from the manufacturer's metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16); metric values in brackets are the manufacturer's nominal figures. Model numbers are manufacturer designations. Photos may show optional equipment.

ABOUT NOVOTECH

YOUR CANADIAN SOURCE FOR VALUE-LINE HYDRAULIC PRESS BRAKES

Sales, installation, parts and technical support across Canada.

NovoTech Machine Tools Inc. supplies metalworking and fabrication machinery to job shops, fabricators, maintenance departments and manufacturers across Canada from our base in Mississauga, Ontario. Every machine in this catalogue is sold and supported locally by NovoTech — with spare parts and technical support readily available in Canada.

INCLUDED WITH EVERY NOVOTECH MACHINE

- Built in China to North American standards
- CSA-approved electrical panel
- 1-year warranty
- 7-day money-back guarantee
  in-stock machines only
- Spare parts & technical support
  readily available in Canada
- Order today with just 10% down
  0% down financing available
- Installation and training available

NOVOTECH VALUE LINE

CNC AND NC PRESS BRAKES AT A PRICE A SMALL SHOP CAN JUSTIFY

NovoTech's value line is our own brand: machines built in China to our specification with European and Japanese controls and hydraulics — Delem, Estun, Hawe, Rexroth, Schneider, Siemens, NOK — inspected before they ship and sold under NovoTech's name with the same CSA-approved panel, 1-year warranty and parts and technical support from Mississauga, Ontario, as every machine we sell.

The CNC press brakes in this catalogue use electro-hydraulic servo synchronisation with Hawe valves and linear scales, a servo-driven pump that runs only while the ram moves, a Delem DA-53T control and a servo back gauge on ball screws — the architecture of the European machines, from 55 to 331 US tons over 4 to 20 ft, with heavy-duty and tandem machines to 1,323 tons and 26 ft. The NC press brakes keep the two cylinders in step with a torsion bar and set the depth on mechanical stops, with an Estun E21 control for the back gauge and 40 stored programs: the simple, rugged brake for brackets, boxes, channels and roofing, from 33 to 441 tons.

WAD-50T/1300 – WAD-135T/4100 · 9 MODELS

CNC HYDRAULIC PRESS BRAKES, 55 – 149 US TONS × 4 – 13.5 FT



MODEL CNC · NOVOTECH WAD 100T/3200 CNC HYDRAULIC PRESS BRAKE — 10 FT × 110 US TONS, FRONT VIEW WITH THE DELEM CONTROL ON ITS SWING ARM



WAD 100T/3200 CNC hydraulic press brake — front view with front support arms



WAD 110T/3200 CNC hydraulic press brake with the 2D graphic touchscreen control

The value-line CNC press brake: electro-hydraulic servo synchronisation with Hawe valves and linear scales, a servo-driven pump that only runs while the ram moves, a Delem DA-53T control and a servo back gauge on ball screws — the same architecture as the European machines, built to a price that lets a small shop own a real CNC brake. Nine models from 55 US tons × 4 ft to 149 US tons × 13.5 ft; the 110 and 135 t × 10 ft machines are the ones most Canadian shops ask for, with the DA-53T or DA-58T and 4+1 axes. Delem DA-66T / 69T 3D controls, 6-axis back gauges, DSP laser protection, sheet followers and Wila clamping are options.

STANDARD FEATURES

- ✓ Mild steel to 1/4" over 10 ft on the 110 t, 5/16" on the 135 t (V = 8 × thickness)
- ✓ Delem DA-53T 2D touchscreen CNC control; 4 axes — Y1, Y2 (independent ram cylinders), X and R back gauge
- ✓ Electro-hydraulic servo synchronisation: Hawe (Germany) valves, linear scales on both sides, ± 0.01 mm ram repeatability
- ✓ Servo-driven main pump — the pump turns only while the ram moves: 40 – 60 % less energy than a conventional CNC brake, about 60 dB
- ✓ Servo back gauge on ball screws and linear guides, ± 0.01 mm; two stop fingers with four positioning steps
- ✓ Motorised CNC crowning (V axis) on 110 t and up; Schneider electrics; Estun servo drives
- ✓ European-style quick clamps and a segmented 2-V die with sectioned punch set (42CrMo, HRC 47); front support arms on linear rail
- ✓ Side guards, enclosed rear guard, anti-panic foot pedal with emergency stop
- ✓ CSA-approved electrical panel, 600 V 3-phase standard (208 / 240 / 480 V on request)

OPTIONAL EQUIPMENT

- + Delem DA-58T (15" 2D), DA-66T (17" 2D + 3D view) or DA-69T (3D) control; ESA S875, Cybelec options
- + 6-axis back gauge X1, X2, R1, R2, Z1, Z2 on ball screws; back gauge strokes to 39" (1,000 mm)
- + DSP laser finger protection (EN 12622 CAT 4 / SIL 3) or light curtains
- + CNC sheet follower supports
- + Wila hydraulic clamping; double-sided quick clamps; Rolleri pneumatic clamps
- + Automatic angle measurement
- + Hydraulic oil cooler; automatic lubrication
- + Tandem machines on one control; robot bending cells
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS

CNC HYDRAULIC PRESS BRAKES, 55 – 149 US TONS × 4 – 13.5 FT

CNC HYDRAULIC PRESS BRAKES · 4 – 13.5 FT

9 models · 55 – 149 US tons

Model	WAD-50T/1300	WAD-50T/1600	WAD-70T/2000	WAD-70T/2500	WAD-80T/2500	WAD-110T/3200	WAD-110T/4100	WAD-135T/3200	WAD-135T/4100
Bending force	**55 US tons (50 t)**	**55 US tons (50 t)**	**77 US tons (70 t)**	**77 US tons (70 t)**	**88 US tons (80 t)**	**121 US tons (110 t)**	**121 US tons (110 t)**	**149 US tons (135 t)**	**149 US tons (135 t)**
Bending length	**4.3 ft · 51.2" (1,300 mm)**	**5.2 ft · 63.0" (1,600 mm)**	**6.6 ft · 78.7" (2,000 mm)**	**8.2 ft · 98.4" (2,500 mm)**	**8.2 ft · 98.4" (2,500 mm)**	**10.5 ft · 126.0" (3,200 mm)**	**13.5 ft · 161.4" (4,100 mm)**	**10.5 ft · 126.0" (3,200 mm)**	**13.5 ft · 161.4" (4,100 mm)**
Distance between columns	44.1" (1,120 mm)	51.2" (1,300 mm)	63.0" (1,600 mm)	80.7" (2,050 mm)	80.7" (2,050 mm)	106.3" (2,700 mm)	141.7" (3,600 mm)	106.3" (2,700 mm)	141.7" (3,600 mm)
Throat depth	9.8" (250 mm)	9.8" (250 mm)	11.8" (300 mm)	11.8" (300 mm)	11.8" (300 mm)	15.7" (400 mm)	15.7" (400 mm)	15.7" (400 mm)	15.7" (400 mm)
Stroke	5.9" (150 mm)	5.9" (150 mm)	5.9" (150 mm)	5.9" (150 mm)	5.9" (150 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)
Daylight open height	18.1" (460 mm)	18.1" (460 mm)	18.1" (460 mm)	18.1" (460 mm)	18.1" (460 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)
Approach speed	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	8.66 in/s (220 mm/s)	8.66 in/s (220 mm/s)	8.66 in/s (220 mm/s)	8.66 in/s (220 mm/s)	8.66 in/s (220 mm/s)	8.66 in/s (220 mm/s)	8.66 in/s (220 mm/s)
Bending speed	0.51 in/s (13 mm/s)	0.71 in/s (18 mm/s)	0.51 in/s (13 mm/s)	0.59 in/s (15 mm/s)	0.47 in/s (12 mm/s)	0.47 in/s (12 mm/s)	0.47 in/s (12 mm/s)	0.39 in/s (10 mm/s)	0.39 in/s (10 mm/s)
Return speed	6.30 in/s (160 mm/s)	7.87 in/s (200 mm/s)	6.30 in/s (160 mm/s)	7.87 in/s (200 mm/s)	5.71 in/s (145 mm/s)	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	5.12 in/s (130 mm/s)	5.12 in/s (130 mm/s)
Back gauge X stroke · speed	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 15.75 in/s (400 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 15.75 in/s (400 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)
Back gauge R stroke · speed	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)
Servo main motor	5.9 HP (4.4 kW)	5.9 HP (4.4 kW)	7.4 HP (5.5 kW)	7.4 HP (5.5 kW)	11.7 HP (8.7 kW)	14.5 HP (10.8 kW)	14.5 HP (10.8 kW)	14.5 HP (10.8 kW)	14.5 HP (10.8 kW)
Hydraulic oil tank	34 US gal (130 L)	34 US gal (130 L)	34 US gal (130 L)	34 US gal (130 L)	45 US gal (170 L)	45 US gal (170 L)	45 US gal (170 L)	45 US gal (170 L)	45 US gal (170 L)
Dimensions L × W × H	69 × 59 × 92" (1,750 × 1,500 × 2,330 mm)	85 × 59 × 92" (2,150 × 1,500 × 2,330 mm)	94 × 63 × 94" (2,400 × 1,600 × 2,400 mm)	122 × 63 × 94" (3,100 × 1,600 × 2,400 mm)	122 × 63 × 97" (3,100 × 1,600 × 2,460 mm)	148 × 87 × 106" (3,750 × 2,202 × 2,700 mm)	185 × 71 × 106" (4,700 × 1,800 × 2,700 mm)	150 × 71 × 106" (3,800 × 1,800 × 2,700 mm)	185 × 71 × 106" (4,700 × 1,800 × 2,700 mm)
Weight	7,716 lb (3,500 kg)	7,716 lb (3,500 kg)	9,259 lb (4,200 kg)	9,700 lb (4,400 kg)	12,346 lb (5,600 kg)	16,535 lb (7,500 kg)	19,180 lb (8,700 kg)	18,298 lb (8,300 kg)	23,149 lb (10,500 kg)

Bending force in US tons (metric tons in brackets); the model number is the supplier's — metric tonnage × metric bending length. Capacities vary with the V-die opening, material and sheet length: check the bending chart or ask us for the tonnage your part needs. Dimensions are overall L (along the bed) × W × H with the standard front supports; weights are reference values.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

WAD-170T/3200 – WAD-300T/6000 · 16 MODELS

CNC HYDRAULIC PRESS BRAKES, 187 – 331 US TONS × 10 – 20 FT



MODEL CNC · WAD 110T/3200 CNC PRESS BRAKE IN A ROBOT BENDING CELL



Delem DA-58T 15″ 2D graphic control with bend sequence calculation



Delem DA-66T 17″ 2D control with 3D visualisation

The same CNC press brake from 170 to 300 t: 10, 13.5, 16 and 20 ft bending lengths, 17.7 – 19.7″ throats, 7.9 – 9.8″ strokes and 18.9 – 22.4″ daylight for deep boxes, with 25 – 40 cc pumps and 13 – 21 kW servo main motors. The 220 t × 13 ft and 250 t × 13 ft machines bend 3/8″ plate the full length; the 300 t × 20 ft bends 1/2″ over 13 ft. Delem DA-53T standard, 4+1 axes with CNC crowning.

STANDARD FEATURES

- ✓ Mild steel to 3/8″ over 13 ft on the 220 t, 1/2″ over 13 ft on the 300 t (V = 8 × thickness)
- ✓ Delem DA-53T 2D touchscreen CNC control; 4 axes — Y1, Y2 (independent ram cylinders), X and R back gauge
- ✓ Electro-hydraulic servo synchronisation: Hawe (Germany) valves, linear scales on both sides, ± 0.01 mm ram repeatability
- ✓ Servo-driven main pump — the pump turns only while the ram moves: 40 – 60 % less energy than a conventional CNC brake, about 60 dB
- ✓ Servo back gauge on ball screws and linear guides, ± 0.01 mm; two stop fingers with four positioning steps
- ✓ Motorised CNC crowning (V axis) on 110 t and up; Schneider electrics; Estun servo drives
- ✓ European-style quick clamps and a segmented 2-V die with sectioned punch set (42CrMo, HRC 47); front support arms on linear rail
- ✓ Side guards, enclosed rear guard, anti-panic foot pedal with emergency stop
- ✓ CSA-approved electrical panel, 600 V 3-phase standard (208 / 240 / 480 V on request)

OPTIONAL EQUIPMENT

- + Delem DA-58T (15″ 2D), DA-66T (17″ 2D + 3D view) or DA-69T (3D) control; ESA S875, Cybelec options
- + 6-axis back gauge X1, X2, R1, R2, Z1, Z2 on ball screws; back gauge strokes to 39″ (1,000 mm)
- + DSP laser finger protection (EN 12622 CAT 4 / SIL 3) or light curtains
- + CNC sheet follower supports
- + Wila hydraulic clamping; double-sided quick clamps; Rolleri pneumatic clamps
- + Automatic angle measurement
- + Hydraulic oil cooler; automatic lubrication
- + Tandem machines on one control; robot bending cells
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS · 1 / 2

CNC HYDRAULIC PRESS BRAKES, 187 – 331 US TONS × 10 – 20 FT

CNC HYDRAULIC PRESS BRAKES · 170 – 220 T

8 models · 187 – 243 US tons · 10 – 20 ft

Model	WAD-170T/3200	WAD-170T/4100	WAD-170T/5000	WAD-170T/6000	WAD-220T/3200	WAD-220T/4100	WAD-220T/5000	WAD-220T/6000
Bending force	**187 US tons (170 t)**	**187 US tons (170 t)**	**187 US tons (170 t)**	**187 US tons (170 t)**	**243 US tons (220 t)**	**243 US tons (220 t)**	**243 US tons (220 t)**	**243 US tons (220 t)**
Bending length	**10.5 ft · 126.0" (3,200 mm)**	**13.5 ft · 161.4" (4,100 mm)**	**16.4 ft · 196.9" (5,000 mm)**	**19.7 ft · 236.2" (6,000 mm)**	**10.5 ft · 126.0" (3,200 mm)**	**13.5 ft · 161.4" (4,100 mm)**	**16.4 ft · 196.9" (5,000 mm)**	**19.7 ft · 236.2" (6,000 mm)**
Distance between columns	106.3" (2,700 mm)	141.7" (3,600 mm)	157.5" (4,000 mm)	189.0" (4,800 mm)	102.4" (2,600 mm)	141.7" (3,600 mm)	157.5" (4,000 mm)	189.0" (4,800 mm)
Throat depth	17.7" (450 mm)	17.7" (450 mm)	17.7" (450 mm)	17.7" (450 mm)	17.7" (450 mm)	17.7" (450 mm)	17.7" (450 mm)	17.7" (450 mm)
Stroke	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)
Daylight open height	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)
Approach speed	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)
Bending speed	0.39 in/s (10 mm/s)	0.39 in/s (10 mm/s)	0.39 in/s (10 mm/s)	0.39 in/s (10 mm/s)	0.35 in/s (9 mm/s)	0.35 in/s (9 mm/s)	0.35 in/s (9 mm/s)	0.35 in/s (9 mm/s)
Return speed	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	4.13 in/s (105 mm/s)	4.13 in/s (105 mm/s)	4.13 in/s (105 mm/s)	4.13 in/s (105 mm/s)
Back gauge X stroke · speed	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)
Back gauge R stroke · speed	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)
Servo main motor	17.7 HP (13.2 kW)	17.7 HP (13.2 kW)	17.7 HP (13.2 kW)	17.7 HP (13.2 kW)	22.4 HP (16.7 kW)	22.4 HP (16.7 kW)	22.4 HP (16.7 kW)	22.4 HP (16.7 kW)
Hydraulic oil tank	79 US gal (300 L)	79 US gal (300 L)	79 US gal (300 L)	79 US gal (300 L)	79 US gal (300 L)	79 US gal (300 L)	79 US gal (300 L)	79 US gal (300 L)
Dimensions L × W × H	150 × 79 × 110" (3,800 × 2,000 × 2,800 mm)	185 × 79 × 110" (4,700 × 2,000 × 2,800 mm)	248 × 79 × 124" (6,300 × 2,000 × 3,160 mm)	248 × 79 × 124" (6,300 × 2,000 × 3,160 mm)	150 × 87 × 112" (3,800 × 2,200 × 2,850 mm)	185 × 87 × 112" (4,700 × 2,200 × 2,850 mm)	220 × 87 × 117" (5,600 × 2,200 × 2,980 mm)	264 × 87 × 127" (6,700 × 2,200 × 3,220 mm)
Weight	23,810 lb (10,800 kg)	27,558 lb (12,500 kg)	29,542 lb (13,400 kg)	42,990 lb (19,500 kg)	27,558 lb (12,500 kg)	32,187 lb (14,600 kg)	38,581 lb (17,500 kg)	45,195 lb (20,500 kg)

TECHNICAL SPECIFICATIONS · 2 / 2

CNC HYDRAULIC PRESS BRAKES, 187 – 331 US TONS × 10 – 20 FT

CNC HYDRAULIC PRESS BRAKES · 250 – 300 T

8 models · 276 – 331 US tons · 10 – 20 ft

Model	WAD-250T/3200	WAD-250T/4000	WAD-250T/5000	WAD-250T/6000	WAD-300T/3200	WAD-300T/4000	WAD-300T/5000	WAD-300T/6000
Bending force	**276 US tons (250 t)**	**276 US tons (250 t)**	**276 US tons (250 t)**	**276 US tons (250 t)**	**331 US tons (300 t)**	**331 US tons (300 t)**	**331 US tons (300 t)**	**331 US tons (300 t)**
Bending length	**10.5 ft · 126.0" (3,200 mm)**	**13.1 ft · 157.5" (4,000 mm)**	**16.4 ft · 196.9" (5,000 mm)**	**19.7 ft · 236.2" (6,000 mm)**	**10.5 ft · 126.0" (3,200 mm)**	**13.1 ft · 157.5" (4,000 mm)**	**16.4 ft · 196.9" (5,000 mm)**	**19.7 ft · 236.2" (6,000 mm)**
Distance between columns	102.4" (2,600 mm)	122.0" (3,100 mm)	149.6" (3,800 mm)	189.0" (4,800 mm)	102.4" (2,600 mm)	122.0" (3,100 mm)	149.6" (3,800 mm)	189.0" (4,800 mm)
Throat depth	17.7" (450 mm)	17.7" (450 mm)	17.7" (450 mm)	17.7" (450 mm)	19.7" (500 mm)	19.7" (500 mm)	19.7" (500 mm)	19.7" (500 mm)
Stroke	9.8" (250 mm)	9.8" (250 mm)	9.8" (250 mm)	9.8" (250 mm)	9.8" (250 mm)	9.8" (250 mm)	9.8" (250 mm)	9.8" (250 mm)
Daylight open height	21.3" (540 mm)	21.3" (540 mm)	21.3" (540 mm)	21.3" (540 mm)	22.4" (570 mm)	22.4" (570 mm)	22.4" (570 mm)	22.4" (570 mm)
Approach speed	5.12 in/s (130 mm/s)	5.12 in/s (130 mm/s)	5.12 in/s (130 mm/s)	5.12 in/s (130 mm/s)	4.72 in/s (120 mm/s)	4.72 in/s (120 mm/s)	4.72 in/s (120 mm/s)	4.72 in/s (120 mm/s)
Bending speed	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)
Return speed	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	4.33 in/s (110 mm/s)	4.33 in/s (110 mm/s)	4.33 in/s (110 mm/s)	4.33 in/s (110 mm/s)
Back gauge X stroke · speed	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)	19.7" (500 mm) · 13.78 in/s (350 mm/s)
Back gauge R stroke · speed	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)	7.9" (200 mm) · 7.87 in/s (200 mm/s)
Servo main motor	22.4 HP (16.7 kW)	22.4 HP (16.7 kW)	22.4 HP (16.7 kW)	22.4 HP (16.7 kW)	28.7 HP (21.4 kW)	28.7 HP (21.4 kW)	28.7 HP (21.4 kW)	28.7 HP (21.4 kW)
Hydraulic oil tank	122 US gal (460 L)	122 US gal (460 L)	122 US gal (460 L)	122 US gal (460 L)	172 US gal (650 L)	172 US gal (650 L)	172 US gal (650 L)	172 US gal (650 L)
Dimensions L × W × H	150 × 87 × 123" (3,800 × 2,200 × 3,120 mm)	181 × 87 × 124" (4,600 × 2,200 × 3,150 mm)	220 × 85 × 124" (5,600 × 2,150 × 3,150 mm)	248 × 85 × 124" (6,300 × 2,150 × 3,150 mm)	138 × 89 × 126" (3,500 × 2,250 × 3,200 mm)	169 × 98 × 134" (4,300 × 2,500 × 3,400 mm)	209 × 98 × 134" (5,300 × 2,500 × 3,400 mm)	248 × 98 × 134" (6,300 × 2,500 × 3,400 mm)
Weight	36,376 lb (16,500 kg)	36,597 lb (16,600 kg)	45,195 lb (20,500 kg)	56,218 lb (25,500 kg)	41,447 lb (18,800 kg)	43,872 lb (19,900 kg)	57,982 lb (26,300 kg)	65,477 lb (29,700 kg)

Bending force in US tons (metric tons in brackets); the model number is the supplier's — metric tonnage × metric bending length. Capacities vary with the V-die opening, material and sheet length: check the bending chart or ask us for the tonnage your part needs. Dimensions are overall L (along the bed) × W × H with the standard front supports; weights are reference values.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

WAD-400T/4000 – WAD-1200T/8000 · 21 MODELS · TANDEM TO 60 FT

HEAVY-DUTY CNC PRESS BRAKES, 441 – 1,323 US TONS × 13 – 26 FT, AND TANDEMS



MODEL HEAVY-DUTY · HEAVY-DUTY CNC PRESS BRAKE WITH TWIN SHEET FOLLOWERS — 30 FT BENDING LENGTH



Heavy-duty CNC press brake with a CNC sheet follower table



Tandem CNC press brake — two 300 t × 13 ft machines on one control with sheet followers

For plate work, poles, towers and long profiles: 400 to 1,200 t machines with 13, 16, 20, 23 and 26 ft beds, 23.6″ throats, strokes to 15.7″ and 36″ daylight, twin pumps and twin servo motors from 800 t up, and a 38.6″ (980 mm) back gauge stroke as standard. CNC sheet followers, extra-long front supports and tandem configurations — two machines on one control bending to 60 ft — are built to order; the 3,000 t × 30 ft machine in the photos shows how far the range goes.

STANDARD FEATURES

- ✓ Twin cylinders and twin pumps from 800 t; 38.6″ (980 mm) X back gauge stroke; 11 – 15 ft bed widths
- ✓ Delem DA-53T 2D touchscreen CNC control; 4 axes — Y1, Y2 (independent ram cylinders), X and R back gauge
- ✓ Electro-hydraulic servo synchronisation: Hawe (Germany) valves, linear scales on both sides, ± 0.01 mm ram repeatability
- ✓ Servo-driven main pump — the pump turns only while the ram moves: 40 – 60 % less energy than a conventional CNC brake, about 60 dB
- ✓ Servo back gauge on ball screws and linear guides, ± 0.01 mm; two stop fingers with four positioning steps
- ✓ Motorised CNC crowning (V axis) on 110 t and up; Schneider electrics; Estun servo drives
- ✓ European-style quick clamps and a segmented 2-V die with sectioned punch set (42CrMo, HRC 47); front support arms on linear rail
- ✓ Side guards, enclosed rear guard, anti-panic foot pedal with emergency stop
- ✓ CSA-approved electrical panel, 600 V 3-phase standard (208 / 240 / 480 V on request)

OPTIONAL EQUIPMENT

- + Delem DA-58T (15″ 2D), DA-66T (17″ 2D + 3D view) or DA-69T (3D) control; ESA S875, Cybelec options
- + 6-axis back gauge X1, X2, R1, R2, Z1, Z2 on ball screws; back gauge strokes to 39″ (1,000 mm)
- + DSP laser finger protection (EN 12622 CAT 4 / SIL 3) or light curtains
- + CNC sheet follower supports
- + Wila hydraulic clamping; double-sided quick clamps; Rolleri pneumatic clamps
- + Automatic angle measurement
- + Hydraulic oil cooler; automatic lubrication
- + Tandem machines on one control; robot bending cells
- + Custom voltage: 208 V, 240 V or 480 V 3-phase
- + Extra-long front supports and CNC sheet followers for plate
- + Tandem and tridem machines to 60 ft on one control

TECHNICAL SPECIFICATIONS · 1 / 3

HEAVY-DUTY CNC PRESS BRAKES, 441 – 1,323 US TONS × 13 – 26 FT, AND TANDEMS

HEAVY-DUTY CNC PRESS BRAKES · 400 – 600 T

9 models · 441 – 661 US tons · 13 – 20 ft

Model	WAD-400T/4000	WAD-400T/5000	WAD-400T/6000	WAD-500T/4000	WAD-500T/5000	WAD-500T/6000	WAD-600T/4000	WAD-600T/5000	WAD-600T/6000
Bending force	**441 US tons (400 t)**	**441 US tons (400 t)**	**441 US tons (400 t)**	**551 US tons (500 t)**	**551 US tons (500 t)**	**551 US tons (500 t)**	**661 US tons (600 t)**	**661 US tons (600 t)**	**661 US tons (600 t)**
Bending length	**13.1 ft · 157.5″ (4,000 mm)**	**16.4 ft · 196.9″ (5,000 mm)**	**19.7 ft · 236.2″ (6,000 mm)**	**13.1 ft · 157.5″ (4,000 mm)**	**16.4 ft · 196.9″ (5,000 mm)**	**19.7 ft · 236.2″ (6,000 mm)**	**13.1 ft · 157.5″ (4,000 mm)**	**16.4 ft · 196.9″ (5,000 mm)**	**19.7 ft · 236.2″ (6,000 mm)**
Distance between columns	122.0″ (3,100 mm)	149.6″ (3,800 mm)	189.0″ (4,800 mm)	122.0″ (3,100 mm)	149.6″ (3,800 mm)	189.0″ (4,800 mm)	122.0″ (3,100 mm)	149.6″ (3,800 mm)	189.0″ (4,800 mm)
Throat depth	19.7″ (500 mm)	19.7″ (500 mm)	19.7″ (500 mm)	19.7″ (500 mm)	19.7″ (500 mm)	19.7″ (500 mm)	23.6″ (600 mm)	23.6″ (600 mm)	23.6″ (600 mm)
Stroke	11.8″ (300 mm)	11.8″ (300 mm)	11.8″ (300 mm)	11.8″ (300 mm)	11.8″ (300 mm)	11.8″ (300 mm)	12.6″ (320 mm)	12.6″ (320 mm)	12.6″ (320 mm)
Daylight open height	24.0″ (610 mm)	24.0″ (610 mm)	24.0″ (610 mm)	24.0″ (610 mm)	24.0″ (610 mm)	24.0″ (610 mm)	25.6″ (650 mm)	25.6″ (650 mm)	25.6″ (650 mm)
Approach speed	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)
Bending speed	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.37 in/s (9.5 mm/s)	0.37 in/s (9.5 mm/s)	0.37 in/s (9.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)
Return speed	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	4.33 in/s (110 mm/s)	4.33 in/s (110 mm/s)	4.33 in/s (110 mm/s)	3.35 in/s (85 mm/s)	3.35 in/s (85 mm/s)	3.35 in/s (85 mm/s)
Back gauge X stroke · speed	38.6″ (980 mm) · 7.87 in/s (200 mm/s)	38.6″ (980 mm) · 7.87 in/s (200 mm/s)	38.6″ (980 mm) · 7.87 in/s (200 mm/s)	38.6″ (980 mm) · 8.66 in/s (220 mm/s)	38.6″ (980 mm) · 7.87 in/s (200 mm/s)	38.6″ (980 mm) · 7.87 in/s (200 mm/s)	38.6″ (980 mm) · 7.87 in/s (200 mm/s)	38.6″ (980 mm) · 8.66 in/s (220 mm/s)	38.6″ (980 mm) · 7.87 in/s (200 mm/s)
Back gauge R stroke · speed	7.9″ (200 mm) · 1.57 in/s (40 mm/s)	7.9″ (200 mm) · 1.57 in/s (40 mm/s)	7.9″ (200 mm) · 1.57 in/s (40 mm/s)	7.9″ (200 mm) · 1.57 in/s (40 mm/s)	7.9″ (200 mm) · 1.57 in/s (40 mm/s)	7.9″ (200 mm) · 1.57 in/s (40 mm/s)	7.9″ (200 mm) · 1.57 in/s (40 mm/s)	7.9″ (200 mm) · 1.57 in/s (40 mm/s)	7.9″ (200 mm) · 1.57 in/s (40 mm/s)
Servo main motor	36.1 HP (26.9 kW)	36.1 HP (26.9 kW)	36.1 HP (26.9 kW)	44.3 HP (33 kW)	44.3 HP (33 kW)	44.3 HP (33 kW)	60.3 HP (45 kW)	60.3 HP (45 kW)	60.3 HP (45 kW)
Hydraulic oil tank	211 US gal (800 L)	211 US gal (800 L)	211 US gal (800 L)	201 US gal (760 L)	201 US gal (760 L)	201 US gal (760 L)	277 US gal (1050 L)	277 US gal (1050 L)	277 US gal (1050 L)
Dimensions L × W × H	169 × 106 × 138″ (4,300 × 2,700 × 3,500 mm)	209 × 106 × 138″ (5,300 × 2,700 × 3,500 mm)	248 × 106 × 138″ (6,300 × 2,700 × 3,500 mm)	169 × 106 × 138″ (4,300 × 2,700 × 3,500 mm)	209 × 106 × 138″ (5,300 × 2,700 × 3,500 mm)	248 × 106 × 142″ (6,300 × 2,700 × 3,600 mm)	169 × 130 × 154″ (4,300 × 3,300 × 3,900 mm)	209 × 130 × 154″ (5,300 × 3,300 × 3,900 mm)	248 × 130 × 154″ (6,300 × 3,300 × 3,900 mm)
Weight	54,675 lb (24,800 kg)	66,139 lb (30,000 kg)	78,264 lb (35,500 kg)	73,855 lb (33,500 kg)	79,807 lb (36,200 kg)	92,153 lb (41,800 kg)	95,019 lb (43,100 kg)	106,483 lb (48,300 kg)	123,900 lb (56,200 kg)

TECHNICAL SPECIFICATIONS · 2 / 3

HEAVY-DUTY CNC PRESS BRAKES, 441 – 1,323 US TONS × 13 – 26 FT, AND TANDEMS

HEAVY-DUTY CNC PRESS BRAKES · 800 – 1,200 T

12 models · 882 – 1,323 US tons · 13 – 26 ft · twin pumps

Model	WAD-800T/4000	WAD-800T/5000	WAD-800T/6000	WAD-800T/8000	WAD-1000T/5000	WAD-1000T/6000	WAD-1000T/7000	WAD-1000T/8000	WAD-1200T/5000	WAD-1200T/6000	WAD-1200T/7000	WAD-1200T/8000
Bending force	882 US tons (800 t)	882 US tons (800 t)	882 US tons (800 t)	882 US tons (800 t)	1,102 US tons (1000 t)	1,102 US tons (1000 t)	1,102 US tons (1000 t)	1,102 US tons (1000 t)	1,323 US tons (1200 t)	1,323 US tons (1200 t)	1,323 US tons (1200 t)	1,323 US tons (1200 t)
Bending length	13.1 ft · 157.5" (4,000 mm)	16.4 ft · 196.9" (5,000 mm)	19.7 ft · 236.2" (6,000 mm)	26.2 ft · 315.0" (8,000 mm)	16.4 ft · 196.9" (5,000 mm)	19.7 ft · 236.2" (6,000 mm)	23 ft · 275.6" (7,000 mm)	26.2 ft · 315.0" (8,000 mm)	16.4 ft · 196.9" (5,000 mm)	19.7 ft · 236.2" (6,000 mm)	23 ft · 275.6" (7,000 mm)	26.2 ft · 315.0" (8,000 mm)
Distance between columns	110.2" (2,800 mm)	145.7" (3,700 mm)	181.1" (4,600 mm)	248.0" (6,300 mm)	141.7" (3,600 mm)	181.1" (4,600 mm)	220.5" (5,600 mm)	248.0" (6,300 mm)	137.8" (3,500 mm)	177.2" (4,500 mm)	208.7" (5,300 mm)	248.0" (6,300 mm)
Throat depth	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)	23.6" (600 mm)
Stroke	12.6" (320 mm)	12.6" (320 mm)	12.6" (320 mm)	12.6" (320 mm)	15.7" (400 mm)	15.7" (400 mm)	15.7" (400 mm)	15.7" (400 mm)	15.7" (400 mm)	15.7" (400 mm)	15.7" (400 mm)	15.7" (400 mm)
Daylight open height	31.5" (800 mm)	31.5" (800 mm)	31.5" (800 mm)	31.5" (800 mm)	36.2" (920 mm)	36.2" (920 mm)	36.2" (920 mm)	36.2" (920 mm)	36.2" (920 mm)	36.2" (920 mm)	36.2" (920 mm)	36.2" (920 mm)
Approach speed	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)
Bending speed	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)
Return speed	3.54 in/s (90 mm/s)	3.54 in/s (90 mm/s)	3.54 in/s (90 mm/s)	3.54 in/s (90 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)	3.15 in/s (80 mm/s)
Back gauge X stroke · speed	38.6" (980 mm) · 8.66 in/s (220 mm/s)	38.6" (980 mm) · 8.66 in/s (220 mm/s)	38.6" (980 mm) · 8.66 in/s (220 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)	38.6" (980 mm) · 7.87 in/s (200 mm/s)
Back gauge R stroke · speed	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)	7.9" (200 mm) · 1.57 in/s (40 mm/s)
Servo main motor	2 × 36.1 HP (26.9 kW)	2 × 36.1 HP (26.9 kW)	2 × 36.1 HP (26.9 kW)	2 × 36.1 HP (26.9 kW)	2 × 44.3 HP (33 kW)	2 × 44.3 HP (33 kW)	2 × 44.3 HP (33 kW)	2 × 44.3 HP (33 kW)	2 × 60.3 HP (45 kW)	2 × 60.3 HP (45 kW)	2 × 60.3 HP (45 kW)	2 × 60.3 HP (45 kW)
Hydraulic oil tank	476 US gal (1800 L)	476 US gal (1800 L)	476 US gal (1800 L)	476 US gal (1800 L)	449 US gal (1700 L)	449 US gal (1700 L)	502 US gal (1900 L)	502 US gal (1900 L)	608 US gal (2300 L)	608 US gal (2300 L)	608 US gal (2300 L)	608 US gal (2300 L)
Dimensions L × W × H	167 × 138 × 161" (4,250 × 3,500 × 4,100 mm)	209 × 142 × 174" (5,300 × 3,600 × 4,420 mm)	248 × 142 × 169" (6,300 × 3,600 × 4,300 mm)	327 × 142 × 177" (8,300 × 3,600 × 4,500 mm)	207 × 174 × 168" (5,260 × 4,410 × 4,260 mm)	246 × 174 × 176" (6,260 × 4,410 × 4,460 mm)	288 × 174 × 184" (7,310 × 4,410 × 4,680 mm)	327 × 174 × 196" (8,300 × 4,410 × 4,980 mm)	208 × 182 × 168" (5,280 × 4,620 × 4,260 mm)	247 × 182 × 180" (6,280 × 4,620 × 4,560 mm)	287 × 182 × 191" (7,280 × 4,620 × 4,860 mm)	326 × 182 × 199" (8,280 × 4,620 × 5,060 mm)

TECHNICAL SPECIFICATIONS · 3 / 3

HEAVY-DUTY CNC PRESS BRAKES, 441 – 1,323 US TONS × 13 – 26 FT, AND TANDEMS

HEAVY-DUTY CNC PRESS BRAKES · 800 – 1,200 T (CONTINUED)

12 models · 882 – 1,323 US tons · 13 – 26 ft · twin pumps

Model	WAD-800T/4000	WAD-800T/5000	WAD-800T/6000	WAD-800T/8000	WAD-1000T/5000	WAD-1000T/6000	WAD-1000T/7000	WAD-1000T/8000	WAD-1200T/5000	WAD-1200T/6000	WAD-1200T/7000	WAD-1200T/8000
Weight	125,663 lb (57,000 kg)	145,505 lb (66,000 kg)	163,142 lb (74,000 kg)	192,904 lb (87,500 kg)	171,960 lb (78,000 kg)	194,007 lb (88,000 kg)	211,644 lb (96,000 kg)	233,690 lb (106,000 kg)	213,848 lb (97,000 kg)	233,690 lb (106,000 kg)	249,122 lb (113,000 kg)	271,168 lb (123,000 kg)

Bending force in US tons (metric tons in brackets); the model number is the supplier's — metric tonnage × metric bending length. Capacities vary with the V-die opening, material and sheet length: check the bending chart or ask us for the tonnage your part needs. Dimensions are overall L (along the bed) × W × H with the standard front supports; weights are reference values.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

WC67K-30T/1600 – WC67K/E-125T/6000 · 13 MODELS

NC HYDRAULIC PRESS BRAKES, 33 – 138 US TONS × 5 – 20 FT — TORSION BAR



MODEL NC · NOVOTECH WC67E 100T/3200 NC HYDRAULIC PRESS BRAKE — 10 FT × 110 US TONS, TORSION-BAR SYNCHRONISED, WITH THE ESTUN CONTROL



Torsion bar and the motorised X back gauge seen from the rear



Torsion-bar synchronisation of the ram — the mechanical link between the two cylinders

The simplest press brake we sell: a torsion bar keeps the two ram cylinders in step mechanically, mechanical stops set the depth and an Estun E21 control positions the back gauge and the ram for 40 stored programs. No servo valves, no linear scales — nothing that needs a technician — which is why these machines run for decades in general fabrication shops bending brackets, boxes, channels and roofing. Thirteen models from 33 tons × 5 ft to 138 tons × 20 ft; the 100 t × 10 ft and 125 t × 13 ft are the standard sizes.

STANDARD FEATURES

- ✓ Mild steel to 1/4" over 10 ft on the 100 t, 5/16" over 10 ft on the 125 t (V = 8 × thickness)
- ✓ Estun E21 NC control — programs the back gauge (X) and ram depth (Y), 40 programs × 25 steps, stroke counter; inches or millimetres
- ✓ Torsion-bar synchronised ram with mechanical depth stops — simple, rigid and easy to service
- ✓ Motorised X back gauge on ball screw and linear guide, 23.6" (600 mm) stroke; manual crowning
- ✓ Welded, stress-relieved monoblock frame machined in one setting; Rexroth-type hydraulic block; Schneider electrics
- ✓ European-style quick clamps, segmented 2-V die and sectioned punch set; front support arms
- ✓ Side and rear guards; foot pedal with emergency stop
- ✓ CSA-approved electrical panel, 600 V 3-phase standard (208 / 240 / 480 V on request)

OPTIONAL EQUIPMENT

- + Estun E300P / E310P NC control with R axis
- + Y-axis CNC upgrade (closed-loop ram) to the WAD series
- + DSP laser finger protection or light curtain
- + Sheet follower support; longer back gauge
- + Hydraulic oil cooler
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS · 1 / 2

NC HYDRAULIC PRESS BRAKES, 33 – 138 US TONS × 5 – 20 FT — TORSION BAR

NC PRESS BRAKES · 30 – 125 T

13 models · 33 – 138 US tons · 5 – 20 ft

Model	WC67K-30t/1600	WC67K/E-30t/2000	WC67K/E-40t/2500	WC67K-63t/2500	WC67K/E-80t/2500	WC67K/E-100t/2500	WC67K-100t/3200	WC67K-100t/4000	WC67K/E-125t/2500	WC67K-125t/3200	WC67K-125t/4000	WC67K/E-125t/5000	WC67K/E-125t/6000
Bending force	**33 US tons (30 t)**	**33 US tons (30 t)**	**44 US tons (40 t)**	**69 US tons (63 t)**	**88 US tons (80 t)**	**110 US tons (100 t)**	**110 US tons (100 t)**	**110 US tons (100 t)**	**138 US tons (125 t)**	**138 US tons (125 t)**	**138 US tons (125 t)**	**138 US tons (125 t)**	**138 US tons (125 t)**
Bending length	**5.2 ft · 63.0″ (1,600 mm)**	**6.6 ft · 78.7″ (2,000 mm)**	**8.2 ft · 98.4″ (2,500 mm)**	**8.2 ft · 98.4″ (2,500 mm)**	**8.2 ft · 98.4″ (2,500 mm)**	**8.2 ft · 98.4″ (2,500 mm)**	**10.5 ft · 126.0″ (3,200 mm)**	**13.1 ft · 157.5″ (4,000 mm)**	**8.2 ft · 98.4″ (2,500 mm)**	**10.5 ft · 126.0″ (3,200 mm)**	**13.1 ft · 157.5″ (4,000 mm)**	**16.4 ft · 196.9″ (5,000 mm)**	**19.7 ft · 236.2″ (6,000 mm)**
Distance between columns	51.2″ (1,300 mm)	63.0″ (1,600 mm)	79.9″ (2,030 mm)	80.7″ (2,050 mm)	80.7″ (2,050 mm)	80.7″ (2,050 mm)	98.8″ (2,510 mm)	122.0″ (3,100 mm)	80.7″ (2,050 mm)	98.8″ (2,510 mm)	122.0″ (3,100 mm)	149.6″ (3,800 mm)	189.0″ (4,800 mm)
Throat depth	7.9″ (200 mm)	7.9″ (200 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	12.6″ (320 mm)	12.6″ (320 mm)	16.5″ (420 mm)	12.6″ (320 mm)	12.6″ (320 mm)	16.5″ (420 mm)	12.6″ (320 mm)	12.6″ (320 mm)
Stroke	3.1″ (80 mm)	3.1″ (80 mm)	3.9″ (100 mm)	4.7″ (120 mm)	4.7″ (120 mm)	6.3″ (160 mm)	6.3″ (160 mm)	6.3″ (160 mm)	6.3″ (160 mm)	6.3″ (160 mm)	6.3″ (160 mm)	6.3″ (160 mm)	6.3″ (160 mm)
Daylight open height	13.2″ (335 mm)	13.2″ (335 mm)	14.0″ (355 mm)	14.6″ (370 mm)	15.0″ (380 mm)	16.9″ (430 mm)	16.9″ (430 mm)	16.9″ (430 mm)	16.9″ (430 mm)	16.9″ (430 mm)	16.9″ (430 mm)	16.9″ (430 mm)	16.9″ (430 mm)
Approach speed	4.72 in/s (120 mm/s)	5.51 in/s (140 mm/s)	4.33 in/s (110 mm/s)	3.94 in/s (100 mm/s)	4.33 in/s (110 mm/s)	3.54 in/s (90 mm/s)	3.94 in/s (100 mm/s)	4.72 in/s (120 mm/s)	3.54 in/s (90 mm/s)	3.74 in/s (95 mm/s)	4.33 in/s (110 mm/s)	4.72 in/s (120 mm/s)	5.12 in/s (130 mm/s)
Bending speed	0.67 in/s (17 mm/s)	0.67 in/s (17 mm/s)	0.59 in/s (15 mm/s)	0.39 in/s (10 mm/s)	0.39 in/s (10 mm/s)	0.30 in/s (7.5 mm/s)	0.30 in/s (7.5 mm/s)	0.30 in/s (7.5 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)
Return speed	6.30 in/s (160 mm/s)	6.30 in/s (160 mm/s)	3.54 in/s (90 mm/s)	2.76 in/s (70 mm/s)	3.15 in/s (80 mm/s)	2.76 in/s (70 mm/s)	2.76 in/s (70 mm/s)	2.76 in/s (70 mm/s)	2.56 in/s (65 mm/s)	2.56 in/s (65 mm/s)	2.56 in/s (65 mm/s)	2.56 in/s (65 mm/s)	2.56 in/s (65 mm/s)
Back gauge X stroke · speed	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)
Main motor	7.4 HP (5.5 kW)	7.4 HP (5.5 kW)	7.4 HP (5.5 kW)	7.4 HP (5.5 kW)	7.4 HP (5.5 kW)	10.1 HP (7.5 kW)	10.1 HP (7.5 kW)	10.1 HP (7.5 kW)	10.1 HP (7.5 kW)	10.1 HP (7.5 kW)	10.1 HP (7.5 kW)	10.1 HP (7.5 kW)	10.1 HP (7.5 kW)
Hydraulic oil tank	21 US gal (80 L)	26 US gal (100 L)	45 US gal (170 L)	45 US gal (170 L)	45 US gal (170 L)	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)
Dimensions L × W × H	71 × 47 × 67″ (1,800 × 1,200 × 1,700 mm)	87 × 47 × 67″ (2,200 × 1,200 × 1,700 mm)	106 × 47 × 75″ (2,700 × 1,200 × 1,900 mm)	98 × 53 × 90″ (2,500 × 1,350 × 2,282 mm)	98 × 55 × 85″ (2,500 × 1,400 × 2,150 mm)	98 × 59 × 87″ (2,500 × 1,500 × 2,200 mm)	126 × 59 × 91″ (3,200 × 1,500 × 2,300 mm)	157 × 59 × 94″ (4,000 × 1,500 × 2,400 mm)	101 × 64 × 96″ (2,570 × 1,620 × 2,450 mm)	126 × 63 × 93″ (3,200 × 1,600 × 2,350 mm)	157 × 69 × 102″ (4,000 × 1,750 × 2,590 mm)	197 × 63 × 96″ (5,000 × 1,600 × 2,450 mm)	236 × 63 × 96″ (6,000 × 1,600 × 2,450 mm)

TECHNICAL SPECIFICATIONS · 2 / 2

NC HYDRAULIC PRESS BRAKES, 33 – 138 US TONS × 5 – 20 FT — TORSION BAR

NC PRESS BRAKES · 30 – 125 T (CONTINUED)

13 models · 33 – 138 US tons · 5 – 20 ft

Model	WC67K-30t/1600	WC67K/E-30t/2000	WC67K/E-40t/2500	WC67K-63t/2500	WC67K/E-80t/2500	WC67K/E-100t/2500	WC67K-100t/3200	WC67K-100t/4000	WC67K/E-125t/2500	WC67K-125t/3200	WC67K-125t/4000	WC67K/E-125t/5000	WC67K/E-125t/6000
Weight	4,630 lb (2,100 kg)	5,071 lb (2,300 kg)	7,055 lb (3,200 kg)	9,039 lb (4,100 kg)	10,141 lb (4,600 kg)	12,346 lb (5,600 kg)	14,771 lb (6,700 kg)	18,519 lb (8,400 kg)	13,889 lb (6,300 kg)	15,653 lb (7,100 kg)	19,842 lb (9,000 kg)	25,353 lb (11,500 kg)	32,187 lb (14,600 kg)

Bending force in US tons (metric tons in brackets); the model number is the supplier's — metric tonnage × metric bending length. Capacities vary with the V-die opening, material and sheet length: check the bending chart or ask us for the tonnage your part needs. Dimensions are overall L (along the bed) × W × H with the standard front supports; weights are reference values.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

WC67K/E-160T/2500 – WC67K/E-400T/6000 · 21 MODELS

NC HYDRAULIC PRESS BRAKES, 176 – 441 US TONS × 8 – 20 FT — TORSION BAR



MODEL NC · NOVOTECH WC67E 100T/3200 NC HYDRAULIC PRESS BRAKE — 10 FT × 110 US TONS, TORSION-BAR SYNCHRONISED, WITH THE ESTUN CONTROL



Torsion bar and the motorised X back gauge seen from the rear

The torsion-bar press brake in the heavy sizes: 160 to 400 t over 8 to 20 ft, with 13.8 – 15.7″ throats, 7.9 – 9.8″ strokes and 18.9 – 22.8″ daylight, 20 – 50 cc pumps and 11 – 22 kW motors. The right machine for a shop that bends 3/8″ and 1/2″ plate in simple shapes and does not need a CNC — the E21 control still stores 40 programs and positions the back gauge and depth automatically.

STANDARD FEATURES

- ✓ Mild steel to 3/8″ over 10 ft on the 200 t, 1/2″ over 13 ft on the 300 t, 1/2″ over 20 ft on the 400 t (V = 8 × thickness)
- ✓ Estun E21 NC control — programs the back gauge (X) and ram depth (Y), 40 programs × 25 steps, stroke counter; inches or millimetres
- ✓ Torsion-bar synchronised ram with mechanical depth stops — simple, rigid and easy to service
- ✓ Motorised X back gauge on ball screw and linear guide, 23.6″ (600 mm) stroke; manual crowning
- ✓ Welded, stress-relieved monoblock frame machined in one setting; Rexroth-type hydraulic block; Schneider electrics
- ✓ European-style quick clamps, segmented 2-V die and sectioned punch set; front support arms
- ✓ Side and rear guards; foot pedal with emergency stop
- ✓ CSA-approved electrical panel, 600 V 3-phase standard (208 / 240 / 480 V on request)

OPTIONAL EQUIPMENT

- + Estun E300P / E310P NC control with R axis
- + Y-axis CNC upgrade (closed-loop ram) to the WAD series
- + DSP laser finger protection or light curtain
- + Sheet follower support; longer back gauge
- + Hydraulic oil cooler
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS · 1 / 2

NC HYDRAULIC PRESS BRAKES, 176 – 441 US TONS × 8 – 20 FT — TORSION BAR

NC PRESS BRAKES · 160 – 200 T

9 models · 176 – 220 US tons · 8 – 20 ft

Model	WC67K/E-160t/2500	WC67K-160t/3200	WC67K-160t/4000	WC67K/E-160t/5000	WC67K/E-160t/6000	WC67K-200T/3200	WC67K-200T/4000	WC67K/E-200T/5000	WC67K/E-200T/6000
Bending force	**176 US tons (160 t)**	**176 US tons (160 t)**	**176 US tons (160 t)**	**176 US tons (160 t)**	**176 US tons (160 t)**	**220 US tons (200 t)**	**220 US tons (200 t)**	**220 US tons (200 t)**	**220 US tons (200 t)**
Bending length	**8.2 ft · 98.4" (2,500 mm)**	**10.5 ft · 126.0" (3,200 mm)**	**13.1 ft · 157.5" (4,000 mm)**	**16.4 ft · 196.9" (5,000 mm)**	**19.7 ft · 236.2" (6,000 mm)**	**10.5 ft · 126.0" (3,200 mm)**	**13.1 ft · 157.5" (4,000 mm)**	**16.4 ft · 196.9" (5,000 mm)**	**19.7 ft · 236.2" (6,000 mm)**
Distance between columns	80.7" (2,050 mm)	98.8" (2,510 mm)	122.0" (3,100 mm)	149.6" (3,800 mm)	189.0" (4,800 mm)	98.8" (2,510 mm)	122.0" (3,100 mm)	149.6" (3,800 mm)	189.0" (4,800 mm)
Throat depth	13.8" (350 mm)	13.8" (350 mm)	13.8" (350 mm)	13.8" (350 mm)	13.8" (350 mm)	13.8" (350 mm)	13.8" (350 mm)	13.8" (350 mm)	13.8" (350 mm)
Stroke	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)	7.9" (200 mm)
Daylight open height	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)	18.9" (480 mm)
Approach speed	4.33 in/s (110 mm/s)	4.33 in/s (110 mm/s)	4.33 in/s (110 mm/s)	4.72 in/s (120 mm/s)	4.72 in/s (120 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)
Bending speed	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)	0.33 in/s (8.5 mm/s)
Return speed	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.56 in/s (65 mm/s)	2.56 in/s (65 mm/s)	2.56 in/s (65 mm/s)	2.56 in/s (65 mm/s)
Back gauge X stroke · speed	23.6" (600 mm) · 5.91 in/s (150 mm/s)	23.6" (600 mm) · 5.91 in/s (150 mm/s)	23.6" (600 mm) · 5.91 in/s (150 mm/s)	23.6" (600 mm) · 5.91 in/s (150 mm/s)	23.6" (600 mm) · 5.91 in/s (150 mm/s)	23.6" (600 mm) · 5.91 in/s (150 mm/s)	23.6" (600 mm) · 5.91 in/s (150 mm/s)	23.6" (600 mm) · 5.91 in/s (150 mm/s)	23.6" (600 mm) · 5.91 in/s (150 mm/s)
Main motor	14.8 HP (11 kW)	14.8 HP (11 kW)	14.8 HP (11 kW)	14.8 HP (11 kW)	14.8 HP (11 kW)	20.1 HP (15 kW)	20.1 HP (15 kW)	20.1 HP (15 kW)	20.1 HP (15 kW)
Hydraulic oil tank	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)	69 US gal (260 L)	115 US gal (435 L)	115 US gal (435 L)	115 US gal (435 L)	115 US gal (435 L)
Dimensions L × W × H	98 × 65 × 106" (2,500 × 1,650 × 2,700 mm)	126 × 65 × 110" (3,200 × 1,650 × 2,800 mm)	157 × 65 × 110" (4,000 × 1,650 × 2,800 mm)	197 × 69 × 122" (5,000 × 1,750 × 3,100 mm)	236 × 69 × 130" (6,000 × 1,750 × 3,300 mm)	126 × 65 × 110" (3,200 × 1,650 × 2,800 mm)	157 × 65 × 110" (4,000 × 1,650 × 2,800 mm)	197 × 77 × 122" (5,000 × 1,950 × 3,100 mm)	236 × 77 × 122" (6,000 × 1,950 × 3,100 mm)
Weight	18,960 lb (8,600 kg)	21,605 lb (9,800 kg)	25,353 lb (11,500 kg)	29,762 lb (13,500 kg)	36,376 lb (16,500 kg)	25,133 lb (11,400 kg)	30,203 lb (13,700 kg)	36,156 lb (16,400 kg)	49,604 lb (22,500 kg)

TECHNICAL SPECIFICATIONS · 2 / 2

NC HYDRAULIC PRESS BRAKES, 176 – 441 US TONS × 8 – 20 FT — TORSION BAR

NC PRESS BRAKES · 250 – 400 T

12 models · 276 – 441 US tons · 10 – 20 ft

Model	WC67K-250T/3200	WC67K-250T/4000	WC67K/E-250T/5000	WC67K/E-250T/6000	WC67K-300T/3200	WC67K-300T/4000	WC67K/E-300T/5000	WC67K/E-300T/6000	WC67K/E-400T/3200	WC67K/E-400T/4000	WC67K/E-400T/5000	WC67K/E-400T/6000
Bending force	**276 US tons (250 t)**	**276 US tons (250 t)**	**276 US tons (250 t)**	**276 US tons (250 t)**	**331 US tons (300 t)**	**331 US tons (300 t)**	**331 US tons (300 t)**	**331 US tons (300 t)**	**441 US tons (400 t)**	**441 US tons (400 t)**	**441 US tons (400 t)**	**441 US tons (400 t)**
Bending length	**10.5 ft · 126.0″ (3,200 mm)**	**13.1 ft · 157.5″ (4,000 mm)**	**16.4 ft · 196.9″ (5,000 mm)**	**19.7 ft · 236.2″ (6,000 mm)**	**10.5 ft · 126.0″ (3,200 mm)**	**13.1 ft · 157.5″ (4,000 mm)**	**16.4 ft · 196.9″ (5,000 mm)**	**19.7 ft · 236.2″ (6,000 mm)**	**10.5 ft · 126.0″ (3,200 mm)**	**13.1 ft · 157.5″ (4,000 mm)**	**16.4 ft · 196.9″ (5,000 mm)**	**19.7 ft · 236.2″ (6,000 mm)**
Distance between columns	102.4″ (2,600 mm)	122.0″ (3,100 mm)	149.6″ (3,800 mm)	189.0″ (4,800 mm)	102.4″ (2,600 mm)	122.0″ (3,100 mm)	149.6″ (3,800 mm)	189.0″ (4,800 mm)	98.4″ (2,500 mm)	122.0″ (3,100 mm)	149.6″ (3,800 mm)	189.0″ (4,800 mm)
Throat depth	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)	15.7″ (400 mm)
Stroke	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)	9.8″ (250 mm)
Daylight open height	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)	22.8″ (580 mm)
Approach speed	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.94 in/s (100 mm/s)	3.54 in/s (90 mm/s)	3.94 in/s (100 mm/s)	4.33 in/s (110 mm/s)	5.12 in/s (130 mm/s)	3.54 in/s (90 mm/s)	3.54 in/s (90 mm/s)	3.54 in/s (90 mm/s)	3.54 in/s (90 mm/s)
Bending speed	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.31 in/s (8 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)	0.28 in/s (7 mm/s)
Return speed	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)	2.95 in/s (75 mm/s)
Back gauge X stroke · speed	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	23.6″ (600 mm) · 5.91 in/s (150 mm/s)	33.5″ (850 mm) · 5.91 in/s (150 mm/s)	33.5″ (850 mm) · 5.91 in/s (150 mm/s)
Main motor	24.8 HP (18.5 kW)	24.8 HP (18.5 kW)	24.8 HP (18.5 kW)	24.8 HP (18.5 kW)	24.8 HP (18.5 kW)	24.8 HP (18.5 kW)	24.8 HP (18.5 kW)	24.8 HP (18.5 kW)	29.5 HP (22 kW)	29.5 HP (22 kW)	29.5 HP (22 kW)	29.5 HP (22 kW)
Hydraulic oil tank	115 US gal (435 L)	115 US gal (435 L)	115 US gal (435 L)	143 US gal (540 L)	143 US gal (540 L)	143 US gal (540 L)	143 US gal (540 L)	143 US gal (540 L)	143 US gal (540 L)	143 US gal (540 L)	145 US gal (550 L)	145 US gal (550 L)
Dimensions L × W × H	130 × 83 × 124″ (3,300 × 2,100 × 3,150 mm)	157 × 83 × 124″ (4,000 × 2,100 × 3,150 mm)	197 × 83 × 126″ (5,000 × 2,100 × 3,200 mm)	236 × 83 × 126″ (6,000 × 2,100 × 3,200 mm)	126 × 87 × 126″ (3,200 × 2,200 × 3,200 mm)	157 × 87 × 126″ (4,000 × 2,200 × 3,200 mm)	197 × 87 × 126″ (5,000 × 2,200 × 3,200 mm)	236 × 87 × 126″ (6,000 × 2,200 × 3,200 mm)	130 × 94 × 126″ (3,300 × 2,400 × 3,200 mm)	157 × 94 × 126″ (4,000 × 2,400 × 3,200 mm)	197 × 94 × 126″ (5,000 × 2,400 × 3,200 mm)	236 × 94 × 126″ (6,000 × 2,400 × 3,200 mm)
Weight	34,172 lb (15,500 kg)	38,801 lb (17,600 kg)	46,297 lb (21,000 kg)	51,809 lb (23,500 kg)	37,699 lb (17,100 kg)	41,447 lb (18,800 kg)	52,911 lb (24,000 kg)	61,729 lb (28,000 kg)	44,754 lb (20,300 kg)	52,470 lb (23,800 kg)	61,509 lb (27,900 kg)	72,752 lb (33,000 kg)

Bending force in US tons (metric tons in brackets); the model number is the supplier's — metric tonnage × metric bending length. Capacities vary with the V-die opening, material and sheet length: check the bending chart or ask us for the tonnage your part needs. Dimensions are overall L (along the bed) × W × H with the standard front supports; weights are reference values.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

LET'S FIND THE RIGHT MACHINE FOR YOUR SHOP.

Call or visit us for quotes, tooling, demonstrations, installation and service. In-stock machines ship fast from our Mississauga location.

PHONE

+1 647 526 5510

WEB & EMAIL

NovoTechMachineTools.com
info@NovoTechMachineTools.com

ADDRESS

1365 Mid-Way Blvd, Unit 26
Mississauga, ON L5T 2J5

NT NovoTech MACHINE TOOLS Inc.

Specifications subject to change without notice. Imperial values are converted from manufacturer metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16). Model numbers are manufacturer designations. Photos may show optional equipment. 7-day money-back guarantee on in-stock machines only; financing available.