NovoTech MACHINE TOOLS Inc.

PRODUCT CATALOGUE 2026

DENER MAKINA · MADE IN TURKEY · SOLD & SERVICED IN CANADA BY NOVOTECH

TUBE LASER CUTTING MACHINES

DENER E-FTL AND FTL TUBE AND PROFILE FIBER LASERS · Ø0.3″ TO 25.2″ · 3 TO 20 KW · BUNDLE LOADERS







Turkey
MADE IN TURKEY

2
MACHINE FAMILIES

1-year
WARRANTY

Canada
PARTS & TECHNICAL SUPPORT

DENER TUBE LASERS

CONTENTS

E-FTL TUBE LASERS

E-FTL tube and profile laser cutters, Ø0.3″ – 13.8″, 3 – 20 kW E-FTL 120 · 180 · 250 · 350 04

FTL HEAVY TUBE LASERS

FTL tube and profile laser cutters, Ø0.6″ – 25.2″, 3 – 20 kW FTL 250 · 350 · 500 · 640 06

Specifications subject to change without notice. Imperial values are converted from the manufacturer's metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16); metric values in brackets are the manufacturer's nominal figures. Model numbers are manufacturer designations. Photos may show optional equipment.

ABOUT NOVOTECH

YOUR CANADIAN SOURCE FOR DENER TUBE LASERS

Sales, installation, parts and technical support across Canada.

NovoTech Machine Tools Inc. supplies metalworking and fabrication machinery to job shops, fabricators, maintenance departments and manufacturers across Canada from our base in Mississauga, Ontario, Canada. Every machine in this catalogue is sold and supported locally by NovoTech — with spare parts and technical support readily available in Canada.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in Turkey with European components
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

DENER MAKINA · KAYSERI, TURKEY

FROM A BUNDLE OF TUBE TO FINISHED PARTS, WITHOUT AN OPERATOR AT THE MACHINE

A tube laser cuts round, square, rectangular and open profiles to length and cuts the holes, copes, slots and notches in them in one pass, straight from the 3D model — no saw, no drill, no notcher, no layout. Dener builds two lines: the E-FTL, with servo chucks accelerating at 1 G to 394 ft/min for tube from Ø0.3" to 13.8", and the heavy FTL for structural tube and pipe to Ø25.2" and 12 m bars weighing up to 2,600 kg. Both load from a bundle automatically, support the tube as it is cut, nest parts along the bar and unload the finished pieces; fiber sources from 3 to 20 kW and 5-axis bevel heads for weld preparations.

Dener Makina has built sheet-metal and laser machinery in Kayseri since 1974 and exports to more than 100 countries. NovoTech sells, installs and supports the machines in Canada from Mississauga, Ontario, Canada — layout for your building, installation, operator training, a CSA-approved panel, a 1-year warranty and parts stocked in Canada.

E-FTL 120 · 180 · 250 · 350

E-FTL TUBE AND PROFILE LASER CUTTERS, Ø0.3" – 13.8", 3 – 20 KW



MODEL E-FTL · DENER E-FTL TUBE LASER WITH THE AUTOMATIC BUNDLE LOADER



Dener E-FTL tube and profile fiber laser — chucks and following supports



Dener E-FTL tube laser — loading side

The fast tube laser: servo axes accelerating at 1 G move the chucks at up to 394 ft/min, cutting round, square, rectangular and open profiles from Ø0.3" to 13.8" in 7, 9 or 12 m lengths with ±0.05 mm repeatability. Four chuck sizes and 3 to 20 kW sources, with the bundle loader, following supports and tube nesting software that turn a bar of tube into finished parts without an operator at the machine.

STANDARD FEATURES

- ✓ Ø0.3 – 13.8" (8 – 350 mm) round and profile; 1 G, 394 ft/min (120 m/min)
- ✓ Tube length to 39.4 ft (12 m) with automatic bundle loader
- ✓ Fiber laser source 3 – 20 kW, autofocus cutting head
- ✓ Front and rear pneumatic chucks with automatic centring; 3D cutting head for bevels and copes on the 5-axis versions
- ✓ Automatic loader for bundles; tube supports that follow the cut; unloading table
- ✓ CNC with tube nesting and import of STEP / IGES files; cutting database
- ✓ Fume extraction through the tube; chip and slug collection
- ✓ CE safety enclosure
- ✓ CSA-approved electrical panel; 600 V with transformer

OPTIONAL EQUIPMENT

- + Bevel (3D) cutting head
- + Longer loading and unloading, 29.5 and 39.4 ft (9 / 12 m)
- + Seam detection; tapping and drilling attachments
- + Dust collector
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS

E-FTL TUBE AND PROFILE LASER CUTTERS, Ø0.3" – 13.8", 3 – 20 KW

E-FTL TUBE AND PROFILE FIBER LASERS

4 chuck sizes · Ø0.3" – 13.8" · 3 – 20 kW · 1 G

Model	E-FTL 120	E-FTL 180	E-FTL 250	E-FTL 350
Tube diameter round	**Ø0.3 – 4.7" (Ø8 – 120 mm)**	**Ø0.4 – 7.1" (Ø10 – 180 mm)**	**Ø0.6 – 9.8" (Ø15 – 250 mm)**	**Ø1.2 – 13.8" (Ø30 – 350 mm)**
Profile size square / rectangular	0.3 – 4.7" (8 – 120 mm)	0.4 – 7.1" (10 – 180 mm)	0.6 – 9.8" (15 – 250 mm)	1.2 – 13.8" (30 – 350 mm)
Laser source power options	3 / 6 / 12 / 20 kW	3 / 6 / 12 / 20 kW	3 / 6 / 12 / 20 kW	3 / 6 / 12 / 20 kW
Max. tube length and weight	23 ft, 265 lb (7 m, 120 kg)	23 ft, 529 lb (7 m, 240 kg)	23 ft, 661 lb · 29.5 ft, 970 lb · 39.4 ft, 2,646 lb (7 / 9 / 12 m, 300 / 440 / 1,200 kg)	23 ft, 1,323 lb · 29.5 ft, 2,646 lb · 39.4 ft, 3,968 lb (7 / 9 / 12 m, 600 / 1,200 / 1,800 kg)
Max. speed	394 ft/min (120 m/min)	394 ft/min (120 m/min)	262 ft/min (80 m/min)	177 ft/min (54 m/min)
Max. acceleration	1 G	1 G	1 G	1 G
Repeatability	±0.05 mm (±0.002")	±0.05 mm (±0.002")	±0.05 mm (±0.002")	±0.05 mm (±0.002")
Voltage	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer

Chuck size is the model number (250 = Ø250 mm); every chuck size is available with any of the listed laser sources. Loading length and bundle loader to suit the tube length; ask us for the cutting chart for your tube wall and material.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in Turkey with European components
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

FTL 250 · 350 · 500 · 640

FTL TUBE AND PROFILE LASER CUTTERS, Ø0.6" – 25.2", 3 – 20 KW



MODEL FTL · DENER FTL TUBE LASER — THREE-QUARTER VIEW



Dener FTL tube and profile fiber laser, 12 m — full line



Dener FTL 12 m tube laser — loader and cutting cell

The heavy tube laser: four chuck sizes from Ø250 to Ø640 mm for structural tube, pipe and beams to 25.2" across and 12 m long, up to 2,600 kg per bar on the 640 chuck and 12,000 kg on the long-bed 250 version. 3 to 20 kW sources cut wall thicknesses to 1"; the 5-axis head cuts bevels and weld preparations. For steel-construction, trailer, agricultural and equipment builders.

STANDARD FEATURES

- ✓ Ø0.6 – 25.2" (15 – 640 mm) round and profile; bars to 39.4 ft (12 m) and 5,732 lb
- ✓ 3 to 20 kW sources; 5-axis bevel head
- ✓ Fiber laser source 3 – 20 kW, autofocus cutting head
- ✓ Front and rear pneumatic chucks with automatic centring; 3D cutting head for bevels and copes on the 5-axis versions
- ✓ Automatic loader for bundles; tube supports that follow the cut; unloading table
- ✓ CNC with tube nesting and import of STEP / IGES files; cutting database
- ✓ Fume extraction through the tube; chip and slug collection
- ✓ CE safety enclosure
- ✓ CSA-approved electrical panel; 600 V with transformer

OPTIONAL EQUIPMENT

- + Bevel (3D) cutting head
- + Longer loading and unloading, 29.5 and 39.4 ft (9 / 12 m)
- + Seam detection; tapping and drilling attachments
- + Dust collector
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS

FTL TUBE AND PROFILE LASER CUTTERS, Ø0.6" – 25.2", 3 – 20 KW

FTL TUBE AND PROFILE FIBER LASERS

4 chuck sizes · Ø0.6" – 25.2" · 3 – 20 kW

Model	FTL 250	FTL 350	FTL 500	FTL 640
Tube diameter round	**Ø0.6 – 9.8" (Ø15 – 250 mm)**	**Ø1.2 – 13.8" (Ø30 – 350 mm)**	**Ø1.2 – 19.7" (Ø30 – 500 mm)**	**Ø4.7 – 25.2" (Ø120 – 640 mm)**
Profile size square / rectangular	0.6 – 9.8" (15 – 250 mm)	1.2 – 13.8" (30 – 350 mm)	1.2 – 19.7" (30 – 500 mm)	4.7 – 25.2" (120 – 640 mm)
Laser source power options	3 / 6 / 12 / 20 kW	3 / 6 / 12 / 20 kW	3 / 6 / 12 / 20 kW	3 / 6 / 12 / 20 kW
Max. tube length and weight	19.7 ft, 1,323 lb (6 m, 600 kg) · 39.4 ft, 26,455 lb (12 m, 12,000 kg)	29.5 ft, 2,205 lb (9 m, 1,000 kg) · 39.4 ft, 3,086 lb (12 m, 1,400 kg)	39.4 ft, 4,630 lb (12 m, 2,100 kg)	39.4 ft, 5,732 lb (12 m, 2,600 kg)
Max. speed	262 ft/min (80 m/min)	177 ft/min (54 m/min)	82 ft/min (25 m/min)	82 ft/min (25 m/min)
Max. acceleration	0.6 G	0.6 G	0.6 G	0.6 G
Repeatability	±0.05 mm (±0.002")	±0.05 mm (±0.002")	±0.1 mm (±0.004")	±0.1 mm (±0.004")
Voltage	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer

Chuck size is the model number (250 = Ø250 mm); every chuck size is available with any of the listed laser sources. Loading length and bundle loader to suit the tube length; ask us for the cutting chart for your tube wall and material.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in Turkey with European components
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

LET'S FIND THE RIGHT MACHINE FOR YOUR SHOP.

Call or visit us for quotes, tooling, demonstrations, installation and service. In-stock machines ship fast from our Mississauga, ON, Canada location.

PHONE

+1 647 526 5510

WEB & EMAIL

NovoTechMachineTools.com
info@NovoTechMachineTools.com

ADDRESS

1365 Mid-Way Blvd, Unit 26
Mississauga, ON L5T 2J5

NT NovoTech MACHINE TOOLS Inc.

Specifications subject to change without notice. Imperial values are converted from manufacturer metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16). Model numbers are manufacturer designations. Photos may show optional equipment. 7-day money-back guarantee on in-stock machines only; financing available.