NovoTech MACHINE TOOLS Inc.

PRODUCT CATALOGUE 2026

SENFENG LASER · MADE IN CHINA · SOLD & SERVICED IN CANADA BY NOVOTECH

AUTOMATIC PANEL BENDERS

SENFENG BDC PUSH-DOWN PANEL BENDERS 59 – 126″ · SUCTION-CUP PANEL BENDERS 47 – 59″ · 0.2 S PER BEND · ROBOT CELLS







China
MADE IN CHINA

1
MACHINE FAMILIES

1-year
WARRANTY

Canada
PARTS & TECHNICAL SUPPORT

SENFENG PANEL BENDERS

CONTENTS

BDC PANEL BENDERS

BDC automatic panel benders, 47 – 126″ bend width — Senfeng BDC1500 – BDC3200 push-down · BDC1200 / 1500 suction-cup · 6 models 04

Specifications subject to change without notice. Imperial values are converted from the manufacturer's metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16); metric values in brackets are the manufacturer's nominal figures. Model numbers are manufacturer designations. Photos may show optional equipment.

ABOUT NOVOTECH

YOUR CANADIAN SOURCE FOR SENFENG PANEL BENDERS

Sales, installation, parts and technical support across Canada.

NovoTech Machine Tools Inc. supplies metalworking and fabrication machinery to job shops, fabricators, maintenance departments and manufacturers across Canada from our base in Mississauga, Ontario. Every machine in this catalogue is sold and supported locally by NovoTech — with spare parts and technical support readily available in Canada.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in China by Senfeng Laser — CE, FDA and ETL certified
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

SENFENG LASER · JINAN, CHINA

FOUR-SIDE BENDING WITH NO TOOLING CHANGES

A panel bender clamps the blank once and forms every side — up, down, hems, box corners — in 0.2 s per bend while a manipulator turns the part: boxes, doors, enclosures, cabinets and HVAC panels in sheet to 14 ga, five to ten times faster than a press brake and without a skilled operator. The push-down BDC series bends 59 to 126″ with 13 to 16 servo axes, a 7.9″ bending height (11.8″ optional) and automatic thickness compensation; the suction-cup BDC1200 and 1500 are the light machines for door and appliance panels to 20 ga. Robot loading and unloading cells are available.

Senfeng Laser has built fiber laser machines in Jinan, Shandong, since 2004: a 1.8 million ft^2 campus, its own laser sources, cutting heads and welding guns, around 15,000 machines a year, 20 overseas branches and Senfeng Laser USA with a warehouse and service team. CE, FDA and ETL certified. NovoTech sells, installs and supports the machines in Canada from Mississauga, Ontario — layout for your building, installation, operator training, a CSA-approved panel, a 1-year warranty and parts and technical support in Canada.

BDC1500 – BDC3200 PUSH-DOWN · BDC1200 / 1500 SUCTION-CUP · 6 MODELS


BDC AUTOMATIC PANEL BENDERS, 47 – 126″ BEND WIDTH — SENFENG



MODEL BDC · SENFENG BDC2000 PUSH-DOWN AUTOMATIC PANEL BENDER — 79″ BEND WIDTH, 13 SERVO AXES



BDC series panel bender — three-quarter view from the manipulator side



Senfeng BDC2500 push-down panel bender — 98″ bend width

Senfeng's panel benders: the push-down BDC series with 13 to 16 servo axes bends mild steel to 14 ga, stainless to 16 ga and aluminum to 3/32″ at 0.2 s per bend over 59 to 126″, with a 7.9″ bending height (11.8″ optional) and a sheet manipulator that turns the blank for all four sides; the suction-cup BDC1200 and 1500 are the light machines for door and appliance panels to 20 ga. Robot loading and unloading cells are available on the 1500 to 2500.

STANDARD FEATURES

- ✓ 0.2 s per bend; 14 ga mild steel; 59 – 126″ (push-down) or 47 – 59″ (suction-cup); auxiliary tools and clamps optional
- ✓ Bus-based CNC with offline programming; automatic thickness compensation
- ✓ Safety fencing and light curtains; 208 / 240 / 480 / 600 V 3-phase 60 Hz (transformer supplied); single-phase not available

OPTIONAL EQUIPMENT

- \+ 6-axis robot loading / unloading cell (BDC1500 – 2500)
- \+ Auxiliary bending tool and clamps
- \+ 300 mm bending height

BDC PUSH-DOWN AUTOMATIC PANEL BENDERS — TECHNICAL SPECIFICATIONS

Model	BDC1500	BDC2000	BDC2500	BDC3200
Max. bending width	59.1″ (1,500 mm)	78.7″ (2,000 mm)	98.4″ (2,500 mm)	126.0″ (3,200 mm)
Max. blank size L × W	59 × 49″ (1,500 × 1,250 mm)	79 × 49″ (2,000 × 1,250 mm)	98 × 49″ (2,500 × 1,250 mm)	126 × 49″ (3,200 × 1,250 mm)
Max. bending height	7.9″ (200 mm) · 11.8″ (300 mm) optional	7.9″ (200 mm) · 11.8″ (300 mm) optional	7.9″ (200 mm) · 11.8″ (300 mm) optional	7.9″ (200 mm) · 11.8″ (300 mm) optional
Max. thickness, mild steel	14 ga (2.0 mm)	14 ga (2.0 mm)	14 ga (2.0 mm)	14 ga (2.0 mm)
Max. thickness, stainless steel	16 ga (1.5 mm)	16 ga (1.5 mm)	16 ga (1.5 mm)	16 ga (1.5 mm)
Max. thickness, aluminum	3/32″ (2.5 mm)	3/32″ (2.5 mm)	3/32″ (2.5 mm)	3/32″ (2.5 mm)
Min. thickness	0.014″ (0.35 mm)	0.014″ (0.35 mm)	0.014″ (0.35 mm)	0.014″ (0.35 mm)
Bending speed	0.2 s per bend	0.2 s per bend	0.2 s per bend	0.2 s per bend
Servo axes	13	13	13	16
Installed power	45.9 HP (34.2 kW)	48.9 HP (36.5 kW)	87.2 HP (65 kW)	107.3 HP (80 kW)
Dimensions L × W × H	173 × 78 × 108″ (4,390 × 1,980 × 2,740 mm)	196 × 106 × 116″ (4,980 × 2,690 × 2,950 mm)	224 × 125 × 120″ (5,690 × 3,180 × 3,050 mm)	259 × 157 × 129″ (6,580 × 3,990 × 3,280 mm)
Weight	28,660 lb (13,000 kg)	37,479 lb (17,000 kg)	48,502 lb (22,000 kg)	55,115 lb (25,000 kg)

TECHNICAL SPECIFICATIONS

BDC AUTOMATIC PANEL BENDERS, 47 – 126″ BEND WIDTH — SENFENG

BDC SUCTION-CUP PANEL BENDERS

2 models · 47 – 59″ bend width · thin sheet

Model	BDC1200	BDC1500
Max. bending width	47.2″ (1,200 mm)	59.1″ (1,500 mm)
Max. blank size L × W	47 × 47″ (1,200 × 1,200 mm)	59 × 49″ (1,500 × 1,250 mm)
Max. bending height	6.7″ (170 mm)	6.7″ (170 mm)
Max. thickness, mild steel	20 ga (1.0 mm)	20 ga (1.0 mm)
Max. thickness, stainless steel	22 ga (0.8 mm)	22 ga (0.8 mm)
Max. thickness, aluminum	0.05″ (1.3 mm)	0.05″ (1.3 mm)
Bending speed	0.2 s per bend	0.2 s per bend
Servo axes	10	10
Installed power	40.2 HP (30 kW)	52.3 HP (39 kW)
Dimensions L × W × H	12.1 × 5.9 × 9.8 ft (3.7 × 1.8 × 3.0 m)	13.1 × 6.5 × 10 ft (4.0 × 2.0 × 3.0 m)
Weight	19,842 lb (9,000 kg)	26,455 lb (12,000 kg)

Capacities are Senfeng's ratings; the model number is the metric bending width.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in China by Senfeng Laser — CE, FDA and ETL certified
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

LET'S FIND THE RIGHT MACHINE FOR YOUR SHOP.

Call or visit us for quotes, tooling, demonstrations, installation and service. In-stock machines ship fast from our Mississauga location.

PHONE

+1 647 526 5510

WEB & EMAIL

NovoTechMachineTools.com
info@NovoTechMachineTools.com

ADDRESS

1365 Mid-Way Blvd, Unit 26
Mississauga, ON L5T 2J5

NT NovoTech MACHINE TOOLS Inc.

Specifications subject to change without notice. Imperial values are converted from manufacturer metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16). Model numbers are manufacturer designations. Photos may show optional equipment. 7-day money-back guarantee on in-stock machines only; financing available.