NovoTech MACHINE TOOLS Inc.

PRODUCT CATALOGUE 2026

DENER MAKINA · MADE IN TURKEY · SOLD & SERVICED IN CANADA BY NOVOTECH

FIBER LASER CUTTING MACHINES

DENER GFL WITH PALLET CHANGER AND SMART FIBER LASERS WITH SHUTTLE TABLE OR SEMI-CLOSED · 5 × 10 TO 13 × 82 FT · 3 TO 40 KW







Turkey
MADE IN TURKEY

3
MACHINE FAMILIES

1-year
WARRANTY

Canada
PARTS & TECHNICAL SUPPORT

DENER FIBER LASERS

CONTENTS

GFL FIBER LASERS WITH PALLET CHANGER

GFL fiber laser cutting machines, 5 × 10 to 6.6 × 20 ft, 3 – 40 kW GFL 3015 · 4020 · 6020 · 3 – 40 kW 04

SMART FIBER LASERS

Smart fiber lasers with shuttle table, 5 × 10 to 8.5 × 41 ft, 3 – 40 kW Smart 3015 – 12526 · 6 table sizes · 3 – 40 kW 06

Smart semi-closed fiber lasers with single table, 8.2 × 20 to 13 × 82 ft, 3 – 40 kW Smart 6025 – 25040 · 7 table sizes · 3 – 40 kW 08

Specifications subject to change without notice. Imperial values are converted from the manufacturer's metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16); metric values in brackets are the manufacturer's nominal figures. Model numbers are manufacturer designations. Photos may show optional equipment.

ABOUT NOVOTECH

YOUR CANADIAN SOURCE FOR DENER FIBER LASERS

Sales, installation, parts and technical support across Canada.

NovoTech Machine Tools Inc. supplies metalworking and fabrication machinery to job shops, fabricators, maintenance departments and manufacturers across Canada from our base in Mississauga, Ontario, Canada. Every machine in this catalogue is sold and supported locally by NovoTech — with spare parts and technical support readily available in Canada.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in Turkey with European components
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

DENER MAKINA · KAYSERI, TURKEY

PRODUCTION FIBER LASERS FROM TURKEY, FROM A 5 × 10 FT SHEET TO 13 × 82 FT PLATE

A fiber laser cutting machine cuts sheet and plate from a DXF file with a focused beam — mild steel to 3/4" with 6 kW, 1" with 12 kW and 1-1/2" and beyond with 20 to 40 kW — at speeds no plasma or punch can match, with a clean edge and no tooling. Dener builds two sheet lasers: the GFL, the production machine with a stress-relieved frame, a space-frame gantry rated for 1.5 G and a pallet changer, in 5 × 10, 6.6 × 13 and 6.6 × 20 ft; and the Smart, the economy line from the same factory — with a shuttle table in six sizes from 5 × 10 to 8.5 × 41 ft, or semi-closed, with the cabin on the gantry over a single table from 8.2 × 20 to 13 × 82 ft for long plate. Fiber sources from 3 to 40 kW, Precitec or Raytools autofocus heads, nesting software and production reports on the control.

Dener Makina has built sheet-metal and laser machinery in Kayseri since 1974 and exports to more than 100 countries. NovoTech sells, installs and supports the machines in Canada from Mississauga, Ontario, Canada — layout for your building, installation, operator training, a CSA-approved panel, a 1-year warranty and parts stocked in Canada.

GFL 3015 · 4020 · 6020 · 3 – 40 KW

GFL FIBER LASER CUTTING MACHINES, 5 × 10 TO 6.6 × 20 FT, 3 – 40 KW



MODEL GFL · DENER GFL FIBER LASER CUTTING MACHINE — CLOSED CABIN, FRONT-LEFT VIEW



Dener GFL fiber laser cutting machine — three-quarter view



Dener GFL fiber laser — pallet changer with the second table out

The GFL is Dener's production sheet laser: a gantry on a stress-relieved frame accelerating at 1.5 G to 394 ft/min, with a pallet changer so the next sheet is loaded while the first is cut. Three table sizes — 5 × 10, 6.6 × 13 and 6.6 × 20 ft — with fiber sources from 3 to 40 kW, a Precitec autofocus head, nesting software and production reports on the control, and the pneumatic extraction and scrap boxes that keep the floor clean. The machine for a job shop that cuts all day.

STANDARD FEATURES

- ✓ 1.5 G acceleration, 394 ft/min (120 m/min) axis speed, ±0.03 mm positioning
- ✓ 3 to 40 kW fiber sources; 6 kW cuts 3/4" mild steel, 12 kW 1"
- ✓ Fiber laser source (IPG, Raycus or nLIGHT), Precitec or Raytools cutting head with autofocus
- ✓ Stress-relieved welded frame; space-frame bridge for high acceleration
- ✓ Shuttle table / pallet changer so loading overlaps cutting
- ✓ Pneumatic fume-extraction compartments and scrap boxes on wheels; prepared for a dust collector
- ✓ CNC control with nesting software, cutting database and production reports; remote diagnostics
- ✓ Laser-safe viewing glass; CE safety
- ✓ Chiller, air/nitrogen/oxygen assist-gas system
- ✓ CSA-approved electrical panel; 600 V with transformer

OPTIONAL EQUIPMENT

- + Automatic loading / unloading tower
- + Sheet storage automation
- + Bevel cutting head
- + Film-removal and marking functions
- + Dust collector
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS

GFL FIBER LASER CUTTING MACHINES, 5 × 10 TO 6.6 × 20 FT, 3 – 40 KW

GFL FIBER LASER CUTTING MACHINES

3 table sizes · 3 – 40 kW · pallet changer

Model	GFL 3015	GFL 4020	GFL 6020
Working area L × W nominal	**9.8 ft × 4.9 ft · 118 × 59" (3,000 × 1,500 mm)**	**13.1 ft × 6.6 ft · 157 × 79" (4,000 × 2,000 mm)**	**19.7 ft × 6.6 ft · 236 × 79" (6,000 × 2,000 mm)**
Worktable	pallet changer, 2 tables	pallet changer, 2 tables	pallet changer, 2 tables
Laser source power options	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW
Positioning accuracy	±0.03 mm (±0.0012")	±0.03 mm (±0.0012")	±0.03 mm (±0.0012")
Max. axis speed	394 ft/min (120 m/min)	394 ft/min (120 m/min)	394 ft/min (120 m/min)
Max. acceleration	1.5 G	1.5 G	1.5 G
Z-axis stroke	13.8" (350 mm)	13.8" (350 mm)	13.8" (350 mm)
Voltage	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer

The model number gives the nominal working area (3015 = 3,000 × 1,500 mm); every table size is available with any of the listed laser sources. Cutting thickness depends on the source: as a guide, 6 kW cuts 3/4" mild steel, 12 kW 1" and 20 kW 1-1/2" — ask us for the cutting chart for your material.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in Turkey with European components
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

SMART 3015 – 12526 · 6 TABLE SIZES · 3 – 40 KW

SMART FIBER LASERS WITH SHUTTLE TABLE, 5 × 10 TO 8.5 × 41 FT, 3 – 40 KW



MODEL SMART · DENER SMART LASER 6020 FIBER LASER CUTTING MACHINE WITH SHUTTLE TABLE



Dener Smart fiber laser — shuttle table out, rear view



Dener fiber laser cutting machine on the shop floor

The Smart series is the economy sheet laser from the same Turkish factory: a cabin with laser-safe glass, a shuttle table and 459 ft/min at 1 G, in six table sizes from 5 × 10 ft to a 41 ft long bed. The same fiber sources, cutting heads and software as the GFL, built to a lower price with a lighter frame and simpler cabin. Open front for the cutting area, control and remote handset.

STANDARD FEATURES

- ✓ Cabin with laser-safe viewing glass; shuttle table
- ✓ 1 G acceleration, 459 ft/min (140 m/min) axis speed, ±0.03 mm positioning
- ✓ Fiber laser source (IPG, Raycus or nLIGHT), Precitec or Raytools cutting head with autofocus
- ✓ Stress-relieved welded frame; space-frame bridge for high acceleration
- ✓ Shuttle table / pallet changer so loading overlaps cutting
- ✓ Pneumatic fume-extraction compartments and scrap boxes on wheels; prepared for a dust collector
- ✓ CNC control with nesting software, cutting database and production reports; remote diagnostics
- ✓ Laser-safe viewing glass; CE safety
- ✓ Chiller, air/nitrogen/oxygen assist-gas system
- ✓ CSA-approved electrical panel; 600 V with transformer

OPTIONAL EQUIPMENT

- + Automatic loading / unloading tower
- + Sheet storage automation
- + Bevel cutting head
- + Film-removal and marking functions
- + Dust collector
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS

SMART FIBER LASERS WITH SHUTTLE TABLE, 5 × 10 TO 8.5 × 41 FT, 3 – 40 KW

SMART FIBER LASERS WITH SHUTTLE TABLE

6 table sizes · 3 – 40 kW

Model	Smart 3015	Smart 4020	Smart 6020	Smart 6025	Smart 8025	Smart 12526
Working area L × W nominal	**9.8 ft × 4.9 ft · 118 × 59″ (3,000 × 1,500 mm)**	**13.1 ft × 6.6 ft · 157 × 79″ (4,000 × 2,000 mm)**	**19.7 ft × 6.6 ft · 236 × 79″ (6,000 × 2,000 mm)**	**19.7 ft × 8.2 ft · 236 × 98″ (6,000 × 2,500 mm)**	**26.2 ft × 8.2 ft · 315 × 98″ (8,000 × 2,500 mm)**	**41 ft × 8.5 ft · 492 × 102″ (12,500 × 2,600 mm)**
Worktable	shuttle table	shuttle table	shuttle table	shuttle table	shuttle table	shuttle table
Laser source power options	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW
Positioning accuracy	±0.03 mm (±0.0012″)	±0.03 mm (±0.0012″)	±0.03 mm (±0.0012″)	±0.03 mm (±0.0012″)	±0.03 mm (±0.0012″)	±0.03 mm (±0.0012″)
Max. axis speed	459 ft/min (140 m/min)	459 ft/min (140 m/min)	459 ft/min (140 m/min)	459 ft/min (140 m/min)	459 ft/min (140 m/min)	459 ft/min (140 m/min)
Max. acceleration	1 G	1 G	1 G	1 G	1 G	1 G
Voltage	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer

The model number gives the nominal working area (3015 = 3,000 × 1,500 mm); every table size is available with any of the listed laser sources. Cutting thickness depends on the source: as a guide, 6 kW cuts 3/4″ mild steel, 12 kW 1″ and 20 kW 1-1/2″ — ask us for the cutting chart for your material.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in Turkey with European components
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

SMART 6025 – 25040 · 7 TABLE SIZES · 3 – 40 KW

SMART SEMI-CLOSED FIBER LASERS WITH SINGLE TABLE, 8.2 × 20 TO 13 × 82 FT, 3 – 40 KW



MODEL SMART · DENER SMART SEMI-CLOSED FIBER LASER — THE CABIN TRAVELS WITH THE GANTRY OVER A LONG SINGLE TABLE



Dener Smart semi-closed fiber laser — the single table is loaded from the side; the cabin rides on the gantry

The large-format Smart: a single table from 8.2 × 20 ft to 13 × 82 ft with a semi-closed cabin that travels with the gantry over the cut, for long plates, beams and parts that do not fit a standard sheet. ±0.01 mm positioning, 246 ft/min and 3 to 40 kW sources — the 20 – 40 kW machines cut 1-1/2" plate and thicker.

STANDARD FEATURES

- ✓ Single table to 13 × 82 ft (4 × 25 m); semi-closed cabin on the gantry, loading from any side
- ✓ ±0.01 mm positioning, 246 ft/min (75 m/min), 0.6 G
- ✓ Fiber laser source (IPG, Raycus or nLIGHT), Precitec or Raytools cutting head with autofocus
- ✓ Stress-relieved welded frame; space-frame bridge for high acceleration
- ✓ Pneumatic fume-extraction compartments and scrap boxes on wheels; prepared for a dust collector
- ✓ CNC control with nesting software, cutting database and production reports; remote diagnostics
- ✓ Laser-safe viewing glass; CE safety
- ✓ Chiller, air/nitrogen/oxygen assist-gas system
- ✓ CSA-approved electrical panel; 600 V with transformer

OPTIONAL EQUIPMENT

- + Automatic loading / unloading tower
- + Sheet storage automation
- + Bevel cutting head
- + Film-removal and marking functions
- + Dust collector
- + Custom voltage: 208 V, 240 V or 480 V 3-phase

TECHNICAL SPECIFICATIONS

SMART SEMI-CLOSED FIBER LASERS WITH SINGLE TABLE, 8.2 × 20 TO 13 × 82 FT, 3 – 40 KW

SMART SEMI-CLOSED FIBER LASERS · SINGLE TABLE

7 table sizes · 3 – 40 kW

Model	Smart 6025	Smart 8025	Smart 12525	Smart 14035	Smart 16045	Smart 25031	Smart 25040
Working area L × W nominal	**19.7 ft × 8.2 ft · 236 × 98″ (6,000 × 2,500 mm)**	**26.2 ft × 8.2 ft · 315 × 98″ (8,000 × 2,500 mm)**	**41 ft × 8.2 ft · 492 × 98″ (12,500 × 2,500 mm)**	**45.9 ft × 11.5 ft · 551 × 138″ (14,000 × 3,500 mm)**	**52.5 ft × 14.8 ft · 630 × 177″ (16,000 × 4,500 mm)**	**82 ft × 10.2 ft · 984 × 122″ (25,000 × 3,100 mm)**	**82 ft × 13.1 ft · 984 × 157″ (25,000 × 4,000 mm)**
Worktable	single table, semi-closed cabin	single table, semi-closed cabin	single table, semi-closed cabin	single table, semi-closed cabin	single table, semi-closed cabin	single table, semi-closed cabin	single table, semi-closed cabin
Laser source power options	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW	3 / 6 / 12 / 20 / 30 / 40 kW
Positioning accuracy	±0.01 mm (±0.0004″)	±0.01 mm (±0.0004″)	±0.01 mm (±0.0004″)	±0.01 mm (±0.0004″)	±0.01 mm (±0.0004″)	±0.01 mm (±0.0004″)	±0.01 mm (±0.0004″)
Max. axis speed	246 ft/min (75 m/min)	246 ft/min (75 m/min)	246 ft/min (75 m/min)	246 ft/min (75 m/min)	246 ft/min (75 m/min)	246 ft/min (75 m/min)	246 ft/min (75 m/min)
Max. acceleration	0.6 G	0.6 G	0.6 G	0.6 G	0.6 G	0.6 G	0.6 G
Voltage	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer	380 V 50/60 Hz · 600 V with transformer

The model number gives the nominal working area (3015 = 3,000 × 1,500 mm); every table size is available with any of the listed laser sources. Cutting thickness depends on the source: as a guide, 6 kW cuts 3/4″ mild steel, 12 kW 1″ and 20 kW 1-1/2″ — ask us for the cutting chart for your material.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in Turkey with European components
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

LET'S FIND THE RIGHT MACHINE FOR YOUR SHOP.

Call or visit us for quotes, tooling, demonstrations, installation and service. In-stock machines ship fast from our Mississauga, ON, Canada location.

PHONE

+1 647 526 5510

WEB & EMAIL

NovoTechMachineTools.com
info@NovoTechMachineTools.com

ADDRESS

1365 Mid-Way Blvd, Unit 26
Mississauga, ON L5T 2J5

NT NovoTech MACHINE TOOLS Inc.

Specifications subject to change without notice. Imperial values are converted from manufacturer metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16). Model numbers are manufacturer designations. Photos may show optional equipment. 7-day money-back guarantee on in-stock machines only; financing available.