NovoTech MACHINE TOOLS Inc.

PRODUCT CATALOGUE 2026

NOVOTECH VALUE LINE · BUILT IN CHINA TO NORTH AMERICAN STANDARDS · SOLD & SERVICED IN CANADA BY NOVOTECH

DRILL PRESSES

GEAR-HEAD DRILL PRESSES 1 – 2″ IN STEEL WITH POWER FEED AND TAPPING · TX530 INVERTER DRILL PRESSES · TB BELT-DRIVE AND STEPLESS COLUMN DRILLS



China
MADE IN CHINA

4
MACHINE FAMILIES

1-year
WARRANTY

Canada
PARTS & TECHNICAL SUPPORT

VALUE-LINE DRILL PRESSES

CONTENTS

GEAR-HEAD DRILL PRESSES

T-25 – T-40 gear-head drill presses, 1" to 1-9/16" in steel T-25 / T-25A – T-40 · 14 models 04

T5025 · T4025 gear-head drill presses with tilting table, 1" T5025-1A – T4025H · 5 models 07

T-50 heavy gear-head drill presses, 2", and TX530 inverter drill presses T-50 – TX530A · 4 models 09

COLUMN DRILLS — BELT DRIVE AND INVERTER

TB24 · TB28 · TB36 column drills — belt drive or inverter TB24 – TB36V · 6 models 13

Specifications subject to change without notice. Imperial values are converted from the manufacturer's metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16); metric values in brackets are the manufacturer's nominal figures. Model numbers are manufacturer designations. Photos may show optional equipment.

ABOUT NOVOTECH

YOUR CANADIAN SOURCE FOR VALUE-LINE DRILL PRESSES

Sales, installation, parts and technical support across Canada.

NovoTech Machine Tools Inc. supplies metalworking and fabrication machinery to job shops, fabricators, maintenance departments and manufacturers across Canada from our base in Mississauga, Ontario, Canada. Every machine in this catalogue is sold and supported locally by NovoTech — with spare parts and technical support readily available in Canada.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

NOVOTECH VALUE LINE

DRILL PRESSES FOR THE FABRICATION AND MAINTENANCE SHOP

NovoTech's value line is our own brand: machines built in China to our specification by a maker that exports metalworking machinery to more than 70 countries, inspected before they ship and sold under NovoTech's name with a CSA-approved panel on every 3-phase machine, a 1-year warranty and parts and technical support from Mississauga, Ontario, Canada.

A drill press holds the drill square to the work and feeds it with the force and control a hand drill cannot give. The gear-head drill presses change speed through a gearbox — no belts to move — with the torque for large holes and tapping, from 1″ to 2″ in steel; the TX530 runs on a frequency inverter with a two-range gearbox; the TB column drills have a V-belt drive, or stepless speed by frequency converter on single-phase power.

T-25 / T-25A – T-40 · 14 MODELS

T-25 – T-40 GEAR-HEAD DRILL PRESSES, 1" TO 1-9/16" IN STEEL



MODEL T-25 · T-25 / T-26 GEAR-HEAD DRILL PRESS, FLOOR MODEL, WITH SPINDLE GUARD



T-25A gear-head drill press with the control box on the front



T-25C gear-head drill press with 24 V control and spindle guard switch

1 – 1-9/16" in steel

Gear-head drill presses for the fabrication and maintenance shop: eight spindle speeds through a gearbox — no belts to move — from 1" (25 mm) in steel on the T-25 to 1-9/16" (40 mm) on the T-40. Floor and bench models; the drilling head and table move up and down and the table swivels; the T-28, T-32, T-35 and T-40 add a mechanical or electric power feed; the C models a 24 V control and a spindle guard with micro-switch. Tapping is an option on most models.

STANDARD FEATURES

- ✓ Drilling capacity 1 – 1-9/16" (25 – 40 mm) in steel; MT3 or MT4 spindle
- ✓ 8 spindle speeds, about 90 – 3,600 rpm at 60 Hz
- ✓ Power feed 0.004 – 0.013"/rev on the T-28, T-32, T-35, T-40
- ✓ Two-speed motors 0.9 – 2.4 HP; 3 HP on the T-40
- ✓ Safety spindle guard; C models with 24 V control and guard micro-switch; T-25C-H with depth readout

OPTIONAL EQUIPMENT

- \+ Tapping (T-25, T-25A, T-25B, T-26, T-26B, T-28B, T-30, T-30B)

T-25 · T-26 — TECHNICAL SPECIFICATIONS

Model	T-25 / T-25A	T-25C / T-25AC	T-25C-H	T-26	T-26C / T-26AC	T-25B / T-25BC	T-26B / T-26BC
Drilling capacity in steel	**1" (25 mm)**	**1" (25 mm)**	**1" (25 mm)**	**1" (26 mm)**	**1" (26 mm)**	**1" (25 mm)**	**1" (26 mm)**
Tapping capacity, steel / cast iron	M10 / M16 (optional tapping)	M10 / M16 (optional tapping)	M10 / M16 (optional tapping)	M10 / M16 (optional tapping)	M10 / M16 (optional tapping)	M10 / M16 (optional tapping)	M10 / M16 (optional tapping)
Spindle taper	MT3	MT3	MT3	MT3	MT3	MT3	MT3
Spindle travel	**4-7/8" (125 mm)**	**4-7/8" (125 mm)**	**4-7/8" (125 mm)**	**4-7/8" (125 mm)**	**4-7/8" (125 mm)**	**4-7/8" (125 mm)**	**4-7/8" (125 mm)**
Spindle speeds	**8 speeds, 130 – 3,200 rpm at 60 Hz (105 – 2,900 rpm at 50 Hz)**	**8 speeds, 130 – 3,200 rpm at 60 Hz (105 – 2,900 rpm at 50 Hz)**	**8 speeds, 130 – 3,200 rpm at 60 Hz (105 – 2,900 rpm at 50 Hz)**	**8 speeds, 130 – 3,200 rpm at 60 Hz (105 – 2,900 rpm at 50 Hz)**	**8 speeds, 130 – 3,200 rpm at 60 Hz (105 – 2,900 rpm at 50 Hz)**	**8 speeds, 130 – 3,200 rpm at 60 Hz (105 – 2,900 rpm at 50 Hz)**	**8 speeds, 130 – 3,200 rpm at 60 Hz (105 – 2,900 rpm at 50 Hz)**
Motor	**0.9 / 1.2 HP (0.65 / 0.9 kW), two-speed**	**0.9 / 1.2 HP (0.65 / 0.9 kW), two-speed**	**0.9 / 1.2 HP (0.65 / 0.9 kW), two-speed**	**1.2 / 1.5 HP (0.9 / 1.1 kW), two-speed**	**1.2 / 1.5 HP (0.9 / 1.1 kW), two-speed**	**0.9 / 1.2 HP (0.65 / 0.9 kW), two-speed**	**1.2 / 1.5 HP (0.9 / 1.1 kW), two-speed**
Controls	Standard (A: frame with scale for down feed)	24 V control, spindle guard micro-switch	24 V control, depth readout	Standard	24 V control, spindle guard micro-switch	Bench model (BC: 24 V control)	Bench model (BC: 24 V control)
Mounting	Floor	Floor	Floor	Floor	Floor	Bench	Bench
Packing size L × W × H	66 × 22 × 28" (167 × 56 × 72 cm)	66 × 22 × 28" (167 × 57 × 72 cm)	66 × 22 × 28" (167 × 57 × 72 cm)	66 × 22 × 28" (167 × 56 × 72 cm)	66 × 22 × 28" (167 × 57 × 72 cm)	37 × 19 × 29" (94 × 48 × 73 cm)	37 × 19 × 29" (94 × 48 × 73 cm)
Weight	**419 lb (190 kg)**	**419 lb (190 kg)**	**463 lb (210 kg)**	**423 lb (192 kg)**	**423 lb (192 kg)**	**300 lb (136 kg)**	**304 lb (138 kg)**

DETAILS, COMPONENTS AND OPTIONS

T-25 – T-40 GEAR-HEAD DRILL PRESSES, 1" TO 1-9/16" IN STEEL



T-25C-H gear-head drill press with digital depth readout and wire spindle guard



T-25B / T-26B bench gear-head drill press



T-28 gear-head drill press with mechanical power feed



T-30 gear-head drill press with round swivelling table



T-32 / T-35 gear-head drill press with power feed



T-40 gear-head drill press, 1-9/16" in steel, MT4

TECHNICAL SPECIFICATIONS

T-25 – T-40 GEAR-HEAD DRILL PRESSES, 1" TO 1-9/16" IN STEEL

T-28 · T-30 · T-32 · T-35 · T-40

Gear-head drill presses, 1-1/8 to 1-9/16", with power feed

Model	T-28	T-28B	T-30	T-30B	T-32	T-35	T-40
Drilling capacity in steel	1-1/8" (28 mm)	1-1/8" (28 mm)	1-3/16" (30 mm)	1-3/16" (30 mm)	1-1/4" (32 mm)	1-3/8" (35 mm)	1-9/16" (40 mm)
Tapping capacity, steel / cast iron	M12 / M16	M12 / M16	M12 / M16	M12 / M16	M12 / M16	M14 / M18	M18 / M22
Spindle taper	MT3	MT3	MT3	MT3	MT4	MT4	MT4
Spindle travel	5-7/8" (150 mm)	5-7/8" (150 mm)	5-7/8" (150 mm)	5-7/8" (150 mm)	5-7/8" (150 mm)	5-7/8" (150 mm)	7-1/2" (190 mm)
Spindle speeds	8 speeds, 90 – 3,610 rpm at 60 Hz (75 – 3,010 rpm at 50 Hz)	8 speeds, 90 – 3,610 rpm at 60 Hz (75 – 3,010 rpm at 50 Hz)	8 speeds, 90 – 3,610 rpm at 60 Hz (75 – 3,010 rpm at 50 Hz)	8 speeds, 90 – 3,610 rpm at 60 Hz (75 – 3,010 rpm at 50 Hz)	8 speeds, 90 – 3,610 rpm at 60 Hz (75 – 3,010 rpm at 50 Hz)	8 speeds, 90 – 3,610 rpm at 60 Hz (75 – 3,010 rpm at 50 Hz)	8 speeds, 108 – 1,800 rpm at 60 Hz (90 – 1,500 rpm at 50 Hz)
Feed	Mechanical, 0.004 – 0.013"/rev (0.1 – 0.33 mm/rev)	Mechanical, 0.004 – 0.013"/rev (0.1 – 0.33 mm/rev)	Manual	Manual	Electric, 0.004 – 0.013"/rev (0.1 – 0.33 mm/rev)	Electric, 0.004 – 0.013"/rev (0.1 – 0.33 mm/rev)	Mechanical, 0.004 – 0.013"/rev (0.1 – 0.33 mm/rev)
Table	Rectangular	Rectangular (bench)	Round	Round (bench)	Round, rotary	Rectangular	Rectangular
Motor	1.2 / 1.6 HP (0.9 / 1.2 kW), two-speed	1.2 / 1.6 HP (0.9 / 1.2 kW), two-speed	1.5 / 1.7 HP (1.1 / 1.3 kW), two-speed	1.5 / 1.7 HP (1.1 / 1.3 kW), two-speed	1.7 / 2 HP (1.3 / 1.5 kW), two-speed	2 / 2.4 HP (1.5 / 1.8 kW), two-speed	3 HP (2.2 kW)
Packing size L × W × H	69 × 26 × 35" (174 × 67 × 88 cm)	29 × 19 × 46" (74 × 48 × 118 cm)	69 × 26 × 35" (174 × 67 × 88 cm)	29 × 19 × 53" (74 × 48 × 135 cm)	69 × 26 × 35" (174 × 67 × 88 cm)	69 × 26 × 35" (174 × 67 × 88 cm)	85 × 22 × 37" (217 × 57 × 93 cm)
Weight	584 lb (265 kg)	430 lb (195 kg)	562 lb (255 kg)	441 lb (200 kg)	650 lb (295 kg)	677 lb (307 kg)	761 lb (345 kg)

Metric values in brackets are the manufacturer's figures; thin sheet is given in gauge. Packing size is the shipping crate L × W × H and weight is the net weight of the machine.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

T5025-1A – T4025H · 5 MODELS

T5025 · T4025 GEAR-HEAD DRILL PRESSES WITH TILTING TABLE, 1"



MODEL T5025 · T5025-1A GEAR-HEAD DRILL PRESS WITH ROUND TABLE



T5025-3A gear-head drill press with ±50° tilting table



T4025 gear-head drill press with box column base

1" in steel

Compact gear-head drill presses for 1" (25 mm) in steel with eight speeds, a forward / reverse switch, preset drilling depth and a spindle cover with micro-switch: floor models with a round table or a table that tilts ±50°, and bench models; the H models have a 12.4" deep throat.

STANDARD FEATURES

- 1" (25 mm) in steel; MT3; 5.5" (140 mm) spindle travel
- 8 speeds, 120 – 3,480 rpm at 60 Hz; two-speed 3/4 / 1 HP motor
- Tilting table ±50° (T5025-3A, T5025H); T-slotted base
- Forward / reverse switch; preset drilling depth; spindle cover micro-switch

OPTIONAL EQUIPMENT

T5025 · T4025 — TECHNICAL SPECIFICATIONS

Model	T5025-1A	T5025-3A	T5025H	T4025	T4025H
Drilling capacity in steel	**1" (25 mm)**	**1" (25 mm)**	**1" (25 mm)**	**1" (25 mm)**	**1" (25 mm)**
Spindle taper	MT3	MT3	MT3	MT3	MT3
Spindle travel	**5-1/2" (140 mm)**	**5-1/2" (140 mm)**	**5-1/2" (140 mm)**	**5-1/2" (140 mm)**	**5-1/2" (140 mm)**
Spindle speeds	**8 speeds, 120 – 3,480 rpm at 60 Hz (100 – 2,900 rpm at 50 Hz)**	**8 speeds, 120 – 3,480 rpm at 60 Hz (100 – 2,900 rpm at 50 Hz)**	**8 speeds, 120 – 3,480 rpm at 60 Hz (100 – 2,900 rpm at 50 Hz)**	**8 speeds, 120 – 3,480 rpm at 60 Hz (100 – 2,900 rpm at 50 Hz)**	**8 speeds, 120 – 3,480 rpm at 60 Hz (100 – 2,900 rpm at 50 Hz)**
Throat (spindle to column)	**8-7/8" (225 mm)**	**8-7/8" (225 mm)**	**12-1/2" (315 mm)**	**8-7/8" (225 mm)**	**12-1/2" (315 mm)**
Spindle nose to table / base	24.4" (620 mm) / 42.3" (1,075 mm)	23.6" (600 mm) / 42.3" (1,075 mm)	26" (660 mm) / 47.2" (1,200 mm)	— / 17.5" (445 mm)	— / 17.5" (445 mm)
Table	Ø15.4" (390 mm), round	12.4 × 10.8" (315 × 275 mm), tilts ±50°	12.4 × 16.3" (315 × 415 mm), tilts ±50°	Base 12 × 11.7" (305 × 297 mm)	18.7 × 15.7" (475 × 400 mm) on the base
Mounting	Floor	Floor	Floor	Bench	Bench
Motor	**3/4 / 1 HP (0.55 / 0.75 kW), two-speed**	**3/4 / 1 HP (0.55 / 0.75 kW), two-speed**	**3/4 / 1 HP (0.55 / 0.75 kW), two-speed**	**3/4 / 1 HP (0.55 / 0.75 kW), two-speed**	**3/4 / 1 HP (0.55 / 0.75 kW), two-speed**
Packing size L × W × H	65 × 24 × 18" (166 × 60 × 46 cm)	65 × 24 × 18" (166 × 60 × 46 cm)	75 × 23 × 38" (190 × 59 × 96 cm)	43 × 20 × 30" (108 × 50 × 77 cm)	43 × 20 × 35" (108 × 50 × 90 cm)
Weight	**545 lb (247 kg)**	**549 lb (249 kg)**	**745 lb (338 kg)**	**386 lb (175 kg)**	**485 lb (220 kg)**

Metric values in brackets are the manufacturer's figures; thin sheet is given in gauge. Packing size is the shipping crate L × W × H and weight is the net weight of the machine.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

DETAILS, COMPONENTS AND OPTIONS

T5025 · T4025 GEAR-HEAD DRILL PRESSES WITH TILTING TABLE, 1”



T5025H gear-head drill press with tilting table

T-50 – TX530A · 4 MODELS

T-50 HEAVY GEAR-HEAD DRILL PRESSES, 2", AND TX530 INVERTER DRILL PRESSES



MODEL T-50 · T-50 HEAVY-DUTY GEAR-HEAD DRILL PRESS, 2" IN STEEL, 12 SPEEDS AND POWER FEED



T-50E heavy-duty drill press with 400 mm throat and swivelling table



TX530 inverter-drive drill press with two-range gearbox and coolant

To 2" in steel

The heavy end of the range: the T-50 and T-50E drill 2" (50 mm) in steel and tap M30, with twelve speeds, a three-step power feed, hardened gears and an MT4 spindle; the T-50E has a 15.7" deep throat, a 23.6 × 21.7" table that swivels and coolant built into the base. The TX530 drill presses run on a frequency inverter with a two-range gearbox — variable speed with full torque at low speed — for 1-1/4 and 1-9/16" holes and 3/4 to 1" taps, forward and reverse.

STANDARD FEATURES

- T-50 / T-50E: 2" (50 mm) in steel, 2-1/4" in cast iron; taps M30 in steel
- 12 speeds 75 – 1,525 rpm at 60 Hz; power feed 0.004 / 0.008 / 0.012"/rev
- T-50E: 15.7" (400 mm) throat, swivelling table, coolant in the base
- TX530 / TX530A: inverter speed control with high / low gear range; 3 HP; coolant; guard micro-switch
- TX530A: mechanical power feed

OPTIONAL EQUIPMENT

DETAILS, COMPONENTS AND OPTIONS

T-50 HEAVY GEAR-HEAD DRILL PRESSES, 2", AND TX530 INVERTER DRILL PRESSES



TX530A inverter-drive drill press with power feed, work light and coolant

TECHNICAL SPECIFICATIONS · 1 / 2

T-50 HEAVY GEAR-HEAD DRILL PRESSES, 2", AND TX530 INVERTER DRILL PRESSES

T-50 · T-50E

Heavy-duty gear-head drill presses, 2" in steel, 12 speeds and power feed

Model	T-50	T-50E
Drilling capacity	**2" (50 mm) in steel, 2-1/4" (58 mm) in cast iron**	**2" (50 mm) in steel, 2-1/4" (58 mm) in cast iron**
Tapping capacity	**M30 in steel, M38 in cast iron**	**M30 in steel, M38 in cast iron**
Throat (spindle to column)	**10-7/8" (275 mm)**	**15-3/4" (400 mm)**
Spindle nose to table	1-1/8 – 29-3/4" (30 – 755 mm)	1-1/8 – 24" (30 – 610 mm)
Spindle nose to base	36 – 44-3/4" (915 – 1,135 mm)	36 – 44-3/4" (915 – 1,135 mm)
Spindle stroke	7-1/8" (180 mm) power feed, 8-5/8" (220 mm) by hand	7-1/8" (180 mm) power feed, 8-5/8" (220 mm) by hand
Spindle taper	MT4	MT4
Spindle speeds	**12 speeds, 75 – 1,525 rpm at 60 Hz (60 – 1,270 rpm at 50 Hz)**	**12 speeds, 75 – 1,525 rpm at 60 Hz (60 – 1,270 rpm at 50 Hz)**
Power feed	3 steps, 0.004 / 0.008 / 0.012"/rev (0.1 / 0.2 / 0.3 mm/rev)	3 steps, 0.004 / 0.008 / 0.012"/rev (0.1 / 0.2 / 0.3 mm/rev)
Motor	**3 HP, 4-pole**	**3 HP, 4-pole**
Table	Ø20" (510 mm), 16 mm T-slots	23.6 × 21.7" (600 × 550 mm), swivels left and right, 18 mm T-slots
Table (knee) travel	19-3/4" (500 mm)	15-1/2" (395 mm)
Base size	19.7 × 35.4" (500 × 900 mm)	23.6 × 41.7" (600 × 1,060 mm)
Overall height	86.6" (2,200 mm)	88.4" (2,245 mm)
Coolant	Separate coolant unit	Built into the base
Packing size L × W × H	44 × 28 × 94" (113 × 70 × 240 cm)	49 × 30 × 96" (125 × 75 × 245 cm)
Weight	**1,455 lb (660 kg)**	**1,896 lb (860 kg)**

TECHNICAL SPECIFICATIONS · 2 / 2

T-50 HEAVY GEAR-HEAD DRILL PRESSES, 2", AND TX530 INVERTER DRILL PRESSES

TX530 · TX530A

Inverter-drive drill presses with two-range gearbox — drill and tap, forward and reverse

Model	TX530	TX530A
Drilling capacity in steel	**1-1/4" (32 mm)**	**1-9/16" (40 mm)**
Tapping capacity	**3/4" (19 mm)**	**1" (25 mm)**
Swing	12.7" (323 mm)	12.7" (323 mm)
Spindle taper	MT3	MT4
Spindle travel	**5-7/8" (150 mm)**	**5-7/8" (150 mm)**
Spindle speeds	**Variable (inverter): high range 245 – 2,000 rpm, low range 65 – 540 rpm**	**Variable (inverter): high range 245 – 2,000 rpm, low range 65 – 540 rpm**
Feed	Manual	Mechanical power feed
Spindle nose to table / base	20.9" (530 mm) / 46.5" (1,180 mm)	23.8" (605 mm) / 45.3" (1,150 mm)
Quill / column diameter	Ø3" (75 mm) / Ø4-1/2" (115 mm)	Ø3" (75 mm) / Ø4-1/2" (115 mm)
Table size	22 × 18.7" (560 × 475 mm), 16 mm T-slots	22 × 18.7" (560 × 475 mm), 16 mm T-slots
Base size	27.1 × 19.1" (688 × 486 mm), T-slotted, with coolant return	27.1 × 19.1" (688 × 486 mm), T-slotted, with coolant return
Motor	**3 HP (2.2 kW)**	**3 HP (2.2 kW)**
Packing size L × W × H	37 × 25 × 79" (95 × 64 × 200 cm)	38 × 26 × 90" (96 × 65 × 229 cm)
Weight	**750 lb (340 kg)**	**842 lb (382 kg)**

Metric values in brackets are the manufacturer's figures; thin sheet is given in gauge. Packing size is the shipping crate L × W × H and weight is the net weight of the machine.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

TB24 – TB36V · 6 MODELS

TB24 · TB28 · TB36 COLUMN DRILLS — BELT DRIVE OR INVERTER



MODEL TB · TB36 BELT-DRIVE INDUSTRIAL COLUMN DRILL



TB36V inverter-drive column drill with coolant



TB24 belt-drive column drill with work light

15/16 – 1-5/16" in steel

Industrial column drills with a V-belt drive and a quality motor, a digital speed display, forward / reverse, a precisely finished table with cross T-slots, a large base plate, an adjustable chuck guard and a work light, for 15/16 to 1-5/16" (24 – 34 mm) in steel. The V models run on a frequency converter for stepless speed control — up to 6,500 rpm — on single-phase power, with coolant on the TB28V and TB36V.

STANDARD FEATURES

- 24, 28 and 34 mm (15/16, 1-1/8 and 1-5/16") in steel; MT2, MT3, MT4
- TB: 7 – 16 belt speeds; TB...V: stepless 35 – 6,500 rpm by frequency converter, 1-phase
- Digital speed display; forward / reverse; easy tool change
- T-slotted table and base; adjustable chuck guard; work light
- Coolant on the TB28V and TB36V

OPTIONAL EQUIPMENT

TB24 · TB28 · TB36 — TECHNICAL SPECIFICATIONS

Model	TB24	TB28	TB36
Drilling capacity in steel	**15/16" (24 mm)**	**1-1/8" (28 mm)**	**1-5/16" (34 mm)**
Spindle travel	**3-3/8" (85 mm)**	**4-1/8" (105 mm)**	**6-1/4" (160 mm)**
Spindle taper	MT2	MT3	MT4
Spindle speeds	**7 speeds, 360 – 4,200 rpm**	**16 speeds, 120 – 4,250 rpm**	**9 speeds, 130 – 4,940 rpm**
Throat (spindle to column)	6-1/2" (165 mm)	7-7/8" (200 mm)	11-1/4" (285 mm)
Table size	11 × 11.8" (280 × 300 mm)	13.4 × 14.2" (340 × 360 mm)	15.7 × 19.7" (400 × 500 mm)
Spindle to table / base, max	20.3" (515 mm) / 26.8" (681 mm)	33.8" (858 mm) / 50" (1,270 mm)	31.1" (790 mm) / 50" (1,270 mm)
Column diameter	3-1/8" (80 mm)	3-5/8" (92 mm)	4-1/2" (115 mm)
Motor	**1 HP (750 W), 3-phase**	**1.1 HP (850 W), 3-phase**	**2 / 3 HP (1.5 / 2.2 kW), 3-phase**
Overall height	46.1" (1,170 mm)	68.9" (1,750 mm)	76" (1,930 mm)
Packing size L × W × H	33 × 17 × 52" (83 × 43 × 132 cm)	40 × 26 × 76" (101 × 65 × 192 cm)	43 × 26 × 83" (110 × 67 × 210 cm)
Weight	**265 lb (120 kg)**	**441 lb (200 kg)**	**794 lb (360 kg)**

DETAILS, COMPONENTS AND OPTIONS

TB24 · TB28 · TB36 COLUMN DRILLS — BELT DRIVE OR INVERTER



TB24V inverter-drive column drill with digital speed display



TB28 belt-drive column drill



TB28V inverter-drive column drill with coolant

TECHNICAL SPECIFICATIONS

TB24 · TB28 · TB36 COLUMN DRILLS — BELT DRIVE OR INVERTER

TB24V · TB28V · TB36V

Inverter-drive industrial column drills, stepless speed, 1-phase

Model	TB24V	TB28V	TB36V
Drilling capacity in steel	**15/16" (24 mm)**	**1-1/8" (28 mm)**	**1-5/16" (34 mm)**
Spindle travel	**3-3/8" (85 mm)**	**4-1/8" (105 mm)**	**6-1/4" (160 mm)**
Spindle taper	MT2	MT3	MT4
Spindle speeds	**Stepless, 100 – 4,400 rpm**	**Stepless, 35 – 6,100 rpm**	**Stepless, 40 – 6,500 rpm**
Throat (spindle to column)	6-1/2" (165 mm)	7-7/8" (200 mm)	11-1/4" (285 mm)
Table size	11 × 11.8" (280 × 300 mm)	13.4 × 14.2" (340 × 360 mm)	15.7 × 19.7" (400 × 500 mm)
Spindle to table / base, max	19.5" (495 mm) / 26.8" (681 mm)	30.1" (765 mm) / 47.2" (1,200 mm)	31.1" (790 mm) / 50" (1,270 mm)
Column diameter	3-1/8" (80 mm)	3-5/8" (92 mm)	4-1/2" (115 mm)
Coolant	—	Standard	Standard
Motor	**2 HP (1.5 kW), 1-phase**	**2 HP (1.5 kW), 1-phase**	**3 HP (2.2 kW), 1-phase**
Overall height	46.1" (1,170 mm)	68.9" (1,750 mm)	76" (1,930 mm)
Packing size L × W × H	33 × 17 × 52" (83 × 43 × 132 cm)	40 × 26 × 76" (101 × 65 × 192 cm)	43 × 26 × 83" (110 × 67 × 210 cm)
Weight	**265 lb (120 kg)**	**441 lb (200 kg)**	**794 lb (360 kg)**

Metric values in brackets are the manufacturer's figures; thin sheet is given in gauge. Packing size is the shipping crate L × W × H and weight is the net weight of the machine.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Built in China to North American standards
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

LET'S FIND THE RIGHT MACHINE FOR YOUR SHOP.

Call or visit us for quotes, tooling, demonstrations, installation and service. In-stock machines ship fast from our Mississauga, ON, Canada location.

PHONE

+1 647 526 5510

WEB & EMAIL

NovoTechMachineTools.com
info@NovoTechMachineTools.com

ADDRESS

1365 Mid-Way Blvd, Unit 26
Mississauga, ON L5T 2J5

NT NovoTech MACHINE TOOLS Inc.

Specifications subject to change without notice. Imperial values are converted from manufacturer metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16). Model numbers are manufacturer designations. Photos may show optional equipment. 7-day money-back guarantee on in-stock machines only; financing available.