NovoTech MACHINE TOOLS Inc.

PRODUCT CATALOGUE 2026

NOVOTECH PREMIUM LINE · MADE IN TURKEY · SOLD & SERVICED IN CANADA BY NOVOTECH

PIPE BENDERS AND WELDING POSITIONERS

TB 34 / TB 42 MANDREL-LESS PIPE BENDERS · WP 100 / WP 300 TILTING WELDING POSITIONERS





Turkey
MADE IN TURKEY

3
MACHINE FAMILIES

1-year
WARRANTY

Canada
PARTS & TECHNICAL SUPPORT

PIPE BENDERS AND WELDING POSITIONERS

CONTENTS

MANDREL-LESS PIPE BENDERS

TB 34 electric mandrel-less pipe bender, 1" NPS pipe TB 34 · 1 model 04

TB 42 hydraulic mandrel-less pipe bender, 1-1/4" NPS pipe TB 42 · 1 model 05

WELDING POSITIONERS

WP 100 · WP 300 tilting welding positioners, 220 – 661 lb WP 100 · WP 300 · 2 models 07

Specifications subject to change without notice. Imperial values are converted from the manufacturer's metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16); metric values in brackets are the manufacturer's nominal figures. Model numbers are manufacturer designations. Photos may show optional equipment.

ABOUT NOVOTECH

YOUR CANADIAN SOURCE FOR PIPE BENDERS AND WELDING POSITIONERS

Sales, installation, parts and technical support across Canada.

NovoTech Machine Tools Inc. supplies metalworking and fabrication machinery to job shops, fabricators, maintenance departments and manufacturers across Canada from our base in Mississauga, Ontario, Canada. Every machine in this catalogue is sold and supported locally by NovoTech — with spare parts and technical support readily available in Canada.

INCLUDED WITH EVERY NOVOTECH MACHINE

- ✓ Made in Turkey for NovoTech's premium line — with European components
- ✓ CSA-approved electrical panel
- ✓ 1-year warranty
- ✓ 7-day money-back guarantee
  in-stock machines only
- ✓ Spare parts & technical support
  readily available in Canada
- ✓ Order today with just 10% down
  0% down financing available
- ✓ Installation and training available

NOVOTECH PREMIUM LINE · MADE IN TURKEY

SIMPLE, SOLID MACHINES FOR THE PIPE AND WELDING SHOP

NovoTech's premium-line pipe benders and welding positioners are built in Turkey to our specification. The TB 34 and TB 42 are simple mandrel-less pipe benders with a digital angle readout and a brake motor that holds the bend, and the WP 100 and WP 300 tilting welding positioners turn round parts under the torch at 1 – 5.5 rpm, foot-pedal controlled.

NovoTech sells, installs and supports its premium-line pipe benders and welding positioners in Canada from Mississauga, Ontario, Canada — dies chosen for your parts, installation, operator training, a CSA-approved panel on three-phase machines, a 1-year warranty and parts and technical support in Canada.

TB 34 · 1 MODEL

TB 34 ELECTRIC MANDREL-LESS PIPE BENDER, 1" NPS PIPE



MODEL TB · NOVOTECH TB 34 ELECTRIC MANDREL-LESS PIPE BENDER WITH DIGITAL ANGLE READOUT



Street furniture, bike racks and serpentine tube bent on the TB 34



Safety barrier bent from pipe on the TB 34

1" NPS pipe · Ø1-5/16" × 11 ga to 180° · digital angle readout · 198 lb

A bench-size electric pipe bender for 1" NPS pipe and Ø1-5/16" × 11 ga tube to 180°: a gear-reduced drive turns the bend die at 1.9 rpm, a digital readout shows the angle and stops the bend where you set it, and a brake motor holds the angle so spring-back does not creep into the part. 198 lb with detachable carrying handles — it goes to the work — and one die set in your pipe size is included. Street furniture, bike racks, safety barriers and handrail parts.

STANDARD FEATURES

- ✓ Bends pipe and tube to Ø1-5/16" × 11 ga (Ø34 × 3 mm) — 1" NPS — up to 180°, minimum radius 3 × tube Ø
- ✓ Digital readout; the bend angle can be limited from the readout for repeat parts
- ✓ Gearbox-driven power transmission; brake motor prevents bending errors from spring-back
- ✓ Durable steel body; detachable carrying handles for moving it around the shop
- ✓ 1 set of pipe bending dies included
- ✓ CSA-approved electrical panel; 600 V 3-phase with transformer (208 / 240 / 480 V on request)

OPTIONAL EQUIPMENT

- + Pipe dies in custom sizes
- + Custom voltage: 208 V, 240 V, 480 V or 600 V 3-phase

TB 34 — TECHNICAL SPECIFICATIONS

Model	TB 34
Max. bending capacity OD × wall, to 180°	**1" NPS pipe · Ø1-5/16" × 11 ga (Ø34 × 3 mm)**
Min. bending radius centreline	**3 × tube Ø**
Control	**Digital angle readout with angle limit · brake motor**
Output speed	1.9 rpm
Motor power	0.7 HP (0.55 kW)
Dimensions L × W × H	28 × 10 × 18" (720 × 260 × 460 mm)
Weight	**198 lb (90 kg)**

Capacity is mild steel pipe or tube with the matching die set; one die set in the size you order is included.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

TB 42 · 1 MODEL


TB 42 HYDRAULIC MANDREL-LESS PIPE BENDER, 1-1/4" NPS PIPE



MODEL TB · NOVOTECH TB 42 HYDRAULIC MANDREL-LESS PIPE BENDER



Pipe bent to a U on the TB 42



TB 42 pipe bending dies on the top plate

17 US ton hydraulic · 1-1/4" NPS pipe · Ø1-5/8" × 11 ga · digital readout

A 17-ton hydraulic pipe bender in a closed steel cabinet: the cylinder pushes the former through the pipe or tube between two wing dies on the top plate, a manual angle switch and digital readout set the bend, and the speed is adjustable. 1-1/4" NPS pipe and Ø1-5/8" × 11 ga tube; free holes in the plate take special dies for section, flat and solid bar. One set of pipe bending dies included, 485 lb.

STANDARD FEATURES

- ✓ Tube bending capacity to Ø1-5/8" × 11 ga (Ø42 × 3 mm) — 1-1/4" NPS pipe
- ✓ 17 US ton (15 t) hydraulic cylinder, 5.9" stroke, adjustable speed
- ✓ Manual adjustable angle switch with digital readout
- ✓ Free holes in the top plate for special tools; steel welded frame
- ✓ One set of pipe bending dies included
- ✓ CSA-approved electrical panel; 600 V 3-phase with transformer (208 / 240 / 480 V on request)

OPTIONAL EQUIPMENT

- + Sets of pipe, tube, section or solid bar dies to the required size
- + Custom voltage: 208 V, 240 V, 480 V or 600 V 3-phase

TB 42 — TECHNICAL SPECIFICATIONS

Model	TB 42
Max. bending capacity OD × wall	**1-1/4" NPS pipe · Ø1-5/8" × 11 ga (Ø42 × 3 mm)**
Max. force at 2,900 psi (200 bar)	17 US ton (15 t)
Control	**Digital readout · manual angle switch · adjustable speed**
Maximum stroke	5.9" (150 mm)
Working speed	0.79 in/s (20 mm/s)
Oil tank	4 US gal (15 L)
Motor power	1.5 HP (1.1 kW)
Dimensions L × W × H	18 × 39 × 39" (450 × 1,000 × 1,000 mm)
Weight	**485 lb (220 kg)**

Capacity is mild steel pipe or tube with the matching die set; one die set in the size you order is included.

Custom voltage available: 208 V, 240 V, 480 V or 600 V 3-phase.

DETAILS, COMPONENTS AND OPTIONS

TB 42 HYDRAULIC MANDREL-LESS PIPE BENDER, 1-1/4" NPS PIPE



TB 42 control panel with digital readout, emergency stop and joystick

WP 100 · WP 300 · 2 MODELS

WP 100 · WP 300 TILTING WELDING POSITIONERS, 220 – 661 LB



MODEL WP · NOVOTECH WP 300 TILTING WELDING POSITIONER WITH SLOTTED TURNTABLE AND CONTROL BOX



NovoTech WP 100 compact tilting welding positioner



WP 300 with a custom perforated work plate for welding fixtures

220 – 661 lb · 360° at 1 – 5.5 rpm · 90 – 120° tilt · foot pedal

A welding positioner turns the part under the torch, so a round weld is laid in one continuous pass in the flat position instead of being stopped and restarted around the part. NovoTech's premium-line WP 100 carries 220 lb on a Ø13-3/4″ table that tilts 120°; the WP 300 carries 661 lb on a Ø18-7/8″ table that tilts 90°. The table turns 360° at 1 to 5.5 rpm, set on the control box and run from the standard foot pedal; T-slots take clamps and fixtures, and a Ø6-1/4″ or Ø7-7/8″ lathe chuck or a custom fixture plate (WP 300) is available. Single-phase 220 V.

STANDARD FEATURES

- ✓ Adjustable tilt angle for easy positioning of the part — 120° (WP 100) or 90° (WP 300), right or left
- ✓ Adjustable turning speed, 1 – 5.5 rpm, for a steady travel speed under the torch
- ✓ Standard foot pedal; control box with speed and direction
- ✓ T-slotted turntable (M10) for clamps and fixtures
- ✓ Runs on single-phase 220 V

OPTIONAL EQUIPMENT

- + Ø6-1/4″ (160 mm) or Ø7-7/8″ (200 mm) 3-jaw lathe chuck
- + Custom work plate for welding fixtures (WP 300)

WP 100 · WP 300 — TECHNICAL SPECIFICATIONS

Model	WP 100	WP 300
Nominal load capacity table horizontal	**220 lb (100 kg)**	**661 lb (300 kg)**
Load capacity, table tilted table vertical	110 lb (50 kg)	331 lb (150 kg)
Table diameter	**Ø13-3/4″ (350 mm)**	**Ø18-7/8″ (480 mm)**
Table rotation	**360° · 1 – 5.5 rpm, variable**	**360° · 1 – 5.5 rpm, variable**
Tilt	**120°, right – left**	**90°, right – left**
Turntable motor	0.33 HP (0.25 kW)	0.5 HP (0.37 kW)
Power supply	220 V 1-phase	220 V 1-phase
T-slots	M10 × 12	M10 × 12
Dimensions L × W × H	22 × 26 × 15″ (550 × 650 × 370 mm)	25 × 29 × 22″ (640 × 740 × 550 mm)
Weight	**99 lb (45 kg)**	**209 lb (95 kg)**

Nominal load is a centred part on the horizontal table; with the table tilted the WP 100 carries 110 lb and the WP 300 331 lb. Metric values in brackets are the manufacturer's figures.

Single-phase 220 V supply — no three-phase power needed.

LET'S FIND THE RIGHT MACHINE FOR YOUR SHOP.

Call or visit us for quotes, tooling, demonstrations, installation and service. In-stock machines ship fast from our Mississauga, ON, Canada location.

PHONE

+1 647 526 5510

WEB & EMAIL

NovoTechMachineTools.com
info@NovoTechMachineTools.com

ADDRESS

1365 Mid-Way Blvd, Unit 26
Mississauga, ON L5T 2J5

NT NovoTech MACHINE TOOLS Inc.

Specifications subject to change without notice. Imperial values are converted from manufacturer metric data and rounded: thin sheet in gauge (ga), plate and capacities in common fractions (1/2, 1/4, 1/8, 1/16). Model numbers are manufacturer designations. Photos may show optional equipment. 7-day money-back guarantee on in-stock machines only; financing available.