PROJECT VAJRA: AUTOMATED INTELLIGENT DEFENCE AGENT OF CYBERSECURITY

Mohd Danish Ansari
Department of CSE
Alliance University
Bengaluru, Karnataka
dmohdbtech23@ced.alliance.edu.in

Arpit Kumar
Department of CSE
Alliance University
Bengaluru,Karnataka
karpitbtech23@ced.alliance.edu.in

Akshat Srivastava
Department of CSE
Alliance University
Bengaluru,Karnataka
sakshatbtech23@ced.alliance.edu.in

Soumya Ranjan Pradhan
Department of CSE
Alliance University
Bengaluru,Karnataka
rsoumyabtech23@ced.alliance.edu.in

Abstract*—As digital transformation accelerates, Distributed Denial of Service (DDoS) attacks remain a primary threat to critical infrastructure. Traditional, static defence mechanisms are increasingly outmatched by the high-volume and polymorphic nature of modern multi-vector assaults. This paper introduces Project Vajra, an autonomous cyber defence platform engineered to bridge the widening gap between attack sophistication and defensive capability. The system utilizes a hybrid artificial intelligence core that synergizes machine learning pattern recognition with deep-seated hierarchical insights from deep learning. By performing real-time analysis of network flow features—including packet velocity, IP entropy, and protocol behaviour—the system identifies malicious signatures with high fidelity. The core innovation lies in its native integration with Continuous Integration and Continuous Deployment (CI/CD) pipelines, transforming the tool into an evolving digital immune system. This architecture enables automated model retraining and validation to counter emerging zero-day threats with zero downtime.

Experimental evaluations demonstrate a detection accuracy exceeding 98% and a near-instantaneous mitigation response. Project Vajra provides a resilient, adaptive framework for securing modern online services against evolving cyber threats.

***Keywords*—Distributed Denial of Service (DDoS), Machine Learning, Deep Learning, DevSecOps, Cybersecurity.**

I. INTRODUCTION

The contemporary digital landscape is characterized by constant connectivity, yet this interconnectedness creates profound vulnerabilities. Distributed Denial of Service (DDoS) attacks continue to be one of the most devastating threats to online service availability, capable of generating attack volumes that can overwhelm even the most robust network architectures. The fundamental challenge in DDoS mitigation is the speed and variety of modern attacks. Traditional security tools, such as signature-based Intrusion Detection Systems (IDS) and static firewalls, are fundamentally reactive; they rely on known patterns of previous attacks and fail to adapt to the high-velocity, polymorphic nature of modern threats that mimic legitimate traffic.

Project Vajra is introduced as an intelligent, next-generation cyber defence tool designed to act as a "digital immune system." Its feasibility is rooted in the convergence of two powerful technological forces: the predictive intelligence of machine learning (ML) and the responsive agility of modern DevOps. The system moves beyond the "block-or-allow" binary logic of traditional firewalls. By utilizing a hybrid model that integrates deep learning for anomaly detection and machine learning for classification, Project Vajra analyses multi-dimensional signatures in real-time, effectively distinguishing botnet activity from organic human behaviour. A critical problem in AI-driven security is "model atrophy"—the degradation of a model's effectiveness over time as attackers modify their strategies. Project Vajra addresses this by integrating its AI core into a CI/CD pipeline. This acts as a digital nervous system, allowing for the automatic retraining, testing, and redeployment of models as new threats are identified in the wild. This approach shifts the security paradigm from manual incident response to continuous, automated adaptation.

II. LITERATURE REVIEW

A. Limitations

Existing research on AI-driven DDoS mitigation highlights significant gaps that restrict practical application in high-velocity environments. A primary limitation is "model atrophy," where AI models lose effectiveness as attackers evolve, yet most current systems lack a framework for automated, real-time logic updates. Furthermore, high-accuracy deep learning models often carry excessive computational costs, making them unsuitable for real-time edge deployment or resource-constrained IoT infrastructures. Many studies rely on outdated benchmark datasets like NSL-KDD, which fail to represent the polymorphic nature of modern zero-day assaults. Additionally, traditional defense infrastructures are often too rigid, relying on manual intervention which is too slow to respond to attacks that can cripple services in mere seconds.

B. Scope of the Project

Project Vajra addresses these research gaps by developing an autonomous, self-evolving defence platform that synergizes a hybrid AI core with a modern DevOps CI/CD pipeline. The system scope encompasses:

- Real-Time Adaptive Detection: Utilizing statistical, behavioural, and volumetric analysis of network flows to identify subtle attack signatures.
- Continuous Learning: Native CI/CD integration allows for the automatic logging of novel threats and the subsequent retraining and hot-swapping of models without system downtime.
- Scalable Automated Mitigation: Interfaces directly with network hardware to apply surgical mitigation rules (e.g., BGP Flowspec) in under 60 seconds.
- Network-Level Specialization: Focuses on volumetric and protocol-based DDoS, with an architecture designed to process traffic volumes exceeding 100 Gbps.

While application-level threats like SQL injection are outside the current scope, the project provides a robust foundation for securing critical infrastructure through a scalable, user-facing monitoring dashboard.

III. SYSTEM DESIGN

The system design of Project Vajra defines how the autonomous defense platform processes, learns, and neutralizes DDoS threats with high fidelity and zero manual intervention. It follows a modular, multi-stage pipeline covering data acquisition, intelligent analysis, automated response, and continuous deployment. This section outlines the problem definition and the modular system architecture, highlighting how hybrid AI models and CI/CD integration enable Project Vajra to deliver a resilient digital immune system.

A. Problem Definition


The rapid expansion of internet-facing services and IoT devices has created an unprecedented attack surface for Distributed Denial of Service (DDoS) attacks. These attacks are no longer simple floods but are sophisticated, multi-vector assaults that adapt to evade traditional defences. Conventional rule-based systems are infeasible at the scale and speed of modern botnets, while static AI models suffer from "model atrophy"—a degradation in effectiveness as attackers shift strategies over time. Furthermore, manual intervention by security teams is too slow to respond to attacks that can cripple critical infrastructure in mere seconds. Project Vajra is designed to bridge this gap by providing an autonomous cyber defense platform capable of real-time multi-dimensional analysis and self-evolution. The goal is to create an intelligent system that can distinguish between botnets and organic human behavior, apply surgical mitigation, and automatically retrain its logic to counter novel zero-day threats.

B. System Architecture

The Project Vajra system is built on a distributed multi-stage architecture that integrates high-velocity telemetry processing with an adaptive hybrid AI core and a robust DevSecOps loop.

1. Data Acquisition and Preprocessing: Collects high-velocity network telemetry (NetFlow, sFlow) and raw packet headers from key network junctions. This module filters irrelevant "noisy" traffic and sessionizes data into time-windowed traffic flows ready for analysis.
2. Real-Time Feature Extraction: Converts cleaned flows into mathematical representations, calculating statistical (packet/byte rates), protocol-based (SYN/ACK ratios), and behavioral features (IP entropy). This generates a multi-dimensional vector (80-120 dimensions) for every network flow.
3. Hybrid AI Core (Detection Engine): Implements a two-pronged analysis strategy. An unsupervised Autoencoder (AE) calculates reconstruction errors to identify zero-day anomalies, while a Random Forest (RF) classifier identifies known attack signatures through ensemble voting.
4. Continuous Integration and Retraining: When the system identifies high-confidence novel threats, the feature vectors are automatically logged. This triggers a CI/CD pipeline that Pulls new data, re-trains the core models using SMOTE for class balancing, and validates performance against a "golden" test set.
5. Automated Mitigation and Deployment: Upon detection, the system interfaces with network hardware via a vendor-agnostic API to apply surgical rules (e.g., BGP Flowspec) in under 60 seconds. Newly validated models are promoted via Kubernetes to the inference engine, enabling hot-swapping with zero system downtime.

This architecture ensures that the defensive intelligence remains current and resilient against the evolving threat landscape through a closed-loop digital nervous system.



C. Mathematical Foundation

The core of Project Vajra relies on reconstruction error for anomaly detection and ensemble voting for classification.

1. Unsupervised Anomaly Detection (Autoencoder)

For an input vector x, the encoder f_θ and decoder g_ϕ *are* defined as:

$$h=f_\theta(x)$$

$$x\sim=g_\phi(h)$$

The system calculates the Reconstruction Error using Mean Squared Error (MSE). If the error exceeds threshold τ, the flow is flagged as an anomaly:

$$L(x,\tilde{x}) = \frac{1}{n}\sum_{i=1}^{n}(x_i - \tilde{x_i})^2$$

2. Supervised Classification (Random Forest)

The Random Forest classifier C_{RF} consists of a collection of M decision trees. The final classification is determined by a majority vote:

$$\bar{r_n}(X) = \frac{1}{M}\sum_{m=1}^{M} r_n(X,\Theta_m)$$

The quality of splits is evaluated using the Gini Index:

$$Gini(T) = 1 - \sum_{i=1}^{J} p_i^2$$

where p_i is the probability that a selected case belongs to class C_i.

IV. System Implementation

Project Vajra is implemented as a distributed, containerized platform.

A. Hardware and Software Requirements

Hardware: Minimum NVIDIA RTX 3060 (6GB VRAM) for training, server-grade CPU (Intel Xeon/AMD EPYC) and 8GB RAM for deployment.

Software: Python 3.9+, PyTorch/TensorFlow for AI frameworks, and Jenkins/Docker for CI/CD pipeline orchestration.

B. Module-wise Architecture Implementation

The implementation of Project Vajra is subdivided into eight specialized modules that form a continuous defence-and-learning loop:

1. Data Acquisition and Preprocessing Module: This module utilizes network Tap/SPAN ports and log collectors (Filebeat, Logstash) to ingest NetFlow/sFlow datagrams. It normalizes timestamps and sessionizes traffic using a Kafka buffering system to manage data bursts during high-volume floods.

2. Real-Time Feature Extraction Module: Implements statistical calculations for flow parameters such as Packets Per Second (PPS) and Bytes Per Second (BPS). It engineers advanced behavioural features, specifically calculating source/destination IP entropy and protocol flag ratios (SYN/FIN) to highlight DDoS patterns.

3. Feature Integration and Normalization Module: Concatenates disparate feature vectors and applies scaling to ensure zero-mean and unit-variance. It handles missing values through mean imputation to maintain model stability during packet loss events.

4. Hybrid AI Core (Detection Module): The implementation employs a two-pronged logic. The unsupervised Autoencoder learns the "manifold of normality" from benign traffic, while a Random Forest classifier is optimized via ensemble pruning to identify known DDoS signatures with high confidence.

5. Model Training and Validation Module: Manages the offline pipeline, utilizing Synthetic Minority Over-sampling Technique (SMOTE) to address class imbalance. It employs Bayesian optimization for hyperparameter tuning and versions model checkpoints using Data Version Control (DVC).

6. Real-Time Inference Engine: Built with NVIDIA Triton or FastAPI, this engine loads serialized model files (.pkl/.pt) and provides sub-millisecond predictions. It supports "hot-swapping," allowing the CI/CD pipeline to update detection logic without service interruption.

7. Mitigation and Dashboard Module: Acts on malicious classifications by generating BGP Flowspec rules or firewall ACLs via a vendor-agnostic API. A React-based dashboard provides Security Operations Centre (SOC) analysts with real-time charts of network health.

8. CI/CD and Model Retraining Module: This "adaptive loop" automatically triggers retraining when the Anomaly Logger captures a threshold of novel threats. It pulls new data, re-validates the model, and promotes successful candidates to Kubernetes production clusters.

V. RESULTS AND DISCUSSION

The performance of Project Vajra was evaluated using benchmark datasets (CIC-DDoS2019, UNSW-NB15, and NSL-KDD) alongside live network traffic. The results confirm that the hybrid AI model provides superior performance compared to individual detection components.

A. Detection Performance Analysis

On the CIC-DDoS2019 dataset, the system achieved a detection accuracy of 98.8% with an F1-score of 98.5% and a low False Positive Rate (FPR) of 0.22%. Similar high performance was observed with the UNSW-NB15 dataset (98.2% accuracy) and the NSL-KDD dataset (99.1% accuracy). In live production testing, the system maintained an accuracy of 98.5% with a 0.25% FPR, which effectively minimizes alert fatigue for security analysts. The synergy of the unsupervised Autoencoder and supervised Random Forest allows the system to accurately identify zero-day threats while maintaining high confidence for known attack vectors.

B. Real-Time Mitigation and Scalability

Evaluation in simulated real-time environments showed that Project Vajra processes high-velocity traffic with minimal latency. For standard volumetric attacks (UDP Flood), the total response time—from detection to rule deployment—was 3.3 seconds. Protocol-based attacks (SYN Flood) were mitigated in 4.3 seconds. More complex zero-day anomalies identified by the Autoencoder required 18.7 seconds for full mitigation, representing a significant improvement over traditional manual intervention time.

C. Adaptive Learning and Drift Resilience

A critical finding is the system's resilience against model drift. In static systems, accuracy typically degrades as attackers modify their profiles. The integration of the CI/CD pipeline enabled Project Vajra to restore accuracy from a 75% degraded state back to 98% within 30 minutes of identifying a novel attack signature. This adaptive learning loop ensures that the defensive intelligence remains current without manual human intervention.

VI. CONCLUSION AND FUTURE SCOPE

The Project Vajra initiative represents a transformative answer to Distributed Denial of Service (DDoS) attacks. By synergizing advanced hybrid AI with modern DevOps CI/CD pipelines, the platform provides a truly scalable, adaptive, and automated defence system that moves beyond static, outdated guards. What sets this project apart is its self-evolving architecture, which cuts the time to stop an attack from hours to seconds.

Future work will focus on integrating Graph Neural Networks (GNNs) and Transformer-based architectures to better detect complex, multi-stage assaults. Additionally, the framework will be expanded to include federated learning, enabling organizations to share threat intelligence securely without exposing sensitive network telemetry. Adding explainable ai (xai) features will further improve transparency for security analysts in high-stakes environments.

REFERENCES

[1] M. Seufert *et al.*, "Marina: Realizing ML-Driven Real-Time Network Traffic Monitoring at Terabit Scale," *IEEE Trans. Netw. Serv. Manag.*, vol. 21, no. 3, pp. 2773–2790, Jun. 2024.

[2] N. Alugunuri *et al.*, "AI for continuous security in DevOps (DevSecOps): Integrating machine learning into CI/CD pipelines," *Int. J. Intell. Syst. Appl. Eng.*, vol. 11, no. 6s, pp. 45–58, 2023.

[3] J. Bhayo *et al.*, "Towards a machine learning-based framework for DDOS attack detection in software-defined IoT (SD-IoT) networks," *Eng. Appl. Artif. Intell.*, vol. 123, p. 106432, 2023.

[4] M. Bensaoud and V. Kalita, "Hybrid deep learning model for DDoS detection," *J. Netw. Comput. Appl.*, vol. 202, p. 103348, 2022.

[5] S. Sapkota *et al.*, "DDoS in multi-controller SDN: Optimized controller placement and ML-based IDS," *Telecommun. Syst.*, vol. 84, pp. 121–135, 2023.

[6] M. Nawaz *et al.*, "Lightweight DDoS detection for IoT using extra trees classifier," *Sensors*, vol. 22, no. 18, p. 6965, 2022.

[7] R. Sriraman and S. Ra, "End-to-end security for DevOps: Holistic Slide-Block framework," *J. Inf. Syst. Eng. Manag.*, vol. 9, no. 1, p. em2341, 2024.

[8] H. Mehmood *et al.*, "Optimized DL for DDoS in SDN using CNN-MLP and SHAP," *J. Comput. Netw. Eng.*, vol. 15, no. 2, pp. 88–104, 2023.

[9] D. C. Santhosh and M. Sambath, "ML model comparison for DDoS using Modified XGBoost," *Eng. Appl. Artif. Intell.*, vol. 89, p. 104521, 2020.

[10] N. Rajan and A. Aravindhar, "Real-time hybrid CNN-LSTM model with IP traceback for DDoS detection in SDN," *Secur. Commun. Netw.*, vol. 2021, p. 5532104, 2021.

[11] B. Sumukh and S. Sandhya, "Comparative analysis of ML and DL models for DDoS detection," *Int. J. Eng. Adv. Technol.*, vol. 9, no. 4, pp. 2110–2115, 2020.

[12] A. Rahman *et al.*, "Efficient ML for DDoS in SDN with RYU controller integration," *Comput. Netw. Secur.*, vol. 31, no. 1, pp. 45–60, 2025.

[13] K. Tallam *et al.*, "Analysis of CyberSentinel: An emergent threat detection system for AI security," *Proc. AI Secur. Conf.*, 2024.

[14] M. Sambath *et al.*, "Analysis of an efficient real time DDoS detection model using machine learning algorithms," *Int. J. Mach. Learn.*, vol. 12, no. 2, pp. 112–125, 2022.

[15] H. U. Khan *et al.*, "AI-driven cybersecurity framework for software development based on the ANN-ISM paradigm," *Nature Res. Comput. Sci.*, vol. 1, p. 14, 2021.

[16] L. P. Rongali *et al.*, "Integrating AI and DevOps practices to develop cybersecurity frameworks for utility infrastructure," *J. Informatics Educ. Res.*, vol. 5, no. 2, pp. 310–325, 2025.