When computers call the shots — a systematic review exploring the impact of AI in high-stakes decision-making

Nataly R. Panczyk[a], Majdi I. Radaideh[a,1]

[a]*Department of Nuclear Engineering and Radiological Sciences, University of Michigan, 2355 Bonisteel Blvd., Ann Arbor, 48109, Michigan, USA*
[b]*Department of Computer Science and Engineering, University of Michigan, 2260 Hayward Street, Ann Arbor, 48109, Michigan, USA*

Abstract

While applications abound for the modern surge of artificial-intelligence (AI)-based technologies, we owe special care to those in which *human lives are at stake*. Perilously, AI advances faster than the regulations that protect us from it. As such, in this review, **we explore the impact of AI on high-stakes decision-making.** Though reviews have attempted adjacent analyses before, none have effectively targeted safety-critical industries or considered the relation between AI developers, users, and regulators. To address these gaps, we conduct a systematic literature review. We cast a wide net in our search of two databases, Web of Science and Scopus, then filter with a series of criteria that qualify a system's sensitivity, decision-making framework, and risk. After distilling our initial pool of 1,135 papers retrieved on December 15, 2025 into a final subset of 72 reports, we identify critical features of AI systems and industry implementation practices that demonstrate: 1) the safety risks of using AI in high-stakes decision-making, 2) how we can mitigate these risks, and 3) how we can assign responsibility for AI-based decisions. We perform a quality assessment, including risk of bias, on each study in our final corpus to ensure adequate rigor of retrieved material. We extract categorical and binary data from the articles reviewed to provide quantitative trends towards the types of AI used across the industries considered and the expertise of the end-user of these applications, as well as the decision-making time those users are allotted. We also perform a qualitative analysis of the trends described in these studies, on a per-industry basis.

A key finding of our review is that, contrary to popular broad calls for

increasing model interpretability and explainability, we find these features only useful in specific safety-critical scenarios– when the user has both the *expertise and time* to review a model output. Such cases do not require regulation to authorize user trust. Counterintuitively, overregulation in these scenarios may obstruct expert oversight in the United States. Alternatively, when expertise or time is limited, validation (*not* explanation) techniques and robust regulation *must* authorize user trust.

A major limitation of this review is the heterogeneity of the industries our final subset of studies considers. Nearly 60% of our final subset consisted of medical papers, whereas only about 8% consisted of aviation, and a single paper evaluated manufacturing. Therefore, while we reasonably expect the findings of this report to be consistent across applications, we cannot guarantee it. Still, this review bridges the gap among developers, users, and regulators regarding decision-making in safety-critical AI applications and offers specific recommendations for policy and future work based on its findings.

This work was funded by both the U.S. Nuclear Regulatory Commission and the U.S. National Science Foundation.

Keywords: AI-Informed Decision-Making, Sensitive Industries, Systematic Literature Review, AI Regulation

---

1. Introduction

There is no more critical time to evaluate the safety risks that artificial intelligence (AI) poses to our most sensitive industries than when governments are actively devising strategies to regulate AI [1]. To properly mitigate these risks, we need to understand how these systems are applied, who uses them, and the level of autonomy they have. This may include applications like AI-assisted surgery [2], self-piloted cargo planes [3], and autonomous vehicles [4]. Then, by evaluating the gaps between developers, users, and regulators, we can piece together a more complete picture of the high-stakes AI environment and appropriately recommend safeguards.

Other authors have attempted to characterize this landscape in the past, but have missed key features. For example, Wang and Chung [5] conduct a systematic literature review of AI in safety-critical industries, but fail to target specific industries, do not distinguish between validation and explanation, and neglect the impact of regulation. Additionally, Bach et al. [6]

conduct a systematic literature review of human-AI interaction in safety-critical industries, but again, make broad calls for explainability without considering the application, fail to discuss validation methods, do not target specific industries, and miss the mark in establishing trust frameworks.

To fill this gap, we conduct a systematic literature review on AI-based decision-making in sensitive industries. Our review seeks to answer two research questions:

1. *What is the impact of AI on high-stakes decision-making?*
2. *What are the safety risks of using AI to make decisions in sensitive industries?*

These questions highlight distinguishing features of AI-based decision-making from traditional methods. Likewise, answers would provide insight for both governmental agencies and engineers to mitigate evident shortcomings of this high-impact technology.

1.1. Novelty

As seen in [5] and [6], the "black box" nature of AI tends to take the brunt of the blame for model mistakes and induced accidents. While calls for transparency are all in good faith, we argue that a broad "explainability-based" solution may not suit all applications. This review establishes the differences between those applications through a generalizable framework by considering a variety of industries.

While the safety outcomes we consider all include some threat to human health or safety, the diversity of these industries means that use of AI may risk the health of one to many individuals with low to high probability. This variety supports the generalizability of our conclusions, with some caveats stemming from the heterogeneity of our final corpus. Aside from the size of the affected population and the likelihood of an incident, the applications include variety in *who* interacts directly with the AI system in question and the time they have to decide (or intervene). Our study brings novelty to the field by extracting key qualities of sensitive industries, understanding how AI affects outcomes based on those qualities, and identifying how those interactions impact safety, trust, and liability. Further, we make recommendations for regulators, users, and developers based on these findings.




Figure 1: Directed acyclic graph showing automatic search workflow.

2. Method

This review prioritizes reproducibility and, therefore, collects documents in a systematic and automated way. In this section, we describe our steps in detail, but those seeking to replicate our methodology can find specifics in our code repository. This review was not registered, but follows guidelines of Preferred Reporting Items for Systematic Reviews and Meta-Analyses (PRISMA) [7]. As such, we include the PRISMA 2020 checklist and PRISMA Abstract extension checklist [7] and the Synthesis Without Meta-analysis (SWiM) checklist [8] in Supplemental Materials.

2.1. Query Term Compilation

After determining our research questions, we define a set of key terms using the Population, Intervention, Comparison, Outcome (PICO) methodology [9] and use the Cartesian product of these terms (one from each category) to generate relevant search queries. We use APIs for the two databases, Scopus and Web of Science, to run these queries via a Python workflow, storing all resulting papers. Then, we remove duplicates based on digital object identifier (DOI), and merge the results of both database searches into a combined bibliography. Figure 1 shows a visual representation of this workflow.

Critical to actually making these queries is defining the lists of keywords that comprise them. We start by defining our *population* terms.

We can organize the population terms we decided to include in this search into five major groups:

- autonomous driving,
- aviation,
- energy and industrial processes,
- medical technology and pharmaceuticals, and
- nuclear and radiation.

We selected these groups for their highly sensitive nature, their propensity to use AI, and their regulatory authorities. This includes oversight by the National Highway Traffic Safety Administration (NHTSA), the Federal Aviation Administration (FAA), the Occupational Health and Safety Administration (OSHA), the Food and Drug Administration (FDA), and the U.S. Nuclear Regulatory Commission (NRC) in the United States. Although we mention these agencies explicitly, our review also considers regulation across international borders, including oversight from the EU, the United Kingdom, and Japan.

Though incomplete, we prioritize the industries listed above as a representative set in our analysis. In determining our search terms, we tried to avoid cases that address risks *not imminently* related to human health and safety (e.g., financial or environmental risks); we will discuss this further when we consider our exclusion criteria. The population search terms we include in our querying are shown in Table 1. In general, we will synthesize the results of this review by industry.

After population, we must consider our *intervention* terms. We determined this group by compiling a list of AI-related terms that would likely appear in any AI-based decision-making model. This includes words and phrases like "machine learning," "neural networks," and "language models." In our full query, which we describe later in this section, we use the search operator `W/5` and `NEAR/5` for Scopus and Web of Science, respectively, to pair each intervention term in Table 1 with the wildcard term "decision*". In lieu of a mere `AND` operator, these operators require the word "decision" and its derivatives to be within five words of the AI-intervention term. The objective of this pairing is to return articles that use AI to either make or inform some kind of decision. The intervention search terms we include in our querying are shown in Table 1.

Finally, we consider our *outcome* terms. Our research question focuses on the impact of AI-based decision-making on safety outcomes in sensitive

industries. Thus, our outcome terms focus on safety, specifically, on risks to human health. We include general terms like "incident," "accident," and "near miss," as well as more industry-specific terms, like "misdiagnos*" and "operating experience." To capture any failures that led to official infractions, we included several regulation-specific terms, too, like "FDA recall*" and "OSHA citation." We do not include highly broad terms like "hazard" or "risk" because we found such terms to yield an unmanageably large volume of results not necessarily relevant to safety-critical applications during our query term development process. We acknowledge this as a limitation of our search strategy. We also do not consider *comparison* terms in the search term compilation, but we do exclude certain kinds of comparisons during screening (i.e., AI vs AI instead of traditional method vs AI). Table 1 shows a complete list of outcome terms used in our querying.

Table 1: Search terms used to produce Cartesian-product-based queries

Population Terms	**Intervention Terms**	**Outcome Terms**
aerospace	"machine learning"	accident*
aviation	ML	"near miss*"
aircraft	"neural network*"	injur*
airport	"language model*"	failure*
"autonomous driving"	computer vision	"adverse event*"
"autonomous vehicle*"	automated	malfunction
self-driving	"deep learning"	fatalit*
automotive*	"artificial intelligence"	misdiagnos*
energy	AI	harm
"power grid*"		"operating experience*"
"electric grid*"		"OSHA citation*"
chemical		"FDA recall*"
petroleum		"NHTSA investigation*"
nuclear		incident*
radiation		"close call*"
"medical device*"		violation*
"medical equipment"		"enforcement action*"
"diagnostic device*"		
"imaging device*"		
"surgical robot*"		
"implantable device*"		
drug*		
"patient safety"		
pharmaceutical*		
radiotherapy		
"clinical trial*"		

Note: Asterisks (*) indicate truncation wildcards.

2.2. Search Process

We searched two databases, Scopus and Web of Science, for all articles containing our three primary search terms in their title, abstract, or keywords. We imposed two additional requirements: that the papers be published after 2014 and not include 2014, and that the papers be either journal articles or conference papers from the top five AI conferences as listed by Google Scholar Metrics [10]. While we assume journal articles will cover most domains, some relevant computer science only appears in conference papers. This conference paper subset includes *Neural Information Processing Systems* (NEURIPS), the *International Conference on Learning Representations* (ICLR), the *International Conference on Machine Learning* (ICML), the *AAAI Conference of Artificial Intelligence* (AAAI), and the *International Joint Conference on Artificial Intelligence* (IJCAI). We created this subset by combining a paper type of `conference proceedings` and that conference proceeding containing one of the five acronyms listed above. If this search identifies an additional conference, we will exclude that paper during the abstract screening phase.

We combined our search terms into the following query search:

```
TITLE-ABS-KEY ( {population term} ) AND TITLE-ABS-KEY (
{intervention AI term} within five words of {decision*})
AND TITLE-ABS-KEY ( {outcome term} ) AND PUBLICATION YEAR
AFTER 2014 AND (DOCUMENT TYPE(article) OR (DOCUMENT TYPE(conference
proceeding) AND {conference subset}))
```

Note: the query format above matches Scopus syntax most closely, but is intended for demonstrative purposes only. We show our exact query structure in the code repository. The final set of articles considered for this analysis was pulled from both Scopus and Web of Science on **December 15, 2025**.

After searching the full set of queries in both Scopus and Web of Science, merging the results into a single database and removing duplicates based on DOI, we generated a single bibliographic file in the `.bib` format. We then loaded the bibliographic information into Zotero [11].

2.3. Screening Process

Following the PRISMA methodology [7], we perform the screening process in two phases: title and abstract screening, and full-text review. A single reviewer screened all records for both phases. During the abstract screening,

we followed the inclusion/exclusion criteria shown in Table 2, conservatively keeping articles solely based on their titles and abstracts. The purpose of this phase is to quickly remove all articles that absolutely do not meet our criteria, while keeping any that may. During the abstract screening, this mainly involved removing articles that focused on outcomes that were not threats to human health or safety.

We excluded many articles during this phase because they fell under the category of "predictive maintenance," which we define as using AI to reduce the frequency of scheduled maintenance. By design, these studies focus on reducing costs and, at best, have no impact on safety. Systems can conservatively avoid the worst-case safety impacts by following their original maintenance schedule. Note that when AI is used to predict equipment failures without reducing maintenance frequency (e.g., ML-based alarms), we do not consider this predictive maintenance and include these studies in our review.

While these threats are dangerous, we also excluded papers that focused on cybersecurity and thus did not pose an immediate threat to human health. To maintain our scope, we focused on physical and immediate threats. Future work, however, should consider security risks of AI-based decision-making.

We also created exclusion criteria to define "AI." Because we sought to consider regulatory approaches to AI in this analysis, we drew the line at pure linear regression-based models and IF/ELSE-type logic models, since these algorithms are already widely accepted. Finally, we excluded any reviews that were non-systematic, any articles that were retracted, any ethics-based papers without a clear application to the AI technology or use of AI technology in their target domain, and any papers not written in English. To assist with our screening process, we used Covidence, a website designed for systematic reviews [12]. We did not track case-by-case reasons for exclusion during the abstract screening phase. As shown in Figure 2, we excluded 479 articles in this phase, yielding 151 articles for the full-text review process.

Table 2: Inclusion and exclusion criteria used for abstract screening phase.

	Inclusion	Exclusion
Population	Sensitive technology (e.g., nuclear, aviation) Medical studies, emphasizing equipment, devices, and drugs	Finance Human resources (even if health related) Cybersecurity
Intervention	AI-informed decision-making (with any degree of autonomy)	Simple flow chart or IF/ELSE logic Linear regression models
Comparison	Human evaluation Deterministic method	ML-ML comparison (with exceptions)
Outcome	Incidents, accidents, and failures Threat to human health Regulatory compliance violations	Non-threat to human health risks Financial risks or economic losses Cyber or other security risks
Other	Peer-reviewed journal articles Select conference papers	Non-systematic review papers Retracted articles Ethics without application Not written in English Published before 2015

2.4. Full Text Screening

After the title and abstract screening, we proceeded to the full text screening stage. This phase, as its name suggests, involves reading each paper in full and applying the same inclusion/exclusion criteria shown in Table 2. During the full-text screening phase, we track the exclusion reason for each article. The number of articles and their specific exclusion reason are shown in Figure 2.

We included some additional exclusion criteria during this phase to manage scope. One example was: "too field-specific." This was only a handful of papers, but they consisted of studies that overly focused on the AI algorithm or the application, and insufficiently described their intersection. Similarly, we did not include methods-only papers. We excluded one paper due to clear abuse of generative AI in its creation, with an apparent lack of editing or attribution, and removed it from all materials for credibility concerns. We could access the abstracts of some articles in English, but not the full text, so two studies were excluded this way as well.

Overall, we attributed most exclusions to a lack of decision-making frameworks in the actual application of the AI. While we allowed for a variety of decision-making types (autonomous, augmented human-decision-making, human-in-the-loop, and even static benchmark setting), if the AI outputs were not applied for *any* type of decision-making, we excluded the paper. The goal was, again, to highlight the most safety-critical AI scenarios. If no AI-based decision-making occurs, it becomes challenging to attribute any of the outcome towards the AI. During the full-text review, we excluded 79 articles. Figure 2 shows the remaining 72 articles that comprise the final set included in this review.

2.5. Data Extraction

Finally, a single reviewer extracted the data from the final subset of 72 articles, which included tabulating data for a variety of fields: industry type, industry subcategory, AI type, comparison type, decision-making time, level of expertise of the end user, inclusion of explainability and type, consideration of regulation and regulatory authority, decision-making type, data type, whether the system was deployed, output feature considered, safety outcome, and country of origin. Note: while the term "model explainability" has a variety of definitions, here we assume the most broad– anything that constitutes unpacking the logic of an AI model (interpretability, feature im-

portance, etc.) counts. We do not consider, however, the sheer mention of a "black box" as consideration of explainability.

Throughout the articles considered in this review, we encountered a variety of mentions of "model validation." We did not extract data on types or consideration of validation in the studies in this review, because we found the definitions of validation to vary dramatically between the studies, making comparisons between them practically irrelevant. Finally, if any variables of interest were not present or non-applicable to a particular study, this was denoted as either "non-specific" for presence with lack of specificity or "non-applicable" when the data type of interest did not correspond to the type of study under review (e.g., explainability type for a legal analysis).

2.6. Quality Assessment

During data extraction, we also conducted a brief quality assessment. Due to the heterogeneous nature of the papers included in this analysis, a single, pre-made quality assessment template would not provide sufficient flexibility for our set of articles. Accordingly, instead of confirming if each article meets a certain set of criteria, we pre-defined a simplified set of "flags" to mark areas of concern for each article based on an existing framework, APPRAISE-AI [13]. These flags and the criteria we considered for each are shown in Table 3.

Because this review considers a large portion of medical papers, we critically evaluated each study for its consideration of bias, a known concern for AI applications in that field. To keep our assessment fair, we applied the same judgment to all other papers. Given that all papers concern human health, the way AI views differences between humans can substantially impact its judgment. After assessing for bias, we flagged other categories if we had a concern considering the criteria in Table 3 while reviewing the articles. Commonly, this included flagging for a limited dataset size. When applying a flag for any category, we rated the flag with a level of concern corresponding to either low, medium, or high, which equated to a severity score of 1, 2, or 3, respectively. Then, we applied Equation 1 to determine the quality score for that article.

$$\text{QA Score} = 100 - \frac{\sum_{\text{categories}} \text{severity score}}{21} \times 100 \tag{1}$$

We set our score thresholds as shown in Table 4 based on the cutoff bands established in the APPRAISE-AI framework [13].

Table 3: Flag categories used for quality assessment based on APPRAISE-AI framework [13].

Flag	**Criteria — must consider:**	**Appraise-AI Domain**
Background	- Context and rationale for specific model and problem - Review of relevant literature - Clearly stated objective	Introduction
Data	- Dataset and collection described - Rationale provided for sample size - Ground truth determination described and defined - Handling of missing data described - Data cleaning and splitting described	Methods
Modeling	- Model generalizability considered - Baseline model described (existing model, regression, or domain expert) - Type of AI model(s) reported - Software versions reported - Hyperparameter tuning described	Methods
Results	- Summary statistics/metrics provided - Final model specifications provided (features/hyperparameters) - Evaluation metrics provided and rationalized - Clinical utility (risk/benefit tradeoffs) reported - Error analysis conducted	Results
Bias	- Performance evaluated across $\geq$1 subgroup (age, gender, ethnicity) - Clinical utility evaluated across $\geq$1 subgroup - Considers how subgroups may be helped/hurt by the model	Results — Bias Assessment
Discussion	- Limitations of the study discussed	Discussion
Other	- Conflicts of interest disclosed (if any) - Data descriptions for all features provided - Data availability described - Model availability described	Other Information

Table 4: Quality category assignment ranges based on the APPRAISE-AI framework [13].

Quality Category	Score Range
Very Low Quality	0-19
Low Quality	20-39
Moderate Quality	40-59
High Quality	60-79
Very High Quality	80-100

2.7. Synthesis Methods

Article heterogeneity served as a major limitation to the synthesis methods available for this work. Generally, we dealt with categorical or binary data (e.g. *Did the study consider explainability? If so, what kind?*). Full details of the fields extracted are available in Supplemental Materials (data_extraction.csv). Due to a large, widely varied set of categorical and binary variables our analysis methods are high-level and required narrative synthesis rather than pure meta-analysis. When synthesizing data for quantitative results (Section 3), our results were primarily histograms indicating the number of articles that met a specific criterion of interest during data extraction. As mentioned previously, if a particular data extraction field was irrelevant for a particular type of study, it was simply denoted "non-applicable." Again, because of the highly heterogeneous nature of the papers included in this review, we minimized summary statistics for our study. In one case, where we evaluate papers considering explainability, we include all studies, but create a variety of subcategories to qualify our metrics. We generated visualizations of the data extracted during this review using various Python-based plotting libraries, all of which are available for reference in our code repository.

2.8. Method Limitations

A major limitation of our method is that a single reviewer screened the articles for inclusion, extracted data, and performed quality assessment. This precludes our study from inter-rater reliability metrics across the full dataset for all stages. To mitigate this, a second reviewer independently reviewed a randomly selected 10% subset of the articles at two stages: title and abstract screening and full text screening. Using the subset, we calculated Cohen's kappa for each phase and show these results in Table 5. Based on these results, we can see moderate agreement [14] between the two readers, but we cannot extend this confidence to the data extraction or quality assessment methods.

Although moderate agreement for our spot check is lower than ideal, this has two likely explanations. First, our spot check sample size is very small: 63 out of 630 articles for title/abstract screening and 15 out of 151 for full text screening. This means that individual disagreements can dramatically swing our resultant metric, especially for the full text screening phase. Secondly, some of our inclusion/exclusion criteria were subjective, thus yielding different interpretations between reviewers. For example, under a major inclusion

Table 5: Cohen's κ scores for a 10% subset of dual-reviewed articles.

Phase	κ
Title and Abstract Screening	0.472
Full Text Screening	0.464

criterion "AI informed decision-making," our main reviewer and spot-checker had disagreements on what constituted an AI-based decision versus a purely informative model. Since we only performed the secondary review on a subset of the articles, disagreements between the two reviewers are purely informative; we maintain the first reviewer's decisions as final in this analysis, so no disagreement resolution was necessary.

Another limitation of this work is database selection bias. In our method, we only query articles from Web of Science and Scopus. We chose these databases for their broad scopes, but still note that we necessarily missed some critical pieces not contained on these platforms.

Aside from database selection bias, our querying method may have also omitted safety relevant research via an over-restriction. We made the choice to require an AI term to occur within five words of a derivative of "decision*" to ensure that decision-making was a focus of the work, but we chose this distance arbitrarily and included the term to actually help narrow our scope. After much experimentation, we were forced to balance the restrictiveness of our query with the volume of literature returned.

Further, in our exclusion criteria, we chose not to consider papers published in languages other than English. We made this decision to avoid misinterpreting texts that we could not read in their original form, but recognize that this restricts the reach of our search and may have excluded otherwise appropriate papers for our review.

Finally, the rapid evolution of the topic of this work, artificial intelligence, inherently limits the efficacy of this review. We acknowledge that the field of machine learning and therefore its applications to sensitive industries (including regulation), progresses by the day. For this reason, we chose to expand our search from strictly journal articles to also include papers from five major AI conferences. The goal of this decision was to help cover a field that moves faster than most journal publication timelines, while prioritizing rigorously peer-reviewed publications. This adaptation ultimately did not yield any publications from conference papers in our final corpus. We hypothe-

size that some of our search terms likely required work with more domain specificity than these conferences would attract. Still, we recognize that both the decision to not search conference papers from other domains and the unsuccessful retrieval of papers from the queried AI conferences contribute an additional selection bias to our work.

Despite these limitations, we believe that the findings of this review, based on the state of the field at a snapshot in time, can still provide meaningful insight to users and developers alike. We encourage near-term future work to repeat and expand our analysis to stay up-to-date with this technology as it evolves.

3. Quantitative Results

3.1. Querying Results

Figure 2 shows the number of articles we retained and removed during each phase of querying and screening. We removed two records Zotero marked as retracted in the pre-screening phase, along with one manually identified duplicate record. This yielded 630 records for screening.

During the full screening phase, marked as "Studies assessed for eligibility" in Figure 2, we show the broad categories of reasons for all exclusions. The largest exclusion category ($n = 24$) was for a lack of AI-based decision-making in the article of interest. An example of an excluded study with this reasoning was, "Stochastic route optimization under dynamic ground risk uncertainties for safe drone delivery operations" [15]. Based on the title, this paper would appear to fit well into our inclusion criteria– a safety-critical application (unmanned aerial system) guided by machine learning. However, upon full text review, we determined that the focus of the article was on using ML for risk assessment and route optimization, which consequently could be used for planning, but did not sufficiently focus on safety-critical decision-making to be included in our final corpus. The key feature for exclusion here, was that during route planning, a safer but less convenient or more expensive option may be available. The emphasis on "optimization" indicated that the decision-making focus was for risk tolerance, not safety maximization. This logic ultimately excluded many articles from our final set.

To demonstrate the efficacy of each term in our query set, Figures 3 and 4 show quantitative querying results (the number of results per query combination) from Scopus and Web of Science when individual search terms were included in all queries.




Figure 2: Paper filtration flow diagram based on PRISMA [7].




Figure 3: Sum of articles returned by Scopus when a given search term was included in all queries. Note: some terms yielded no articles; these are still included for completeness.




Figure 4: Sum of articles returned by Web of Science when a given search term was included in all queries. Note: some terms yielded no articles; these are still included for completeness.

3.2. Data Extraction Results

The database used to tabulate our results can be accessed in our code repository.

After extracting the information mentioned in Section 2, we created figures to portray key trends from the set of articles reviewed. This includes the country of the author institution, the main AI type considered in the article, the decision-making type, the decision-making time, the expertise level of the user, whether regulation or explainability was considered, and the types of explainability methods considered.

3.2.1. AI Method

Figure 5 shows the number of articles that employed each type of AI in the final subset of articles. Note that many articles employed more than one type of AI, so Figure 5 shows more counts than the total number of articles. Similarly, some articles focused on ethical or regulatory frameworks and therefore considered AI more generally. We denote the AI type in these articles as "Non-Specific."




Figure 5: Number of articles in the final subset that considered each type of AI method. Non-specific means the article did not provide details about the model type.

3.2.2. Decision-Making Method

Figure 6 shows the decision-making type evaluated by the articles in the final subset. "Not System Integrated" refers to articles that use AI to set a threshold or benchmark for decision-making but do not integrate a dynamic version of the AI into the system under consideration. Additionally, we distinguish between "augmented human decision-making" and "human-in-the-loop": both require human action to make decisions, but human-in-the-loop leans more heavily on the AI system, whereas augmented simply uses the AI results as an additional piece of information to make a decision with. Autonomous systems do not necessarily require human oversight to take action, though they may have it for intervention purposes (e.g., autonomous vehicles).




Figure 6: Decision-making types observed in the final article subset.

3.2.3. Explanation Method

Here, we encounter three terms that deserve and require special consideration: explainability, interpretability, and validation. Explainability refers to the use of secondary post hoc models to derive "explanations" for the output of the primary, usually black-box model [16]. By their very nature, as a model of a model, we cannot regard explanations as faithful evidence of model reasoning. As described by Cynthia Rudin, post hoc explanations must be wrong some fraction of the time, otherwise the post hoc model would equal the original model, and we would not need the original model in the first place [16]. In other words, explanations are necessarily unreliable. Some examples of common explainability methods are SHAP and LIME explanations.

Dissimilarly, interpretability refers to a model that a human can directly extract reasoning from, no secondary model needed. Thus, we can trust interpretable models to faithfully represent model patterns and logic. Some examples of interpretable models include decision trees and linear regression. Still, while interpretability gives us reliable patterns, it does not quantify or supply confidence in model reliability. In other words, we can trust that

interpretability-based model reasoning is true, but that tells us nothing about the general performance reliability of the model. For this, we need model validation.

Validation can encompass a variety of methods and definitions. For our purposes, we will follow one defined by Kochenderfer et al. as "...the broad process of establishing confidence that a system will behave as desired when deployed in the real world" [17]. Some examples include failure probability estimation [3], cross-institutional dataset validation [18], benchmarking against established and accepted models, or clinical trials [19]. Because validation methods for machine learning models can vary widely in type, rigor, and efficacy, we did not track them for the purposes of this analysis.

Instead, we tracked interpretability and explainability methods, which are more established than validation methods in the machine learning space. Approximately 49% of the articles in our final subset considered explanation methods in some capacity. This combined statistic comprises two subgroups: articles that mentioned explainability but did not apply it and articles that applied a specific type of explainability method. We included "rationale for certain models" as an explainability type to account for articles that used decision-trees and other directly interpretable methods. But again, we did not include any type of validation method (clinical testing, uncertainty quantification, expert review, etc.) as an explainability method.

Figure 7 shows the distribution of explainability methods in further detail. In the former group, 20.83% of articles, authors mentioned the importance of explainability, therefore considering it, but did not conduct any explainability analysis themselves. These articles were denoted a "Non-Specific" explainability type in Figure 7. The remaining 27.78% both considered the importance of explainability and applied a specific method. Of the articles that applied a certain method, 55% applied a post hoc explanation method (SHAP, LIME, etc.), while 45% used a directly interpretable model out of preference for its explainability (denoted as "Rationale for Certain Models" in Figure 7).




Figure 7: Explanation types observed in the final article subset. "Non-Specific" indicates that explainability was considered, but no method was applied.

3.2.4. Country of Origin

Figure 8 shows the number of articles that have at least one contributing author from the countries shown. Of the final subset of articles, approximately 44% considered regulatory oversight. This distribution of countries is therefore intended to show how the regulatory oversight bodies might be distributed and to highlight the complexity of defining AI regulatory frameworks that span international boundaries.




Figure 8: Number of articles in the final subset that have at least one author from the listed country. "International Collaboration" article is excluded from this figure; see Supplemental Materials for details.

3.2.5. Industry Distribution

Table 6 shows the distribution of articles by industry for the final subset. The heterogeneous distribution of industries for the articles in our final subset means that our overall findings cannot be broadly generalized, but rather represent emerging trends.

Table 6: Final article subset distribution by industry.

Industry	Percent of Final Subset of Articles
Medical	59.72%
Autonomous Vehicles	18.06%
Nuclear	9.72%
Aviation	8.33%
Ethics	2.78%
Manufacturing	1.39%

Table 7: Cross tabulation analysis for expertise level of the intended AI-user and time to decide in each study.

Expertise Time	Expert	Trained User	General Public	Non-Specific
Days or More	16	1	0	0
Minutes-Hours	17	3	1	0
Seconds or Less	6	2	14	0
Non-Specific	2	0	0	10

3.2.6. Expertise and Decision-Making Time

Table 7 shows the cross tabulation results for two of the extracted variables: expertise level of the intended AI-user and the time for that user to make a decision using that AI system. The fourth category for each of these variables, "Non-Specific," categorizes to articles that discuss AI at large but do not specify a type of model, target user, and/or application. While these articles do not provide extractable metrics, they contain qualitative insights which we discuss in Section 4.

As a visual extension of Table 7, Figure 9 shows the flow of articles as they consider four key extracted variables. Again, because of the heterogeneous nature of our final corpus, the center of this Sankey diagram shows lots of thin flows, indicating the many diverging patterns and edge cases of our dataset. However, the top and bottom of Figure 9 show a clear trend towards applications with high levels of expertise and longer decision times and, conversely, applications with low levels of expertise and shorter decision times. Likewise, we see a greater proportion of articles in the former category (high expertise and long decision times) corresponding to the inclusion of explainability methods.




Figure 9: Sankey diagram showing flow of articles across four major extracted variables: expertise of the user, time to decide, decision-making type, and whether explainability was considered.

3.2.7. Quality Assessment

Most articles in our review scored above the "very high quality" threshold (80-100), indicating no major concerns about the quality of the retrieved articles. Figure 10 shows the distribution of quality assessment scores for articles in the final subset. Additionally, we provide the database containing full details of our quality assessment on a per-article basis in Supplementary Materials. Because the quality assessment was completed by a single reviewer, we acknowledge reviewer subjectivity to be a limitation of our assessment. Still, because the majority of our articles ranked in the "very high" category, we do not believe this significantly impacted the results of our work.




Figure 10: Quality assessment score distribution for articles in the final subset.

4. Qualitative Results and Discussion

We will now discuss each of the major industries identified in our study, highlighting key takeaways from the individual industries and some papers that brought especially unique points to our attention. Then, we will examine the similarities and differences across industries to determine which AI features and findings were universally beneficial, and which industries have specific challenges and demands.

4.1. Medical

Medical papers comprised nearly 60% of our final subset of articles (see Table 6). As the largest industry in terms of article numbers from both the query results and the final subset analysis, the medical industry has a lot to offer in terms of experience using AI systems and highly sensitive usage demands. AI in this industry generally has greater decision-making times and interfaces usually with highly skilled professionals (like doctors), but can also interact directly with patients. Due to its size and variety, we break down this group of papers into smaller categories.

4.1.1. Pharmacology

Eight out of the 43 papers categorized as medical considered applications related to the prescribing and dispensing of medication. The articles in this cohort emphasize that AI requires expert supervision, and the coordination of an expert and AI in pharmacological applications yields the best outcomes (mitigates safety risks). Though only two of these papers considered regulation, three considered model explainability. Interestingly, two of the papers that did consider explainability evaluated large language models (LLMs), which are widely considered the most opaque.

The aforementioned articles [20] and [21] both evaluate LLMs as medication safety-focused clinical decision support systems (CDSS), including prescription errors and drug-drug interactions. Both evaluated variants of Gemini, ChatGPT, and Claude. Ong et al. [20] evaluated the success rate of identifying "drug-related problems" (DRPs) in three scenarios: pharmacist alone, pharmacist with AI-assistance (co-pilot mode), and AI alone and found co-pilot mode to yield the highest success of DRP identification. Chase et al. [21] do not consider AI-pharmacist cooperation, and instead evaluate the LLM independently, still substantiating the finding that the LLMs perform suboptimally alone. They found the LLMs to make potentially harmful clinical recommendations up to 15.4% of the time (ChatGPT). Chase et al. [21] also raise concerns for the less overtly dangerous but still problematic scenario of suboptimal recommendations, such as flagging non-clinically relevant drug interactions, which can lead to alert fatigue over time. These reports highlight the importance of studying not only the pure accuracy of AI systems, but also how their users interact with them.

In response to their findings, Chase et al. directly call for both external validation and benchmarking of medical AI against existing standards *and*

model explainability techniques to address the black box nature of LLMs before they are implemented into clinical practice [21].

However, not all "explainability" methods are created equal. Ong et al. [20] state that the LLMs tested (ChatGPT, Gemini, and Claude) offer something that many "explainable AI tools" cannot— "conversational interfaces [that] allow clinicians to ask questions and receive context-specific explanations in plain language." While the conversational nature of chatbots may seem like a more approachable "explanation," this logic can be dangerous, as reasoning provided by a chatbot is *not* a true explanation and does not indicate *any* amount of model reliability, accuracy, or trustworthiness. We caution that this reasoning may lead to complacency and instead urge practitioners, regulators, and developers to consider genuine explainability and validation methods when applying these tools in practice. Explainability, in particular, can help the ultimate decision-maker (the pharmacist or prescriber) rationalize the CDSS recommendation, giving them grounds to dismiss or accept it with cause.

The remaining articles in the pharmacology subcategory use either classical ML techniques (decision trees and gradient boosting) [22, 23, 24], association rule learning [25], and CDSS built-in systems [19, 26]. Of these, Kieu et al. [22] considered decision trees explicitly for their inherent interpretability. From a deployment perspective, Liu et al. [26] interviewed pharmacists on trusting CDSS recommendations. They found that after consulting a CDSS, 78% of pharmacists did not adjust their dosing regimens due to "distrust and lack of understanding of the justification of the CDSS recommendations" among other concerns, despite a "generally positive attitude toward CDSS." This supports claims made by papers throughout this report that model trust is paramount to implementation and that this trust can be gained from explainability or "justification." Even if a co-piloted pharmacist-AI approach yields the safest medication prescription and dispensing, without pharmacist trust in the partnership, the accuracy improvements are moot.

4.1.2. Imaging and Diagnostics

Eight of the 43 papers evaluated in this section used AI for diagnostic and/or imaging techniques. Of these papers, specific AI techniques included convolutional neural networks (CNNs) for classification of glaucoma [27], LLMs for emergency medical advice [28], generative adversarial networks (GANs) and other methods for skin lesion classification [29], decision trees for cervical spine injury diagnosis [30], and CNNs for stroke onset time pre-

diction [31]. Of the remaining three papers, two included the use of AI for prophylaxis efforts, including preventing falls [32] and blood clots [33]. The last paper in this category discusses AI in radiology more broadly and offers methods to increase generalizability by overcoming overfitting and underspecification [34].

Of the articles considered in this subsection, three of them consider regulation and four of them consider explainability. Vieira et al. [27] model both, anticipating and acting on the needs of clinicians to understand model results and following regulatory transparency guidelines, such as the European General Data Protection Regulation (GDPR). They use retinography images on CNNs coupled with CAM, GradCAM, LIME, SHAP, vanilla gradients, SmoothGrad, and SCIM to evaluate the quality of the different explainability methods for a high-risk clinical application (glaucoma). They found CAM-based methods most reliable to support diagnosis via clear identification of clinically relevant regions and intuitive visual interpretation.

While inherently interpretable models, like decision trees, can offer a clearer, more straightforward understanding of model logic, simpler models are not always an option, especially in the imaging and diagnostic realm. Vieira et al.'s ad-hoc explainability methods model acquiring expert trust in high-stakes applications [27], and it is likely that future work will emulate them in other highly sensitive domains as experts drive demand for rationalized AI recommendations.

4.1.3. Radiation and Other Treatment

Twelve [19, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 2] of the 43 papers reviewed in this section evaluate the use of AI to design and carry out treatment plans with six specifically considering radiation treatment. The number of radiation treatment studies that employ AI alone represents the perceived utility of AI in improving highly sensitive treatment outcomes. Of the twelve papers considered in this section, seven of them considered some aspect of explainability, but only two of them considered regulation, for insulin dosing and [19] maxillofacial trauma surgery [2]. Of the radiation treatment papers considered, nearly all employed classical ML methods, including decision trees, random forests, support vector machines, and gradient boosting. Only one paper [37] considered UNets, a type of CNN, exclusively, and another paper considered neural networks in addition to classical methods [41]. Six [38, 39, 41, 42, 43, 40] of these seven papers either conducted feature importance studies on these classical methods or rationalized their use for

interpretability purposes, highlighting the appeal of simple-as-possible models.

As an outlier, Komorowski et al. [35] used reinforcement learning as the primary learning method for intensive sepsis care, but still used random forests to determine clinically interpretable reasoning (importance of model parameters). The majority of these studies indicate a preference towards simpler, more comprehensible models, and an even greater majority employ explainability for highly sensitive treatment methods.

Most of these papers considered AI to find some threshold radiation dose that is sufficient for treatment success while minimizing harm and secondary radiation side effects to the patient. One of the papers that did not consider explainability outright performed an uncertainty analysis on their UNet model for dose prediction to treat prostate cancer, which still emphasizes a need for some method to establish model trust [37]. Overall, the trend in treatment papers towards explainable AI-decision-support methods supports what we saw in pharmacology– that experts need rationalized recommendations before implementation. Most of the papers in this section focused on doctors administering treatment to patients, therefore overseeing the AI models in question. The one paper [19] that interfaced directly with patients was validated through clinical studies and regulated by the FDA, showing the substitute role (in this case, empirical) validation can play in establishing model trust.

4.1.4. Legal and Regulatory

Eight of the 43 articles considered under the "medical" umbrella directly concerned legal and regulatory factors. Unlike other subsets, these papers generally do not evaluate a specific type of AI. Instead, they describe the ethics, liability, and regulatory considerations that govern these technologies in sensitive domains. Of the eight, five legal/regulatory papers consider explainability in their discussions. In terms of governing bodies concerned, three papers are from E.U. member states, two are from the U.S., two are from the United Kingdom, and one is from Canada.

Of the articles we considered in this subsection, we identified common themes of trust, trustworthiness, and liability. The former are distinguished by Jones et al. [45] following Onora O'Neil's previously established trust framework; trust is something you give, and trustworthiness is how deserving of your trust an entity is. O'Neil emphasizes that trust is only dangerous when placed in an untrustworthy entity. Further, she notes that *"only beings*

with agency are truly capable of being trusted" [45].

We can define the individuals issuing trust and those assessing trustworthiness as separate cases. In the industries considered in this review, when the public is a direct user of an AI-based decision-making system, we must assume they do not have the expertise to assess the trustworthiness of that system. Therefore, these individuals must trust the judgment of some other trustworthiness assessor. For safety-critical industries, as an example, this assessor could be the regulator. In other words, the public places their trust in the regulator, not in the AI itself.

Alternatively, if the direct user of an AI-based decision-making system *does* have the expertise to assess that system's trustworthiness (such as a medical professional), then they can decide on a case-by-case basis when they are willing to accept its recommendations, and they can serve as a barrier to the less knowledgeable public. In this case, the public places their trust in the experienced professional, not in the AI itself.

These two cases also extend to AI use in treatment and in diagnosis, where the former may be used by an expert or a non-expert, and the latter only by experts. The regulator's responsibilities differ in these cases: in treatment, they may authorize a system to be trusted outright, but in diagnosis, they create frameworks to support the decision-maker's assessment of model trustworthiness. Counterintuitively, over-regulating diagnostic AI could increase patient risk by shifting liability away from the professional using it, leading to complacency. The regulatory authority decision of federal agencies in *Loper Bright*, which we discuss later in this section, further complicates this dynamic.

In reality, the cases of trust and trustworthiness outlined above may not be so clear-cut. Trust may fall reasonably back on model developers, users, procurers, etc. Following O'Neil's logic, if a system possesses no agency, it cannot be trusted. The liability question then becomes: *Who is responsible for the consequences of this system?* This is the debate among many legal experts and should be considered by all participants in AI systems, especially as laws and regulations surrounding these technologies change. As a potential solution, Lagiola et al. [46] and Labkoff et al. [47] suggest that unique regulations should correspond to classes of AI automation levels to define the shared level of responsibility and liability between the AI system and the individuals involved in its use.

The current U.S. licensing system is more vague than that and leaves many of the aforementioned questions to the courts. Instances where AI-

assisted decision systems are used by a skilled professional are less regulated and instead rely on their expert judgment (and malpractice insurance). Treatment-based medical AI systems, on the other hand, mainly qualify as medical devices and can be regulated as such in the U.S.

Briefly, the FDA offers three main pathways for licensing depending on the level of rigor of their review. This includes Pre-Market Approval (PMA), *De Novo*, and 510(k), in increasing order of level of rigor. *De Novo*, the newest, is a hybrid pathway that offers neither all the litigation protections of PMA nor the speed of 510(k). Though the outcomes of this pathway remain legally uncertain, AI/ML-enabled device manufacturers use the *De Novo* pathway about three times more often [48], suggesting these companies prefer to accept uncertainty in future liability defense in exchange for expedited approval. This may concern the public as they rely on the FDA's trustworthiness assessment for these (and non-AI) devices. A more thorough approach may include rigorous validation techniques and/or a unique licensing pathway for a unique set of technologies, especially for treatment devices that necessarily elicit trust.

Other legal complications of medical AI may be less obvious. McCradden et al. [49], Kiseleva et al. [50], DeMicco et al. [51], Habli et al. [52], and many others emphasize the ethical concerns of bias in AI systems. However, biased AI systems may also fall under the aforementioned regulatory conditions. Gerke et al. [48] state that when a medical device is licensed, it is licensed as-is. However, "continuous learning" or even discretely retraining an AI system may worsen efficacy for certain patient groups [48]. Shah et al. [53] extend this concern to broader changes post-market release. Failure to warn users of these changes could leave manufacturers liable, even if their original model was protected. Changing efficacy across patient groups, however, may be difficult to assess without formal validation techniques. Thus, aside from being ethically valuable to consistently validate and evaluate models for bias, we also find a legal motive to embed this into system design.

When validated systems fail, explainability methods offer a second layer of protection for the patient, the doctor, and the AI manufacturer. As explained by DiMicco et al. [51], "AI systems should be developed to enable humans to understand their actions and the underlying logic in order to increase transparency and minimise the risk of bias or error." Some jurisdictions have already begun to require aspects of explainability, such as in the European Union's General Data Protection Regulation (GDPR) Articles 13 and 14, which require "meaningful information about the logic involved, as well as

the significance and the envisaged consequences of such processing" when decision-making is automated [46]. Not all jurisdictions offer such a proactive regulatory approach.

Safety-critical domains in the U.S. may find reliance on regulation suboptimal as a protection from faulty AI-based decision support systems; the authority of regulatory agencies in these areas is still legally uncertain. As highlighted by [48], the 2024 Supreme Court case *Loper Bright Enterprises v. Raimondo* [54] and the overturning of the *Chevron* doctrine affect how agencies can regulate these decision support tools. According to Gerke et al., *Loper Bright* "...overruled a longstanding legal doctrine that required courts to defer to reasonable agency interpretations of ambiguous statutes" [55]. This increases litigation risk for American regulatory bodies who interpret ambiguous statutory authority to regulate AI tools, such as CDSS. We are yet to fully realize the effects of this decision, but it may include increased reliance on nonbinding actions on part of regulatory agencies, or it could encourage congressional action on designing regulatory pathways for AI/ML in safety-critical industries [55]. While the main focus of this decision has been on medical applications for AI, it may extend to other industries in which experts might use AI to make "diagnoses," such as in nuclear power or other industrial operations. Practically, this uncertainty regarding regulation of AI-based decision support systems only encourages independent validation and interpretability efforts rather than reliance on federal oversight.

Having established how regulation relates to trust and trustworthiness, we can now consider how developers and users each evaluate these AI systems– and the consequences of their misalignment. We can accomplish this first by understanding O'Neil's three constituents of trust, as described by Jones et al. [45]: trust in truth claims, trust in commitment, and trust in competence. The first is an empirical evaluation: *Is this entity likely to give me a factually correct answer?* Whereas the second two are normative: *Is this entity likely to follow through on their promises?* and *Is this entity likely to execute the promised action successfully?*.

Developers typically focus on the empirical arm of these, as evidenced by the quantitative way we evaluate AI systems: *given 1,000 scenarios, how often will my system predict the correct answer?* Yet, we seldom consider the other two-thirds of how people perceive trust when we set out to develop a "trustworthy system." This misalignment can set users up to overtrust a system that the developer recognizes as having obvious limitations.

The tendency for individuals to place undue trust in these systems, fo-

cusing on their normative elements, is evident. After considering clinician's perspectives on incorporating AI into their practice and the empirical trust issues they encounter, Jones et al. [45] also examine how patients feel about their doctors using AI. They summarize several studies that asked hypothetical patients how they would view various outcomes when their doctors did or did not use AI systems. Overwhelmingly, they found that patients, at worst, had no difference of opinion when AI is used, and at best, viewed their doctors' decisions more favorably, even when the outcome was still unfavorable, suggesting that AI may serve as a "protective shield" for clinicians [45].

There are, of course, some caveats to this: the studies were hypothetical and generally assumed that the AI in question had a known superior diagnostic accuracy than the doctor. Jones et al. conclude that patient favorability towards using AI stems from higher normative trust in two ways: one, that AI is both reliable (machines tend to be more predictable than humans) and two, that AI is competent (on the basis of massive amounts of training data) [45]. Both the patients' readiness to (blindly) trust AI and the clinician's concerns about its empirical accuracy further support the case for co-piloted AI-clinician systems and raise red flags for autonomous AI healthcare providers.

Despite public overconfidence in AI devices, domain experts tend in the opposite direction. In a trial run of AI-assistance at the U.S. FDA to analyze causality in individual case safety reports (ICSRs), reviewers rejected the AI's analysis in most cases because "...the approach did not offer sufficient explanation or flexibility to accommodate information external to the ICSR (e.g., reviewer's knowledge)" [56]. Further, "[b]ecause of the lack of trust in the software tools, any efficiency gains... were not perceived as making it easier for the safety reviewers..." [56]. This highlights a case where domain experts not only question the AI's truth claims, but also its competence, given a lack of sufficient data. The critical feature of this scenario is *the reviewer's expertise*. A less knowledgeable individual may more readily accept the claims of an untrustworthy system, simply because they did not know better. This underscores the importance of "human-in-the-loop" systems and the urgent need to maintain the proficiency of subject-matter experts.

Although experts remain critical of unexplainable AI, developers and regulators should still consider ways to counter "automation bias," the tendency of users to err on the side of the computer [45]. In other words, how can we prevent domain experts from doubting their own judgment when AI suggests a (potentially wrong) alternative? *How can we encourage them to "trust*

their gut?" Holding professionals accountable for their decisions will likely encourage this. Still, how can we ensure that experts are protected when they rely on their own professional expertise? Explainability measures may mitigate automation bias by allowing practitioners to critically analyze the AI's reasoning, creating a situation more akin to a collegial disagreement. Future work may consider implementing guardrails in software design to address these known shortcomings of AI-assisted decision-making systems, and regulation should support trustworthiness assessments while maintaining the professional's liability.

4.1.5. Qualitative Analyses and Roadmaps

The final medical category consisted of six qualitative papers that underscore our finding that expert trust is integral to the success of an AI-supported decision-making system. Two papers focused directly on healthcare professionals' perspectives [57, 58], while another focused directly on patient perspectives [59]. The remaining three make broad recommendations on what AI in healthcare ought to look like, all of which include addressing risk of bias, validation, regulation, and explainability as key issues [47, 60, 18].

The papers in this section uniquely highlight the importance of cross-institutional collaboration. Labkoff et al. [47] propose a CDSS-incident reporting platform to mitigate the repetition of mistakes and standardized documentation to inform clinicians of tool limitations [47]. Similarly, Taylor et al. [18] propose mitigating bias through model "validation across institutional datasets." Unfortunately, sensitive applications like healthcare also come with sensitive data. This is a challenge we can expect across sensitive domains that may be addressed with organizational efforts or federal guidance. Future work may identify safe, anonymized methods to do so.

Finally, the interview-based perspective papers offered insight from both sides of medical practice. They found medical professionals, including doctors, nurses, staff scientists, and administrators, all similarly concerned about model recommendations lacking rationale and the risk of bias, especially because they ultimately felt liable [57, 58]. Alternatively, the patients interviewed in Fransen et al. [59] showed a clear preference for using AI versus not to aid radiologists' judgment of their prostate cancer imaging, but most (85%) preferred radiologist oversight [59]. Fransen et al. [59] acknowledge the limitations of their study by citing a different outcome from an older study on women's acceptance of AI in mammogram interpretation, which found a notably lower level of acceptance. This difference could be attributed to

factors beyond gender, including the year of publication (2025 for Fransen et al. and 2021 for the mammogram study), but it highlights the importance of not only evaluating bias within the model but also understanding how different individuals may view these systems.

4.2. Autonomous Vehicles

Autonomous vehicles comprised just over 18% of our final subset of articles, our second-largest category. These papers ranged from focusing directly on ethics [61, 62, 63, 64], to validation [65, 66], explanations [67, 68], legal implications [69, 70], and pure accident avoidance [71, 4, 72]. Looking broadly at the subcategories alone highlights unique distinctions from the other industries in this review. First, the overwhelming number of ethics-focused papers. Unlike in medical contexts, autonomous vehicles often face two-body ethical dilemmas– *who should be spared in an unavoidable collision scenario?* Further, direct calls for validation and regulation are prolific.

Autonomous vehicles, as their name implies, do not enjoy the protections of "human-in-the-loop" systems, which is how most medical AI operates. Nor do users of these AI-driven systems benefit from a certified expert reviewing every decision. Instead of the AI offering a suggestion and an experienced professional using their expertise to decide whether to take it, autonomous vehicles make decisions nearly continuously and rely on human intervention *only* if something goes awry. This removes a barrier of protection against unreliable systems, making liability issues more complicated, especially when defining "human intervention." How could someone intervene in a system designed to relieve their attention span? Tian et al. [70] approach this argument by promoting proactive insurance involvement and liability rules that encourage manufacturers to invest in safety. Tian et al. [70] explain this in the context of the Hand Formula– if the burden (of safety innovation) is less costly than the probability (of an accident) times the loss (of that accident), it is negligent for the manufacturer *not* to take that safety precaution.

To make the safety designation even more challenging, although many of the AI systems evaluated in this paper are "narrow AI," meaning they are trained for a specific task (the opposite of general AI), autonomous vehicles face a wide variety of scenarios, and can struggle to learn edge cases that have severe consequences (as seen in [65]). This, combined with a lack of general oversight, points to a major need for validation methods that can serve as the basis of verifying the safety of these systems to the public. This

is perhaps why we see the most validation studies in this subcategory– two [65, 66], versus one for aviation [3], and none for any other category.

Generally, we denote validation and explanation as distinct but similarly useful practices for AI-supported decision-making. In the context of autonomous vehicles, however, the latter is less effective. While explanations can be helpful in understanding the rationale of an autonomous vehicle's decision-making, they are less useful than CDSS explanations because the window of time between an autonomous vehicle's data acquisition, modeling calculation, and decision is much shorter. In other words, one would probably hope that a doctor takes more time to decide on a patient's treatment plan than they take to change lanes on their way to work. The same time restriction on those decision-making scenarios applies to autonomous vehicles, so model explanations are not particularly useful for human intervention.

Counterintuitively, then, two papers in this category focus *primarily* on developing model explanations [67, 68]. In these reports, explanations play other roles than rationalizing real-time decision-making, like evaluating model performance before deployment [67] or understanding trust dynamics with human operators [68]. We do caution that, like Ong et al. [20], Feng et al. [67] generate somewhat "pseudo-explanations" by jointly predicting decision-making actions and natural language explanations using natural language processing. These are not true explanations that glean insights into a model's inner workings, so they cannot be given the same authority as feature importance from a random forest, for example. The explanation-focused papers in this category diverge from studies where decision-makers benefit from greater time and expertise. Still, we find explanation methods less useful in the context of autonomous vehicles than in other domains.

4.3. Nuclear

Nuclear systems comprised nearly 10% of our final subset of articles. This subset varied in terms of nuclear application, with most studies we considered toeing the line with predictive maintenance, a classification we excluded from this analysis. All papers related to the operation of nuclear power plants in this section, six of the seven papers, used traditional machine learning methods (i.e., decision trees, random forests, feedforward neural networks) plus more complex models, like Bayesian belief networks and long short-term memory networks. The only paper unrelated to nuclear power plants focused on nuclear crisis management and used generative AI in its analysis [73]. Holmes et al. [73] stood out as an outlier in this category, not only

because the application area differed significantly, but because it focused on using generative AI to avoid the pitfalls of human emotion in high-stakes political decision-making scenarios. In most of the studies we consider in this work, AI is used to support decision-making from a logical, data-based perspective, whereas in this case, it is used to assist in a somewhat emotional capacity. While this paper met all of our inclusion criteria, it serves a small audience and is basically unregulated. Still, it emphasizes a need for humans to remain in the loop for expert-level decision-making.

The nuclear-power-focused papers in this section considered using AI for reactor pressure vessel design [74], severe-accident scenario propagation [75], cooling-water intake reliability [76], sensor fault-detection [77], accident diagnosis [78], and human-error detection [79]. Of these, three considered explainability methods: one inherent to the AI model used (decision trees) [75], one using a post hoc method known as SHAP [79], and one just as a general concept that *should* be incorporated [76]. None of the methods in this category were deployed, and only one considered regulation [77]. Since nuclear power is a highly regulated, highly skilled industry, we find the limited attempts to develop explanations and address regulatory compliance indicative of the state of the field. The systems considered in this category were all subject to human oversight; no papers suggested a fully autonomous system. This means that all AI outputs will need a human go-ahead before making decisions. Without an adequate rationale, we can expect nuclear power plant operators and engineers to be just as unwilling to blindly trust black box recommendations as the medical professionals in Section 4.1. Future work on developing explanatory methods, validation techniques, and regulatory compliance strategies will therefore be critical in the nuclear power space.

Further, unlike other industries in this review, nuclear power faces the unique challenge of extremely limited data availability. This is evidenced by the fact that three of the six nuclear power papers use synthetic data, while the other three rely on mechanical sensors or static measurements. The use of synthetic data adds another layer of epistemic uncertainty to the model results that is avoidable in more data-prolific applications. The use of synthetic datasets will likely require additional validation to meet regulatory standards for safety-critical decision-making in nuclear systems. This barrier is characteristic of the field—almost all the papers in this section mention limitations due to a lack of data. As such, we also observe that most of these studies are "preliminary" or "proof-of-concept," whereas other industries have already deployed and sometimes validated their models.

Finally, the studies in this subsection are geographically concentrated in the U.S., South Korea, China, and Sweden, likely as an effect of the more limited global distribution of nuclear power compared to other technologies, like medicine and aviation. The size and distribution of this industry, combined with its limited data and high-risk nature, make AI research more difficult to transition to a deployed technology. Future work in this area might focus on the regulatory challenges of implementing AI, and on addressing data limitation issues.

4.4. Aviation

Aviation comprised 8.33% of our final subset of articles (see Table 6). Of the aviation papers, three were specifically aimed at predicting accidents and incidents, two during flight [80, 81], and one during scheduling [82]. The three remaining studies examined automated airport security detection [83], a Bayesian validation method for black box systems currently employed by the FAA [3], and a roadmap for AI in flight advisory systems [84]. The airport security screening and the validation study are both deployed systems, while the remaining studies present pure research. Of the six papers, only one, Cankaya et al., considered explainability [82].

Aviation AI targets low-probability, high-risk events that are generally supervised by experienced professionals (e.g., pilots). Due to the varied ways AI can be used in aviation, some scenarios face the same time-restriction challenge as autonomous vehicles, but not all. That said, for applications with human agency and sufficient time for review, explainability methods may be useful. Cankaya et al. [82] use this logic to justify needing interpretable models for the managerial decision-making in aviation– creating a zero-accident ecosystem requires knowing the root causes of *potential* accidents before they happen. While "black box" systems may provide insight into the frequency of failure, they cannot provide likely causes to enable prevention. Interpretable models may therefore fill this gap and allow rationalized decision-making for time-eligible scenarios.

Other studies in this group [84, 81, 85, 83] use AI to improve safety in various aspects of aviation (via flight advisory systems, hard landing warnings, engine flameout predictions, and accurate security screenings, respectively), but they do not evaluate model explainability or perform validation studies on their models. Such levels of model opacity and performance uncertainty leave their frameworks far from implementation from a regulatory perspective, except for [83], which evaluates an already-deployed system separate

from the aircraft's mechanical functionality and therefore subject to different scrutiny.

Notwithstanding their opacity, many non-interpretable models (such as those listed above) perform extremely well when tasked to predict an upcoming incident. While such models are obviously valuable, understanding their reliability, if not their exact inner workings, is critical for deployment. Moss et al. developed a way to accomplish this [3]. They model the failure probability estimation for autonomous flight systems using a Bayesian framework that "...iteratively fits a probabilistic surrogate model to efficiently predict failures" [3]. As the authors state, this system is actively involved in an FAA certification process. As such, other industries might apply a similar protocol to validate AI systems to their respective regulatory bodies. Over all industries, aviation contained one of the few validation studies (though other industries call for validation, such as in [49], which calls for "model auditing"). Though nearly all the industries considered in this review are regulated to some extent, the lack of validation studies, something we would typically expect for implementing new technologies into highly regulated fields, is evidently lacking.

It is not surprising, however, that the most rigorous validation study we found is from aviation, as the aviation industry is widely known for its safety-first culture. In fact, during our analysis, we found that other industries explicitly referenced aviation's success in implementing a strong safety culture and their goal to replicate it [60]. Fuchs et al. [60] emphasize the importance of validation studies like [3] when they call for a graded approach to regulating medical-AI as part of a larger roadmap to mimic aviation's historic tactic to best safety practices.

4.5. Other Industries

The three remaining papers in our review included two legal/ethics papers [86, 87], and one paper on manufacturing defects [88]. While the latter is a more traditional machine learning paper, it emphasizes explainability when predicting void formations during welding, a phenomenon that can lead to unreliable structures [88]. Of the former, Maskur et al. [87] mainly discuss global variations in current AI regulations, stating that the E.U. has taken the most direct, proactive approach, while the U.S. waits for precedents to arise through the courts. We see these differences in the medical space, as described in Section 4.1.4, and suggest that future work consider how to remediate them when technologies cross national borders.

After all the trust concerns described in this review, it seems natural to question whether AI is even worth implementing in our most sensitive domains. Is the status quo good enough? Safer, even? Cerf et al. [86] present a response to this very concern and caution readers that while fears surrounding AI are well-founded, humans have historically proven problematic as well. While Cerf's claims likely aim to address existential concerns of generative AI, we can still heed their warning that we not let risks surrounding AI "...distract from human beings' current proficiency at carrying out the threats attributed to technology" [86]. As such, we can take away from this is that rather than run from a powerful technology, we ought to design, implement, and regulate it with a safety-first approach. By completing this review, we have identified general rules to accomplish this goal, which we describe in the following section.

5. Conclusion

From this review, we find two key trends that remain consistent across the studies in our final corpus. The first is related to explainability. We find that explainability techniques only matter if the user has both the *time* to consider the rationalization and the *expertise* to review it. In other words, if the interfacing user is not a domain expert, developers and regulators should not assume that the user has the necessary background knowledge or understanding to adequately assess the quality of the AI's decision given an explanation. Likewise, even a domain expert cannot possibly evaluate an explanation instantaneously. In scenarios with limited user expertise and/or limited evaluation time, it is necessary to have robust regulation underpinned by model validation techniques to protect users. Validation is always a good idea, but is strictly necessary when AI tools interface with inexperienced or time-pressed individuals. Model explanations are both unhelpful and insufficient in these contexts. Some examples of this may include wearable medical devices, like glucose or heart rate monitors that encourage decision-making without physician review, or broadly, autonomous vehicles.

Second, in scenarios where the user has both sufficient time and expertise to review a model explanation, the explanation is incredibly useful and practically necessary for acceptance. Validation in these scenarios is, of course, reassuring. However, when the decision is ultimately made by a highly skilled professional, they bear the responsibility for it. Overly prescriptive regulation of decision-support systems used by highly skilled professionals may encour-

age complacency. Such complacency would be detrimental to the quality of care in domains where we rely on professional oversight to reap the benefits of co-piloted AI-human systems. The studies in this report broadly indicate that AI-assisted decision-making yields superior results when paired with a critical expert. Absolving these experts of their authority risks deteriorating outcomes. From a legal perspective, formal protections for the opinions of professionals when they disagree with AI recommendations may mitigate this risk. For example: if patients can reliably win lawsuits against doctors for diverging from CDSS recommendations, then doctors cannot reliably oversee those CDSS systems. Regulators, lawmakers, developers, and users should all be aware of this risk.

5.1. Study Limitations

Nearly all studies in this report found that AI technologies "improved outcomes" in some way. This is expected due to publication bias– null results simply do not get published with the same frequency as successful protocols. Second, of the 72 studies considered, only 21 involved what we considered a "deployed system," meaning it was tested in real, critical scenarios. The remaining papers were either not deployed (38) or non-applicable as they were qualitative or roadmap papers (13). This means that even a broad systematic review like this cannot conclusively say if AI improves outcomes in sensitive industries.

Future work might focus exclusively on deployed AI in a specific domain to draw more general conclusions about lives spared by AI, but even this effort will be affected by publication bias. We also observe a chicken-and-egg problem in this facet—sensitive industries will be hesitant to deploy AI systems for safety-critical applications until they are proven safe and/or better than the status quo, yet the only way to evaluate this for a complete black box technology is to study the outcomes of such a system on real scenarios. The solution is called for in papers throughout this review and explicitly demonstrated by Moss et al., a model-agnostic validation technique for black box AI that can be reviewed by regulators [3]. That said, insufficient regulation may render the most effective validation techniques futile. This matters most for non-expert-facing technologies where robust regulation must establish the validation criteria for model developers to apply. On regulation, while we generalize the regulatory recommendations in this work to be internationally applicable, we also note that our regulatory focus is on the United States, so some nuance to other regulatory systems may be overlooked.

Next, the authors of this review do not have expertise in all the fields evaluated. Likewise, the final corpus consisted of an imbalanced set of papers from each industry category. For this reason, there may be nuances to our findings between subdomains that we could not capture in this review. We believe the importance of cross-industry learning supersedes these limitations, but future work should delve further into domain specifics.

This review strictly sourced material from published academic articles on Web of Science and Scopus. As such, our review of relevant regulations across the industries we cover is necessarily incomplete. This, in and of itself, may underscore the disconnect between software developers, industry practitioners, and regulators. We urge each party to make efforts to close this gap to promote the safe use of this technology. Papers such as this serve as a first step in that direction.

Finally, our query terms certainly failed to retrieve every relevant article in the safety-critical AI space. While we tried to maximize our coverage of the relevant literature, doing so completely would be impossible. Because of this, the conclusions drawn in this report should reflect general trends in the literature, but future work should seek to expand our method with additional search terms, especially as AI research advances, we expect the corpus retrieved using our method to rapidly evolve.

5.2. Future Work

Though we describe opportunities for future work throughout this report, a few stand out. First, we observed references to data limitation issues across industries in this review. Future work should seek to improve the quality, accessibility, security, and cross-organizational sharing of data for sensitive applications. More broadly, future work should evaluate the security risks of AI-based decision-making in sensitive industries to both inform regulation and help guide data limitation efforts. From a policy perspective, future work should evaluate how international technology can manage varying national regulations in a way that emphasizes user safety. Likewise, future work should extend on the findings of this report to evaluate the nuances of AI safety in industry-specific applications. Domain-specific regulatory bodies may require this detail for effective policies.

One of the originally intended research questions in this study focused on the safety accidents that occurred as a result of AI in various industries. At the time of study, however, the query methodology we employed did not retrieve any accident analyses that could help address this question.

Future work should consider adapting (likely relaxing) our search strategy to specifically target post-accident or near-miss papers.

Finally, future work must continue to explore validation and explanation techniques. Specifically, a study exploring optimal validation techniques for common expertise and decision-making time combinations we reveal in this work would be valuable to the field. The quality of these techniques will underpin trust in this powerful technology.

6. Acknowledgment

The authors would like to thank Riley Fisher for his feedback and suggestions during review, Leo Tunkle for his help with early abstract screenings, and Dr. Samuel Dotson for his feedback during methodology development.

This research is funded by the U.S. Nuclear Regulatory Commission's University Nuclear Leadership Program for Research and Development, award number 31310024M0013. The first author (N. Panczyk) received sponsorship through the National Science Foundation's Graduate Research Fellowship Program.

The authors declare that they have no known competing financial or personal interests that might influence the findings of this work.

7. CRediT Author Statement

- **Nataly R. Panczyk**: Conceptualization, Methodology, Software, Validation, Formal Analysis, Visualization, Investigation, Data Curation, Writing - Original Draft.
- **Majdi I. Radaideh**: Conceptualization, Methodology, Data Curation, Formal Analysis, Resources, Funding Acquisition, Supervision, Project Administration, Writing - Review and Edit.

References

[1] The White House, National Policy Framework for Artificial-Intelligence (Mar. 2026).

[2] A. Shhadeh, S. Daoud, I. Redenski, D. Oren, A. Zoabi, F. Kablan, S. Srouji, The contribution of real-time artificial intelligence segmentation in maxillofacial trauma emergencies, Diagnostics 15 (8) (2025). doi:10.3390/diagnostics15080984.

[3] R. J. Moss, M. J. Kochenderfer, M. Gariel, A. Dubois, Bayesian safety validation for failure probability estimation of black-box systems 21.0 (2024). doi:10.2514/1.I011395.

[4] T. Lu, G. Kuang, D. Xu, S. Xu, Y. Luo, Q. Wang, S. Shang, Q. Zhou, B. Nie, A physics-informed attention model for integrated driving risk assessment 223.0 (2025). doi:10.1016/j.aap.2025.108266.

[5] Y. Wang, S. H. Chung, Artificial intelligence in safety-critical systems: A systematic review, Industrial Management & Data Systems 122 (2) (2021) 442–470. doi:10.1108/IMDS-07-2021-0419.

[6] T. A. Bach, J. K. Kristiansen, A. Babic, A. Jacovi, Unpacking Human-AI Interaction in Safety-Critical Industries: A Systematic Literature Review, IEEE Access 12 (2024) 106385–106414. doi:10.1109/ACCESS.2024.3437190.

[7] M. J. Page, J. E. McKenzie, P. M. Bossuyt, I. Boutron, T. C. Hoffmann, C. D. Mulrow, L. Shamseer, J. M. Tetzlaff, E. A. Akl, S. E. Brennan, R. Chou, J. Glanville, J. M. Grimshaw, A. Hróbjartsson, M. M. Lalu, T. Li, E. W. Loder, E. Mayo-Wilson, S. McDonald, L. A. McGuinness, L. A. Stewart, J. Thomas, A. C. Tricco, V. A. Welch, P. Whiting, D. Moher, The PRISMA 2020 statement: An updated guideline for reporting systematic reviews, BMJ 372 (2021) n71. doi:10.1136/bmj.n71.

[8] M. Campbell, J. E. McKenzie, A. Sowden, S. V. Katikireddi, S. E. Brennan, S. Ellis, J. Hartmann-Boyce, R. Ryan, S. Shepperd, J. Thomas, V. Welch, H. Thomson, Synthesis without meta-analysis (SWiM) in systematic reviews: Reporting guideline, BMJ 368 (2020) l6890. doi:10.1136/bmj.l6890.

[9] C. Schardt, M. B. Adams, T. Owens, S. Keitz, P. Fontelo, Utilization of the PICO framework to improve searching PubMed for clinical questions, BMC medical informatics and decision making 7 (2007) 16. doi:10.1186/1472-6947-7-16.

[10] Google, Artificial Intelligence Top Publications (2025).

[11] Corporation for Digital Scholarship, Zotero (2025).

[12] Veritas Health Innovation, Covidence systematic review software (2025).

[13] J. C. C. Kwong, A. Khondker, K. Lajkosz, M. B. A. McDermott, X. B. Frigola, M. D. McCradden, M. Mamdani, G. S. Kulkarni, A. E. W. Johnson, APPRAISE-AI Tool for Quantitative Evaluation of AI Studies for Clinical Decision Support, JAMA Network Open 6 (9) (2023) e2335377. doi:10.1001/jamanetworkopen.2023.35377.

[14] J. R. Landis, G. G. Koch, The measurement of observer agreement for categorical data, Biometrics 33 (1) (1977) 159–174.

[15] B. Pang, X. Hu, W. Dai, K. H. Low, Stochastic route optimization under dynamic ground risk uncertainties for safe drone delivery operations 192.0 (2024). doi:10.1016/j.tre.2024.103717.

[16] C. Rudin, Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead, Nature Machine Intelligence 1 (5) (2019) 206–215. doi:10.1038/s42256-019-0048-x.

[17] M. J. Kochenderfer, S. M. Katz, A. L. Corso, M. R. J., Algorithms for Validation, Stanford, California, 2025.

[18] R. A. Taylor, R. B. Sangal, M. E. Smith, A. D. Haimovich, A. Rodman, M. S. Iscoe, S. K. Pavuluri, C. Rose, A. T. Janke, D. S. Wright, V. Socrates, A. Declan, Leveraging artificial intelligence to reduce diagnostic errors in emergency medicine: Challenges, opportunities, and future directions 32.0 (2025). doi:10.1111/acem.15066.

[19] R. Nimri, T. Battelino, L. M. Laffel, R. H. Slover, D. Schatz, S. A. Weinzimer, K. Dovc, T. Danne, M. Phillip, S. Shalitin, R. Bello, M. Nevo-Shenker, N. Fisch-Shvalb, G. Shiovitch-Mantzuri, O. Choresh, I. Drutz, Y. Nava, A. Hemo, O. Hermon, R. Nave, N. Bratina, D. Smigoe-Schweiger, B. Mali, A. Gianini, U. Sever, B. M. Berkopec, M. Katz, E. Isganaitis, S. Mehta, H. Quinn, N. Naik, Z. Guo, L. Volkening, G. Forlenza, R. P. Wadwa, G. T. Alonso, L. Messer, L. Towers, K. Thivener, C. Berget, S. Lange, E. Jost, M. Rossick-Solis, M. Haller, P. Hiers, L. Jacobsen, M. Smith, A. O'Neill, J. Hosford, A. Perry, E. Cengiz, J. Sherr, K. Gibbons, L. Carria, M. Zgorski, T. Biester, O. Kordonouri, T. von dem Berge, S. Biester, K. Remus, Insulin dose optimization using an automated artificial intelligence-based decision support system in youths with type 1 diabetes, Nature Medicine 26 (9) (2020) 1380–1384. doi:10.1038/s41591-020-1045-7.

[20] J. C. L. Ong, L. Jin, K. Elangovan, G. Y. S. Lim, D. Y. Z. Lim, G. G. R. Sng, H. Ke, J. Y. M. Tung, R. J. Zhong, C. M. Y. Koh, K. Z. H. Lee, X. Chen, J. K. Ch'ng, A. Than, K. J. Goh, C. P. Lim, T. M. Ng, N. Liu, D. S. W. Ting, Large language model as clinical decision support system augments medication safety in 16 clinical specialties 6.0 (2025). doi:10.1016/j.xcrm.2025.102323.

[21] A. Chase, A. Most, A. Sikora, S. E. Smith, J. W. Devlin, S. Xu, T. Liu, B. Murray, Evaluation of large language models' ability to identify clinically relevant drug-drug interactions and generate high-quality clinical pharmacotherapy recommendations (2025). doi:10.1093/ajhp/zxaf168.

[22] A. M. Kieu, H. N. Dang, K. T. C. Tran, T. T. T. Nguyen, C. H. Nguyen, T. C. Nguyen, H. T. Pham, J. Le, H. T. Nguyen, Development and validation of machine learning-based predictive clinical decision support system for olanzapine in patients with schizophrenia, Pharmaceutical Sciences Asia 51 (4) (2024) 314–325. doi:10.29090/psa.2024.04.24.AP0713.

[23] M. Bücker, K. Hoti, O. Rose, Artificial intelligence to assist decision-making on pharmacotherapy: A feasibility study, Exploratory Research in Clinical and Social Pharmacy 15 (2024). doi:10.1016/j.rcsop.2024.100491.

[24] J. Corny, A. Rajkumar, O. Martin, X. Dode, J.-P. Lajonchere, O. Billuart, Y. Bezie, A. Buronfosse, A machine learning-based clinical decision support system to identify prescriptions with a high risk of medication error 27.0 (2020). doi:10.1093/jamia/ocaa154.

[25] C.-Y. Chen, Y.-L. Chen, J. Scholl, H.-C. Yang, Y.-C. J. Li, Ability of machine-learning based clinical decision support system to reduce alert fatigue, wrong-drug errors, and alert users about look alike, sound alike medication 243.0 (2024). doi:10.1016/j.cmpb.2023.107869.

[26] X. Liu, E. F. F. Barreto, Y. Dong, C. Liu, X. Gao, M. S. Tootooni, X. Song, K. B. B. Kashani, Discrepancy between perceptions and acceptance of clinical decision support Systems: Implementation of artificial intelligence for vancomycin dosing 23.0 (2023). doi:10.1186/s12911-023-02254-9.

[27] C. Vieira, L. Rocha, M. Guimarães, D. Dias, Exploring transparency: A comparative analysis of explainable artificial intelligence techniques in retinography images to support the diagnosis of glaucoma, Computers in Biology and Medicine 185 (2025). doi:10.1016/j.compbiomed.2024.109556.

[28] J. Y. S. Yau, S. Saadat, E. Hsu, L. S. L. Murphy, J. S. Roh, J. Suchard, A. Tapia, W. Wiechmann, M. I. Langdorf, Accuracy of prospective assessments of 4 large language model chatbot responses to patient questions about emergency care: Experimental comparative study, Journal of Medical Internet Research 26 (2024). doi:10.2196/60291.

[29] C. Metta, A. Beretta, R. Guidotti, Y. Yin, P. Gallinari, S. Rinzivillo, F. Giannotti, Advancing dermatological diagnostics: Interpretable AI for enhanced skin lesion classification, Diagnostics 14 (7) (2024). doi:10.3390/diagnostics14070753.

[30] D. Bertsimas, P. T. Masiakos, K. S. Mylonas, H. Wiberg, Prediction of cervical spine injury in young pediatric patients: An optimal trees artificial intelligence approach 54.0 (2019). doi:10.1016/j.jpedsurg.2019.03.007.

[31] E. M. Z. Akay, J. Rieger, R. Schöttler, J. Behland, R. Schymczyk, A. A. Khalil, I. Galinovic, J. Sobesky, J. B. Fiebach, V. I. Madai, A. Hilbert, D. Frey, A deep learning analysis of stroke onset time prediction and comparison to DWI-FLAIR mismatch, Neuroimage Clinical 40 (2023). doi:10.1016/j.nicl.2023.103544.

[32] M. Woo, B. Alhanti, S. Lusk, F. Dunston, S. Blackwelder, K. S. Lytle, B. A. Goldstein, A. Bedoya, Evaluation of ML-based clinical decision support tool to replace an existing tool in an academic health system: Lessons learned 10.0 (2020). doi:10.3390/jpm10030104.

[33] S. Zhou, X. Ma, S. Jiang, X. Huang, Y. You, H. Shang, Y. Lu, A retrospective study on the effectiveness of Artificial Intelligence-based Clinical Decision Support System (AI-CDSS) to improve the incidence of hospital-related venous thromboembolism (VTE) 9.0 (2021). doi:10.21037/atm-21-1093.

[34] T. Eche, L. H. Schwartz, F.-Z. Mokrane, L. Dercle, Toward generalizability in the deployment of artificial intelligence in radiology: Role of computation stress testing to overcome underspecification 3.0 (2021). doi:10.1148/ryai.2021210097.

[35] M. Komorowski, L. A. Celi, O. Badawi, A. C. Gordon, A. A. Faisal, The Artificial Intelligence Clinician learns optimal treatment strategies for sepsis in intensive care, Nature Medicine 24 (11) (2018) 1716–1720. doi:10.1038/s41591-018-0213-5.

[36] D. S. Bitterman, P. Selesnick, J. Bredfeldt, C. L. Williams, C. Guthier, E. Huynh, D. E. Kozono, J. H. Lewis, R. A. Cormack, C. M. Carpenter, R. H. Mak, K. M. Atkins, Dosimetric planning tradeoffs to reduce heart dose using machine learning-guided decision support software in patients with lung cancer, International Journal of Radiation Oncology Biology Physics 112 (4) (2022) 996–1003. doi:10.1016/j.ijrobp.2021.11.009.

[37] M. Chen, B. Pang, Y. Zeng, C. Xu, J. Chen, K. Yang, Y. Chang, Z. Yang, Evaluation of an automated clinical decision system with deep learning dose prediction and NTCP model for prostate cancer proton therapy, Physics in Medicine and Biology 69 (11) (2024). doi:10.1088/1361-6560/ad48f6.

[38] M. Alizade-Harakiyan, A. Khodaei, A. Yousefi, H. Zamani, A. Mesbahi, Decision tree-based machine learning algorithm for prediction of acute radiation esophagitis, Biochemistry and Biophysics Reports 42 (2025). doi:10.1016/j.bbrep.2025.101991.

[39] E. Fleury, J. P. Pignol, E. Kiliç, C. van Rij, N. Naus, S. Yavuzyigitoglu, W. den Toom, A. Zolnay, K. Spruijt, M. van Vulpen, P. Trnková, M. Hoogeman, Stereotactic radiation therapy or protons for uveal melanoma patients? An artificial intelligence (AI)-based clinical treatment decision-making tool predicting doses to radiation therapy constraints, International Journal of Radiation Oncology Biology Physics 123 (4) (2025) 1159–1164. doi:10.1016/j.ijrobp.2025.06.3867.

[40] M. Sakuragi, E. Uchino, N. Sato, T. Matsubara, A. Ueda, Y. Mineharu, R. Kojima, M. Yanagita, Y. Okuno, Interpretable machine learning-

based individual analysis of acute kidney injury in immune checkpoint inhibitor therapy 19.0 (2024). doi:10.1371/journal.pone.0298673.

[41] I. Chamseddine, Y. Kim, B. De, I. El Naqa, D. G. Duda, J. Wolfgang, J. Pursley, H. Paganetti, J. Wo, T. Hong, E. J. Koay, C. Grassberger, Predictive modeling of survival and toxicity in patients with hepatocellular carcinoma after radiotherapy 6.0 (2022). doi:10.1200/CCI.21.00169.

[42] J. Braun, S. Quirk, E. Tchistiakova, Machine learning-generated decision boundaries for prediction and exploration of patient-specific quality assurance failures in stereotactic radiosurgery plans 49.0 (2022). doi:10.1002/mp.15454.

[43] M. Allen, C. James, J. Frost, K. Liabo, K. Pearn, T. Monks, R. Everson, K. Stein, M. James, Use of clinical pathway simulation and machine learning to identify key levers for maximizing the benefit of intravenous thrombolysis in acute stroke, Stroke 53 (9) (2022) 2758–2767. doi:10.1161/STROKEAHA.121.038454.

[44] M. Cutforth, H. Watson, C. Brown, C. Wang, S. Thomson, D. Fell, V. Dilys, M. Scrimgeour, P. Schrempf, J. Lesh, K. Muir, A. Weir, A. Q. O'Neil, Acute stroke CDS: Automatic retrieval of thrombolysis contraindications from unstructured clinical letters, Frontiers in Digital Health 5 (2023). doi:10.3389/fdgth.2023.1186516.

[45] C. Jones, J. Thornton, J. C. Wyatt, Artificial intelligence and clinical decision support: Clinicians' perspectives on trust, trustworthiness, and liability 31.0 (2023). doi:10.1093/medlaw/fwad013.

[46] F. Lagioia, G. Contissa, The strange case of dr. Watson: Liability implications of ai evidence-based decision support systems in health care 12.0 (2020). doi:10.2924/EJLS.2019.028.

[47] S. Labkoff, B. Oladimeji, J. Kannry, A. Solomonides, R. Leftwich, E. Koski, A. L. Joseph, M. Lopez-Gonzalez, L. A. Fleisher, K. Nolen, S. Dutta, D. R. Levy, A. Price, P. J. Barr, J. D. Hron, B. Lin, G. Srivastava, N. Pastor, U. S. Luque, T. T. T. Bui, R. Singh, T. Williams, M. G. Weiner, T. Naumann, D. F. Sittig, G. P. Jackson, Y. Quintana,

Toward a responsible future: Recommendations for AI-enabled clinical decision support 31.0 (2024). doi:10.1093/jamia/ocae209.

[48] S. Gerke, D. A. Simon, New case law and liability risks for manufacturers of medical AI, Science 388 (6752) (2025) 1138–1140. doi:10.1126/science.adu4932.

[49] M. D. McCradden, S. Joshi, J. A. Anderson, M. Mazwi, A. Goldenberg, R. Z. Shaul, Patient safety and quality improvement: Ethical principles for a regulatory approach to bias in healthcare machine learning 27.0 (2020). doi:10.1093/jamia/ocaa085.

[50] A. Kiseleva, P. Quinn, Are you AI'S favourite? EU legal implications of biased AI systems in clinical genetics and genomics, European Pharmaceutical Law Review 5 (4) (2021) 155–174. doi:10.21552/eplr/2021/4/4.

[51] F. De Micco, S. Grassi, L. Tomassini, G. Di Palma, G. Ricchezze, R. Scendoni, Robotics and AI into healthcare from the perspective of European regulation: Who is responsible for medical malpractice? 11.0 (2024). doi:10.3389/fmed.2024.1428504.

[52] I. Habli, T. Lawton, Z. Porter, Artificial intelligence in health care: Accountability and safety, Bulletin of the World Health Organization 98 (4) (2020) 251–256. doi:10.2471/BLT.19.237487.

[53] N. Shah, M. Mourby, R. N. Matin, Regulatory and legal considerations with artificial intelligence in dermatology 43.0 (2025). doi:10.1016/j.det.2025.05.011.

[54] Loper Bright Enterprises v. Raimondo, 603 U.S. 369 (2024).

[55] S. Gerke, D. A. Simon, Chevron's Fall And Its Impact On Medical AI, Health Affairs Forefront (Jan. 2025). doi:https://www.healthaffairs.org/do/10.1377/forefront.20250101.818091.

[56] R. Ball, A. H. Talal, O. Dang, M. Munoz, M. Markatou, Trust but verify: Lessons learned for the application of AI to case-based clinical decision-making from postmarketing drug safety assessment at the US food and drug administration 26.0 (2024). doi:10.2196/50274.

[57] S. C. E. Nouis, V. Uren, S. Jariwala, Evaluating accountability, transparency, and bias in AI-assisted healthcare decision- making: A qualitative study of healthcare professionals' perspectives in the UK 26.0 (2025). doi:10.1186/s12910-025-01243-z.

[58] C. R. King, A. Shambe, J. Abraham, Potential uses of AI for perioperative nursing handoffs: A qualitative study 6.0 (2023). doi:10.1093/jamiaopen/ooad015.

[59] S. J. Fransen, T. C. Kwee, D. Rouw, C. Roest, Q. Y. van Lohuizen, F. F. Simonis, P. J. van Leeuwen, S. Heijmink, Y. P. Ongena, M. Haan, D. Yakar, Patient perspectives on the use of artificial intelligence in prostate cancer diagnosis on MRI, European Radiology 35 (2) (2025) 769–775. doi:10.1007/s00330-024-11012-y.

[60] B. Fuchs, P. Heesen, From Lindbergh's cockpit to predictive, AI-driven health care: A roadmap for high-reliability medicine 10.0 (2025). doi:10.1016/j.esmorw.2025.100650.

[61] L. Eggert, Autonomised harming 182.0 (2025). doi:10.1007/s11098-023-01990-y.

[62] P. S. Guensberg, Automated vehicles - is a dilution of human responsibility the answer? 13.0 (2022). doi:10.1177/20322844221138049.

[63] M. Geisslinger, F. Poszler, M. Lienkamp, An ethical trajectory planning algorithm for autonomous vehicles 5.0 (2023). doi:10.1038/s42256-022-00607-z.

[64] M. A. K. Bertheau, C. Boetzel, C. S. Herrmann, Event-related potentials reveal incongruent behavior of autonomous vehicles in the moral machine dilemma 15.0 (2025). doi:10.1038/s41598-025-99531-6.

[65] K. Yang, B. Li, W. Shao, X. Tang, X. Liu, H. Wang, Prediction failure risk-aware decision-making for autonomous vehicles on signalized intersections 24.0 (2023). doi:10.1109/TITS.2023.3288507.

[66] Y. Ji, Z. Xu, C. Zhao, K. Chen, Y. Du, Accelerated testing and evaluation for black-box autonomous driving systems via adaptive markov chain monte carlo 26.0 (2025). doi:10.1109/TITS.2024.3525059.

[67] Y. Feng, W. Hua, Y. Sun, NLE-DM: Natural-language explanations for decision making of autonomous driving based on semantic scene understanding 24.0 (2023). doi:10.1109/TITS.2023.3273547.

[68] S. Kaneko, S. Yamada, Predicting trust dynamics with dynamic SEM in human-AI collaboration 13.0 (2025). doi:10.1109/ACCESS.2025.3629365.

[69] X. Ma, W. Yu, C. Zhao, C. Wang, W. Zhou, G. Zhao, M. Ma, W. Wang, L. Yang, R. Mu, H. Wang, J. Li, Legal decision-making for highway automated driving, IEEE Transactions on Intelligent Vehicles (2023) 1–14doi:10.1109/TIV.2023.3318214.

[70] X. Tian, How should autonomous vehicles allocate accident liability? Rethinking the applicability of the hand formula 16.0 (2025). doi:10.1515/ajle-2025-0037.

[71] N. J. Goodall, Comparison of automated vehicle struck-from-behind crash rates with national rates using naturalistic data 154.0 (2021). doi:10.1016/j.aap.2021.106056.

[72] C. Yuan, J. Ding, Y. Cui, H. Chen, J. Ma, Active takeover failure of aggressive drivers during partially automated driving 116.0 (2026). doi:10.1016/j.trf.2025.103416.

[73] M. Holmes, N. J. Wheeler, The role of artificial intelligence in nuclear crisis decision making: A complement, not a substitute 78.0 (2024). doi:10.1080/10357718.2024.2333814.

[74] D. Yao, G. Gao, Q. Yang, F. Fan, J. Yan, Mechanical behaviors and internal pressure bearing capacity of nuclear containment using UHPC and ECC: From numerical simulation, machine learning prediction to fragility analysis 429.0 (2024). doi:10.1016/j.nucengdes.2024.113617.

[75] K. Hossny, W. Villanueva, H. D. Wang, Distinctive physical insights driven from machine learning modelling of nuclear power plant severe accident scenario propagation 13.0 (2023). doi:10.1038/s41598-023-28205-y.

[76] N. Zhao, R. Han, F. Ying, H. Rong, Human-machine cooperation in safety management: An intelligent decision-making framework for cooling water intake reliability 177.0 (2024). doi:10.1016/j.pnucene.2024.105452.

[77] J. W. Hong, J. H. Park, M. G. Na, Fault identification and signal restoration of sensors based on artificial intelligence at nuclear power plants 58.0 (2026). doi:10.1016/j.net.2025.103876.

[78] Y. H. Chae, C. Lee, S. M. Han, P. H. Seong, Graph neural network based multiple accident diagnosis in nuclear power plants: Data optimization to represent the system configuration 54.0 (2022). doi:10.1016/j.net.2022.02.024.

[79] B. Reddy, E. Gursel, K. Daniels, A. Khojandi, J. Baalis Coble, V. Agarwal, R. Boring, V. Yadav, M. Madadi, Uncertainty-aware and explainable human error detection in the operation of nuclear power plants 210.0 (2024). doi:10.1080/00295450.2024.2372217.

[80] W. R. Khattak, A. Salman, S. Ghafoor, S. Latif, Multi-modal LSTM network for anomaly prediction in piston engine aircraft 10.0 (2024). doi:10.1016/j.heliyon.2024.e25120.

[81] Y. Kong, X. Zhang, S. Mahadevan, Bayesian deep learning for aircraft hard landing safety assessment 23.0 (2022). doi:10.1109/TITS.2022.3162566.

[82] B. Cankaya, K. Topuz, D. Delen, A. Glassman, Evidence-based managerial decision-making with machine learning: The case of Bayesian inference in aviation incidents 120.0 (2023). doi:10.1016/j.omega.2023.102906.

[83] D. Huegli, A. Chavaillaz, J. Sauer, A. Schwaninger, Effects of false alarms and miscues of decision support systems on human-machine system performance: A study with airport security screeners 68.0 (2025). doi:10.1080/00140139.2025.2453546.

[84] M. A. Ramos, K. Sankaran, S. Guarro, A. Mosleh, R. Ramezani, A. Arjounilla, The need for and conceptual design of an AI model-based integrated flight advisory system 237.0 (2023). doi:10.1177/1748006X221083379.

[85] M. U. Khalid, S. Laplante, C. Masino, A. Alseidi, S. Jayaraman, H. Zhang, P. Mashouri, S. Protserov, J. Hunter, M. Brudno, A. Madani, Use of artificial intelligence for decision-support to avoid high-risk behaviors during laparoscopic cholecystectomy, Surgical Endoscopy 37 (12) (2023) 9467–9475. doi:10.1007/s00464-023-10403-4.

[86] M. Cerf, A. Waytz, If you worry about humanity, you should be more scared of humans than of AI 79.0 (2023). doi:10.1080/00963402.2023.2245242.

[87] M. A. Maskur, A. Masyhar, R. Damayanti, D. P. Ramada, S. Sanyal, Reimagining criminal liability in the age of artificial intelligence: Toward a comparative and reform-oriented legal framework, Journal of Law and Legal Reform 6 (4) (2025) 1805–1838. doi:10.15294/jllr.v6i4.35540.

[88] A. Baruah, H. Borkar, Optimised machine learning classification model to detect void formations in friction stir welding, Materials Today Proceedings (2023). doi:10.1016/j.matpr.2023.03.386.