Pairwise Preferences and Citation Evidence for TREC AutoJudge 2026

Nidhin Pattaniyil npatta01@gmail.com
Tanwir Zaman zaman.tanwir@gmail.com
Semih Yagli semihyagli1@gmail.com
Independent researchers · Team NP Labs

Abstract

We describe three submitted methods for judging answers from the RAG and RAGTIME tracks. **Pairwise** asks which of two answers is better. **Evidence** checks whether an answer covers the question and whether its citations support its claims. **Combined** averages the two scores.

We submitted all three approaches to both tracks. Pairwise uses ten opponents per answer and compares both presentation orders. Evidence uses one shared checklist per question, separate coverage and citation judgments, and half credit for partial support. Combined gives the two scores equal weight. This paper describes these final submissions.

1 One task, three approaches

RAG and RAGTIME systems generate answers with citations to source documents. AutoJudge evaluates those answers and predicts a leaderboard [3]. Our output is a score for each system. The organizer later evaluates how well the predicted ranking matches the host track's assessment.




Figure 1: Three judging approaches, each submitted to both tracks: six submissions in total. Pairwise and Evidence can be used independently; Combined averages their scores.

Scope. We submitted each method to both tracks, giving six submissions. For RAG, our judges scored answers from 83 submitted systems across 119 questions. For RAGTIME, they scored answers from 49 systems across 103 questions. Here, a system is an answer-generation run being judged, not one of our three judging methods.

Coverage and support. An answer can mention everything requested and still cite weak evidence. We use a four-day-workweek example to show why we keep those judgments separate.

2 Pairwise: compare, swap, then fit a ranking

The judge sees the question and two answers, including their citation markers. It returns a winner or a tie. Comparing both orders reduces sensitivity to answer position [4, 5]; it cannot guarantee a correct judgment.

Workweek example (illustrative, inspired by RAGTIME 2025 topic 1033).


Question	How does a four-day workweek change hours and wellbeing?
Answer A	Employees work 32 hours a week [1]. This reduces stress and doubles company profits [2].
Answer B	A four-day workweek gives employees more time off.

Presentation	Assumed decision	Credit to A
A then B	A wins	1
B then A	Tie	.5

A's pair credit: $(1 + .5)/2 = \mathbf{.75}$

The answers, sources and votes are authored examples. Preference alone does not establish support for A's profit claim.

From comparisons to a system score



For each question, its answers form a fixed hash-ordered ring, shown unrolled above. Numbers mark neighbor distances, not ranks. Repeat for every answer; judge each selected pair in both orders.

Fit Bradley–Terry
For each question, fit answer strengths to the votes. Predict win chances against all its answers, including unjudged opponents.

Average twice
Average each answer's win chances against the other answers. Then average its system's answer scores across questions.

Figure 2: From a limited comparison budget to a full ranking. The question marks represent other anonymous answers. The network and bars illustrate the method, not measured results. Scores estimate preference, not factual correctness.

3 Evidence: check the claim, not just the citation marker

The evidence branch builds one question-guided checklist from pooled evidence and freezes it for all answers. It then checks coverage separately from support. Our submitted model identifier is `openai/gpt-6-luna` [6]; we did not train a new judge.




Figure 3: Left: the question and pooled cited sources jointly produce a checklist shared by all answers. Right: coverage and own-citation support are judged separately, then linked by segment ID. Stress and profits share one answer segment but are shown separately to reveal partial support.

Build the checklist once. The full question and pooled source excerpts guide its requirements. Each item records acceptable alternatives. Required items must be covered; optional items add useful detail. Factual items ask for information, while request-only items concern how the answer should respond. If excerpts exceed the input budget, we use deduplicated, validated claims with provenance and retain qualifications on partial claims.

Evaluate each answer. The coverage judge sees the checklist and answer, but no source text or citation-support labels. A separate citation judgment checks the answer against its own sources. We join these judgments by segment ID and identify the supported portion of a partial claim before assigning grounded coverage.

Coverage measures whether required checklist items are addressed, including factual and request-only items. Grounded factual coverage counts required factual items supported by the answer's own citations. Sources used to build the shared checklist cannot repair a missing or weak citation in that answer. The checklist can still miss important facts.

From judgments to an Evidence score

Each answer receives a coverage score and citation-support scores, all on a 0–1 scale. We combine them with equal weights:

$$E_{\text{RAG}} = \frac{\text{coverage} + \text{citation precision} + \text{citation recall}}{3}$$

$$E_{\text{RAGTIME}} = \frac{\text{grounded factual coverage} + \text{top-citation support}}{2}.$$

Section 4 defines these components and explains the different citation rules.

4 Track-specific scores

RAG evaluates preference, nugget coverage and citation precision/recall [1]. RAGTIME emphasizes correctly cited nuggets and sentence precision [2]. Our shared judgments approximate those targets with two differences:

	RAG	**RAGTIME**
Coverage	Required checklist items addressed	Required factual items addressed *and supported*
Citation support	Precision: mean over cited claim–document pairs. Recall: mean of the best single-citation support per segment.	Mean support from each segment's top-priority citation.

The Evidence formulas in Section 3 average these components. Optional omissions do not lower coverage.

Same citations, different selection rules

RAGTIME follows the system's citation priority, as its guidelines require. Our RAG recall uses the best single citation as an approximation; this is our choice, not an organizer rule.

Example: one claim, two citations	
First citation: no support	Second citation: full support
RAG recall: select best $\longrightarrow$ **1**	RAGTIME: select first $\longrightarrow$ **0**

Shared credit rules

Full support	**Partial support**	**Unestablished**
1	.5	0

These credits and the generated checklist are our design choices. Partial citations are not added into full credit; unestablished support does not mean a claim is false.

Case	Treatment in both tracks
Uncited segment	Zero citation recall/support.
Explicit non-claim	Exclude; retain segments without an explicit label.
Empty denominator	Return zero and flag as undefined.

5 From one answer to a score

For the illustrative workweek answer, coverage is complete but one citation supports only part of its sentence.

1. Coverage: check the two requirements

✓ Working hours ✓ Wellbeing

Both requirements are addressed and supported, so both coverage scores are $2/2 = \mathbf{1}$. Source [2] supports wellbeing through reduced stress. The answer's unsupported profit claim lowers citation support, not coverage: profits were not requested.

2. Citation support: check the two segments (sentences here)

Answer says	Source supports	Credit
"32 hours [1]"	Full: 32 hours	1
"Less stress and double profits [2]"	Partial: less stress only; no support for double profits	.5

One citation per sentence makes precision, recall and top-citation support equal here: $(1 + .5)/2 = \mathbf{.75}$.

3. Calculate Evidence, then Combined

	RAG	**RAGTIME**
Evidence inputs	Coverage + precision + recall	Grounded coverage + top-citation support
Average	$(1 + .75 + .75)/3 = \mathbf{.833}$	$(1 + .75)/2 = \mathbf{.875}$
Add Pairwise	Assume Pairwise = .60	Assume Pairwise = .60
Combined	$(.60 + .833)/2 \approx \mathbf{.717}$	$(.60 + .875)/2 \approx \mathbf{.738}$

Evidence averages **three components for RAG** and **two for RAGTIME**. Combined gives Pairwise and Evidence equal weight. The assumed .60 is this answer's fitted Pairwise score for this question, not its .75 credit from one pair. For all three methods, a system's score is the mean of its answer scores across questions.

Submitted runs

All six runs use `openai/gpt-6-luna` [6]. The table gives submission names and data IDs.

Method	RAG	RAGTIME
Pairwise	`ntp-rag-pairwise-10-v1` (2459)	`ntp-ragtime-pairwise-10-v1` (2480)
Evidence	`ntp-rag-evidence-v1` (2521)	`ntp-ragtime-evidence-v1` (2523)
Combined	`ntp-rag-combined-v1` (2522)	`ntp-ragtime-combined-v1` (2524)

Frozen revisions: `135b5c6` (RAG Pairwise), `284040d` (RAGTIME Pairwise), `c37a657` (Evidence and Combined). Original judgments are retained for replay.

References

[1] TREC RAG organizers. *RAG 2026 task guidelines: Evaluation.*
[2] TREC RAGTIME organizers. *RAGTIME 2026 guidelines: Metrics.*
[3] TREC AutoJudge organizers. *TREC AutoJudge: task and participation information.*
[4] P. Wang et al. *Large Language Models are not Fair Evaluators.* 2023.
[5] L. Zheng et al. *Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena.* 2023.
[6] OpenAI. *GPT-6 Astra System Card: GPT-6 Sol, GPT-6 Luna.* 2026.