NP Labs at TRECVID 2026: Video Answer Generation and Multiple-Choice Ranking

Nidhin Pattaniyil
Individual participant (team: NP Labs)

Structured Abstract

Answer Generation (AG)

Data used	We used pretrained models without fine-tuning. Labeled 2025 examples guided development; test answers were excluded.
What we tried	**AG1**: Qwen answers from 12 video frames. **AG2**: combine Qwen answers from video without a transcript and video with a Whisper speech transcript into one submission. **AG3**: put Gemini's audio-video answer first, followed by Qwen alternatives. **AG4**: reword saved source answers; preserve AG3's first answer.
What changed	AG3 and AG4 lead METEOR@1 (.318 versus .171–.189). AG1 narrowly leads STS; AG2 narrowly leads BERTScore. These are descriptive comparisons.
What helped?	In a selected 30-question 2025 development comparison, adding Whisper to Qwen3.5 frames increased token F1 from .431 to .507. This is development evidence, not an ablation of the submitted AG2 configuration.
What we learned	Fixed Gemini-first ordering can place a Qwen answer matching the official count below a conflicting answer. AG4 preserves rank one by design; its changed answer lists have lower NDCG@10.

Multiple Choice (MC)

Data used	Organizer-provided questions and options, plus our AG3 first answer or the original video. No training or correct test answers were used.
What we tried	**MC1**: match our AG3 answer to the supplied options. **MC2**: use saved MC3 video rankings where a text check flags an uncertain or inconsistent option match. **MC3**: rank options from every available video with Gemini 3.7. **MC4**: use the same approach with Gemini 3.8.
What changed	Accuracy rises from 78.748% (MC1) to 83.402% (MC2) and 84.514% (MC3). MC4 scores 84.308%.
What helped?	Using video predictions wherever available adds 27 correct choices over targeted review, using the same Gemini 3.7 predictions.
What we learned	Full video review fixes 219 MC1 errors but introduces 79 errors. Counting remains difficult: MC3 gets 200 of 309 "how many" questions right.

Overview

We submitted four AG and four MC runs covering 2,443 questions from 1,956 videos. AG returns ten ranked answers; MC ranks the released options [1, 2]. We used the revised MC options. Official scoring covers 2,428 questions after 15 exclusions. Video-based ranking gave our highest overall MC accuracy. For generated answers, the strongest run depended on the similarity metric. The examples below show why source selection, wording, and answer-choice design still matter.

1 Answer Generation

1.1 What we submitted

Independent answer sources	Source priority for each submission	
Qwen3.5: 12 frames	**AG1**	Frame answers
Qwen3.6: video + Whisper text Qwen3.6: video only	**AG2**	Qwen + text → Qwen video → baseline alternatives
Gemini 3.7: audio-video	**AG3**	Gemini → Qwen answers → baseline alternatives

AG4: group and rewrite saved source answers; keep AG3's first answer fixed.

Figure 1: Every source receives the question and generates answers independently. Arrows indicate source priority when assembling saved answers, not calls between models or fixed output ranks. Failed sources and duplicates are skipped. Each submission contains ten ranked answers.

AG1: Qwen3.5 frame baseline. For each available video, we sample the midpoint of each of 12 equal intervals. Ten unavailable-video rows used only the question and were excluded from official scoring. Qwen3.5-4B returns a short answer, then nine alternatives from the same frames. When the model does not produce ten distinct answers, we first request a repair, then fill any remaining positions with predefined generic answers. These fillers occupy 650 of 24,430 positions; they are not predictions from the video.

AG2: combined Qwen3.6 answers. We submitted one list of ten answers per question. To build it, we called Qwen3.6-27B twice on the same video payload, once without and once with speech transcribed into timestamped text by Whisper. Both outputs feed the same submission: the answer from video plus Whisper text first, then the video-without-transcript answer and baseline alternatives, with duplicates removed. Requests use temperature zero, disabled thinking, and a 64-token output cap. We do not assume the video path consumes native audio.

AG3: Gemini-first fusion. Gemini 3.7 Flash answers from audio-video at 4 frames per second, low media resolution, high thinking, and a 2,048-token output cap. Its successful answer goes first; Qwen and baseline candidates fill the list. Missing or failed sources are skipped and duplicates removed. This is a fixed priority for every question, not a learned confidence rule.

AG4: grouped rewrite. Gemini 3.7 Flash receives the saved first answers from the four source calls and generates ten candidates, grouping equivalent meanings and retaining conflicting answers separately. Each group must retain an exact source answer, and duplicate strings are rejected. AG3's first answer stays first. If the rewrite fails our checks, we keep AG3's original list.

Development evidence. A small matched 2025 comparison motivated the use of speech transcripts; Appendix A gives the setup and results.

1.2 Results

Scores are from the organizer release [3]. **Official AG results.** AG3 and AG4 lead METEOR (.318 versus .171–.189). The STS and BERTScore differences are much smaller: AG1 leads STS, and AG2 leads BERTScore, each by about .001 over the next run. Statistical significance was not tested. This pattern also holds with human-only references. AG4 keeps AG3's first answer but has lower ranked-list scores: METEOR NDCG@10 falls from .861585 to .812896. STS and BERTScore NDCG@10 also fall in both reference modes.

Run	STS@1	METEOR@1	BERTScore F1@1
AG1 — `q35_4b_u12`	.485552	.170537	.890737
AG2 — `q36_dualview`	.465828	.188578	.891633
AG3 — `g37_q36_fusion`	.484527	.318244	.878867
AG4 — `g37_grouped_unique`	.484527	.318244	.878867

Table 1: Official AG rank-one similarity using human plus alternative references. These scores are not accuracy. NDCG measures discounted relevance across the ranked list; AG4 changes candidate wording as well as ordering.

1.3 When source answers disagree

An inspected case (Q_ID 106; video `8008.webm`). The question asks how many people are shown. In a 1-fps inspection, we see two people, agreeing with the official MC answer, "2." AG3 instead answers "4 people (two main subjects and two partially visible in the foreground)." MC3 also selects "4." MC1 and MC2 also select four, while MC4 selects the official count. We did not find the additional foreground people in the inspected frames. AG1 answers "2," which AG3 retains at rank three below Gemini's "4" answer.

1.4 Wording and similarity scores

Section 3 follows one weather question through AG scores, recorded AG4 groups, and MC choices. Equivalent answers receive different METEOR scores, and an answer conflicting with the official MC choice receives near-perfect BERTScore. MC3 and MC4 also make different choices despite their shared direct-video approach.

2 Multiple Choice

2.1 What we submitted

All runs rank the organizer's options. MC1 uses *our AG3 first answer*, generated before seeing the options; it does not receive the organizer's correct answer.

Run	Route from evidence to option ranking
MC1	Saved AG3 answer → Gemini 3.7 text matching
MC2	Text checker: review needed? Yes → reuse MC3 ranking; No → keep MC1
MC3	Audio-video → Gemini 3.7 option ranking
MC4	Audio-video → Gemini 3.8 option ranking

Figure 2: Every route receives the question and supplied options. MC2 selects where to use MC3's video predictions. Video calls receive no saved AG answer. Invalid or unavailable video rankings fall back to MC1.

MC1: saved-answer matching. Gemini 3.7 Flash receives the question, AG3's first answer, and every option, then ranks the options.

MC2: selected video checks. A separate text-model call checks how well our saved answer matches the options. We select MC3's video ranking if the match is partial or absent, the checker asks to see video, or MC1's first choice is outside the checker's closest matches. This selects 798 questions. We use valid video rankings for 786 of them and retain MC1 for the other 12 and all questions not selected.

MC3: video review throughout. Gemini 3.7 receives audio-video, the question, and options at 4 frames per second, low resolution, and high thinking. It does not see saved AG answers or text rankings. Valid video rankings replace MC1 on 2,423 questions; 20 retain MC1 because media is unavailable or output is invalid. MC2 reuses these same video predictions.

MC4: Gemini 3.8 video review. This follows MC3's approach with Gemini 3.8 Flash: 2,428 valid video rankings and 15 MC1 fallbacks. These submission counts precede the organizer's exclusion of 15 questions.

2.2 Results

Official MC results. Full Gemini 3.7 review gives our highest accuracy (Table 2). Figure 3 separates corrections from new errors: extending video review beyond MC2's selected questions brings a smaller net gain. Gemini 3.8 has five fewer correct answers than 3.7; this does not establish a general model advantage.

Run	Correct / 2,428	Accuracy	MRR
MC1 — `g37q36_mc_text`	1912	78.748%	.864605
MC2 — `g37_mc_target`	2025	83.402%	.896845
MC3 — `g37_mc_direct`	2052	84.514%	.905653
MC4 — `g38_mc_direct`	2047	84.308%	.905368

Table 2: Official MC scores on the same 2,428 questions. MRR is mean reciprocal rank.




Figure 3: Changes in first-choice correctness on the same 2,428 questions. MC2 and MC3 reuse the same video predictions; expanding their use corrects 69 additional errors but loses 42 previously correct answers.

MC3 ranks second among organizer-listed runs: 2,052 correct versus the leader's 2,058 (84.761%).

On the 309 "how many" questions, MC3 gets 200 right (64.7%), versus MC2's 205 and MC4's 204. Unlike the overall results, MC2 and MC4 score above MC3 on these questions. Among MC3's 109 misses, 76 select an explicit number different from the official option. We compare digits and number words from zero to twenty, excluding vague quantities; this identifies counting disagreements, not their cause.

3 One example across scoring, grouping, and choice



Question: "What is the weather like when someone is filming the white building?"

Q_ID 1835; Video_ID `8083.webm`; frame at 2 s.

Official MC answer: "Sunny." The frame illustrates the clip; it is not a reconstructed model input.

A. Wording and correctness are different from similarity scores.

Run	Actual first answer	STS	METEOR	BERTScore F1
AG1	rainy	.552	.000	.999
AG2	Sunny	1.000	.500	1.000
AG3 / AG4	It is sunny.	1.000	.992	1.000

"Sunny" and "It is sunny." agree but differ in METEOR. "Rainy," which conflicts with the official MC choice, still receives BERTScore .999. These are official all-reference scores; AG reference text is unavailable in the score files.

B. AG4 groups answers by meaning and rewords both groups.

Saved sunny sources: Gemini "It is sunny."; Qwen + transcript "Sunny"; Qwen video "It's sunny."
Saved rainy source: Qwen3.5 "rainy".

Rank	Meaning group	Submitted answer	Origin
1	Sunny	It is sunny.	Source; fixed first
2	Rainy	rainy	Source
3	Sunny	Sunny	Source
4	Sunny	It's sunny.	Source
5	Rainy	The weather is rainy.	Added
6	Sunny	The weather is sunny.	Added
7	Rainy	It is raining.	Added
8	Sunny	Bright and sunny.	Added
9	Rainy	Rainy weather.	Added
10	Sunny	Sunny weather.	Added

Figure 4: Recorded AG4 groups in submission order. Four source answers are retained and six variants added. Allocation and interleaving are generated, not fixed quotas.

The groups remain interleaved: ten different wordings express only two conflicting answers.

C. MC matches the saved answer or ranks from video.


All supplied choices: Sunny; Partly cloudy; Cloudy; Windy; Foggy; Rainy; Stormy; Snowy. Display order follows MC1's ranking.

Run	Method	First choice	Result	Rank of Sunny
MC1	Saved-answer match	Sunny	Correct	1
MC2	Targeted review	Sunny	Correct	1
MC3	Video, Gemini 3.7	Rainy	Incorrect	7
MC4	Video, Gemini 3.8	Sunny	Correct	1

MC1 maps AG3's "It is sunny." to "Sunny." MC3 selects "Rainy," while MC4 selects "Sunny"; neither receives saved AG answers or AG4 groups. This case was selected to illustrate all three panels: its MC pattern occurs in 20/2,428 questions, whereas MC3 gains 140 correct choices overall versus MC1. This illustrates a difference between answering openly and ranking supplied choices; it does not establish why the predictions differ.

4 Shared errors and equivalent answer choices

All four MC runs miss the same **271 questions**. We screened their questions, options, and selected answers, then inspected eight selected clips. Two cases contain equivalent choices that receive different scores.



Q_ID 2049; 50 s
`Archipelago-42.webm`

"How many people in the video are wearing a hat?"

Official choice: "One"

All four runs choose:
"One person is wearing a hat"

Same count; different scoring. Every run selects the longer answer and is marked wrong.

Figure 5: Both wordings are organizer-provided choices. The frame illustrates the clip; it is not a reconstructed model input.

"How many beds are in the house?"

Q_ID 1369; `Memphis-18.webm`

Official choice	All four runs choose
"One"	"One bed"

What this tells us. More video evidence cannot distinguish "One" from "One bed" as answers to a bed-count question. These are failures to select the designated wording, not disagreements about the count. They do not show that the count label itself is wrong. This targeted review does not estimate how often the problem occurs.

This audit covers our runs only; question-level results for other teams were unavailable. Appendix B records the audit method and unresolved cases.

Overall takeaway. Using video rankings more broadly improves MC accuracy, but also introduces new errors. For AG, Gemini-first answers lead METEOR; AG4 keeps rank one unchanged, but its changed answer lists score lower.

Drafting assistance. Codex assisted with writing, diagrams, and source checks. Author review and final model references remain to be completed.

References

[1] NIST. *TRECVID 2026: Video Question Answering guidelines.* https://www-nlpir.nist.gov/projects/tv2026/vqa.html.

[2] A. F. Smeaton, P. Over, and W. Kraaij. Evaluation campaigns and TRECVid. *MIR*, 2006, pp. 321–330. doi:10.1145/1178677.1178722.

[3] NIST. *TREC VQA 2026 evaluation results.* Participant release, September 2026. AG workbook and NP Labs MC scores; archived at repository revision `3efb5b19dbd6d8d59232986cc25ef049af24ba5e`.

A Why we tried speech transcripts

Question. Can a speech transcript help answer questions that video frames alone cannot resolve? This small development comparison motivated the transcript input used in AG2.

What we changed. Both conditions used Qwen3.5-4B, the same questions, and the same 12 uniformly sampled frames. One condition also received a Whisper large-v3 transcript when it passed the transcript-quality check; otherwise the transcript was omitted. The panel comprised 30 labeled 2025 examples: six each on speech, sound/music, temporal actions, spatial/OCR/color, and visual controls.

Input	Exact matches	Overall token F1	Speech token F1
12 frames	9/30	.431	.431
Same frames + transcript	11/30	.507	.700

Exact match requires identical normalized answer strings. Token F1 measures overlap between normalized answer and reference tokens; the table reports means across questions. The speech column covers the six speech questions.

What we took from it. Transcripts helped most on speech questions, so they were worth including as an input. They did not solve non-speech audio: neither condition exactly answered any sound/music question. This explains a development choice, not AG2's test-set gain; the submitted AG2 also used a different model and video input.

B What the shared-failure review established

We wanted to know whether a shared failure meant the models had misunderstood the video. We checked the questions that all four runs missed against the organizer's original options and our submitted rankings, then inspected eight selected clips.

The other cases were less clear. For example, one clip contains both a passing train and a cyclist, so the question's timing matters. Other cases had unclear visual details or potentially synonymous choices. We left those unresolved rather than calling the labels wrong.

Clips were selected for inspection rather than sampled randomly. Detailed case records remain in the supporting analysis.