NP Labs at TRECVID 2026: Video Answer Generation and Multiple-Choice Ranking

Nidhin Pattaniyil
Individual participant (team: NP Labs)

Structured Abstract

Answer Generation (AG)

Data used	We used pretrained models without fine-tuning. Labeled 2025 examples guided development; test answers were excluded.
What we tried	**AG1**: Qwen answers from 12 video frames. **AG2**: combine Qwen answers from video without a transcript and video with a Whisper speech transcript into one submission. **AG3**: put Gemini's audio-video answer first, followed by Qwen alternatives. **AG4**: reword saved source answers; preserve AG3's first answer.
What changed	AG3 and AG4 tie for the highest METEOR@1 (.3182); AG2 has the highest BERTScore F1@1 (.8916), less than .001 above AG1. AG1 narrowly leads STS@1 (.4856). These are descriptive comparisons.
What helped?	In a selected 30-question 2025 development comparison, adding Whisper to Qwen3.5 frames increased token F1 from .431 to .507. This is development evidence, not an ablation of the submitted AG2 configuration.
What we learned	Fixed Gemini-first ordering can overlook a better Qwen answer, as in the inspected counting case. AG4 preserves rank one by design; its reworded answer lists have lower NDCG@10.

Multiple Choice (MC)

Data used	Organizer-provided questions and options, plus our AG3 first answer or the original video. No training or correct test answers were used.
What we tried	**MC1**: match our AG3 answer to the supplied options. **MC2**: revisit the video when a text check finds an uncertain or inconsistent option match. **MC3**: rank options from every available video with Gemini 3.7. **MC4**: use the same approach with Gemini 3.8.
What changed	Accuracy rises from 78.748% (MC1) to 83.402% (MC2) and 84.514% (MC3). MC4 scores 84.308%.
What helped?	Using video predictions wherever available adds 27 correct choices over targeted review, using the same Gemini 3.7 predictions.
What we learned	Full video review fixes 219 text-only errors but introduces 79 errors. Counting remains difficult: MC3 gets 200 of 309 "how many" questions right.

Overview

We submitted four AG and four MC runs covering 2,443 questions from 1,956 videos. AG returns ten ranked answers; MC ranks the released options [1, 2]. We used the revised MC options. Official scoring covers 2,428 questions after 15 exclusions. Figures 1 and 2 explain the submissions; each task section then presents its results and limitations.

1 Answer Generation

1.1 What we submitted




Figure 1: The question is supplied to every model call. Models generate answers independently; arrows carry inputs or saved outputs, not one model's answer into another model. Each submission contains ten ranked answers. AG4 operates on saved text; Section 3 shows actual semantic groups.

AG1: Qwen3.5 frame baseline. For each available video, we sample the midpoint of each of 12 equal intervals. Ten unavailable-video rows used only the question and were excluded from official scoring. Qwen3.5-4B returns a short answer, then nine alternatives from the same frames. When the model does not produce ten distinct answers, we first request a repair, then fill any remaining positions with predefined generic answers. These fillers occupy 650 of 24,430 positions; they are not predictions from the video.

AG2: combined Qwen3.6 answers. We submitted one list of ten answers per question. To build it, we called Qwen3.6-27B twice on the same video payload, once without and once with speech transcribed into timestamped text by Whisper. Both outputs feed the same submission: the answer from video plus Whisper text first, then the video-without-transcript answer and baseline alternatives, with duplicates removed. Requests use temperature zero, disabled thinking, and a 64-token output cap. We do not assume the video path consumes native audio.

AG3: Gemini-first fusion. Gemini 3.7 Flash answers from audio-video at 4 frames per second, low media resolution, high thinking, and a 2,048-token output cap. Its successful answer goes first; Qwen and baseline candidates fill the list. Missing or failed sources are skipped and duplicates removed. This is a fixed priority for every question, not a learned confidence rule.

AG4: grouped rewrite. Gemini 3.7 Flash receives the saved first answers from the four source calls and generates ten candidates, grouping equivalent meanings and retaining conflicting answers separately. AG3's first answer stays first. If the rewrite fails our checks, we keep AG3's original list.

Development evidence. A small matched 2025 comparison motivated the use of speech transcripts; Appendix A gives the setup and results. It is not an ablation of AG2, which also changes the model and video input.

1.2 Results

Scores are from the organizer release [3]. **Official AG results.** AG3 and AG4 tie on METEOR; AG2 has the highest BERTScore, .000896 above AG1; AG1 narrowly leads STS. Statistical significance was not tested. This pattern also holds with human-only references. AG4 keeps AG3's first answer but has lower ranked-list scores: METEOR NDCG@10 falls from .861585 to .812896. STS and BERTScore NDCG@10 also fall in both reference modes.

Run	STS@1	METEOR@1	BERTScore F1@1
AG1 — `q35_4b_u12`	.485552	.170537	.890737
AG2 — `q36_dualview`	.465828	.188578	.891633
AG3 — `g37_q36_fusion`	.484527	.318244	.878867
AG4 — `g37_grouped_unique`	.484527	.318244	.878867

Table 1: Official AG rank-one similarity using human plus alternative references. These scores are not accuracy. NDCG measures discounted relevance across the ranked list; AG4 changes candidate wording as well as ordering.

1.3 A recurring error family: wrong counts

Counting disagreements recur across the test set. Among 309 questions containing "how many," MC3 misses 109. In **76 of those 109 misses**, both its selected option and the official option are explicit numbers and the numbers differ. We compare integer digits and number words (zero–twenty), excluding vague quantities. This measures disagreement, not its cause.

A clear inspected case (Q_ID 106; video `8008.webm`). The question asks how many people are shown. In a 1-fps inspection, we see two people, agreeing with the official MC answer, "2." AG3 instead answers "4 people (two main subjects and two partially visible in the foreground)." MC3 also selects "4." MC1 and MC2 also select four, while MC4 selects the official count. We did not find the additional foreground people in the inspected frames. AG1 answers "2," which AG3 retains at rank three below Gemini's "4" answer.

1.4 Wording and similarity scores

Section 3 follows one weather question through AG scores, recorded AG4 groups, and MC choices. Equivalent answers receive different METEOR scores, and a contradictory answer receives near-perfect BERTScore. MC3 and MC4 also make different choices despite their shared direct-video approach.

2 Multiple Choice

2.1 What we submitted

All runs rank the organizer's options. MC1 uses *our AG3 first answer*, generated before seeing the options; it does not receive the organizer's correct answer.

MC1: text only. Gemini 3.7 Flash receives the question, AG3's first answer, and every option, then ranks the options.

MC2: selected video checks. A separate text-model call checks how well our saved answer matches the options. We request video review if the match is partial or absent, the checker asks to see video, or MC1's first choice is outside the checker's closest matches. This selects 798 questions. We use valid video rankings for 786 of them and retain MC1 for the other 12 and all questions not selected.




Figure 2: One row per submission. Only MC2 chooses which questions receive video rankings; it reuses the same video predictions as MC3. Video calls receive no saved AG answer. If a video ranking is unavailable or invalid, retain MC1.

MC3: video review throughout. Gemini 3.7 receives audio-video, the question, and options at 4 frames per second, low resolution, and high thinking. It does not see saved AG answers or text rankings. Valid video rankings replace MC1 on 2,423 questions; 20 retain MC1 because media is unavailable or output is invalid. MC2 reuses these same video predictions.

MC4: Gemini 3.8 video review. This follows MC3's approach with Gemini 3.8 Flash: 2,428 valid video rankings and 15 MC1 fallbacks. These submission counts precede the organizer's exclusion of 15 questions.

2.2 Results

Official MC results. Full Gemini 3.7 review has 140 more correct first choices than text only and 27 more than targeted review (Table 2). Paired organizer rows show 219 text-only errors corrected by MC3 and 79 text-only successes lost, giving the net gain of 140. Gemini 3.8 has five fewer correct answers than 3.7; this does not establish a general model advantage. These are descriptive comparisons of the submitted runs.

Run	Correct / 2,428	Accuracy	MRR
MC1 — `g37q36_mc_text`	1912	78.748%	.864605
MC2 — `g37_mc_target`	2025	83.402%	.896845
MC3 — `g37_mc_direct`	2052	84.514%	.905653
MC4 — `g38_mc_direct`	2047	84.308%	.905368

Table 2: Official MC scores on the same 2,428 questions. MRR is mean reciprocal rank.

MC3 ranks second among organizer-listed runs: 2,052 correct versus the leader's 2,058 (84.761%). Every official correct answer appears in each submitted ranking; errors arise from placing another option first.

On the 309 "how many" questions, MC3 gets 200 right (64.7%), versus MC2's 205 and MC4's 204. MC3 fixes 24 MC1 errors but introduces 21; its overall advantage does not hold in this lexical group.

3 One example across scoring, grouping, and choice



Question: "What is the weather like when someone is filming the white building?"

Q_ID 1835; Video_ID `8083.webm`; frame at 2 s.

Official MC answer: "Sunny." The frame illustrates the clip; it is not a reconstructed model input.

A. Wording and correctness are different from similarity scores.

Run	Actual first answer	STS	METEOR	BERTScore F1
AG1	rainy	.552	.000	.999
AG2	Sunny	1.000	.500	1.000
AG3 / AG4	It is sunny.	1.000	.992	1.000

"Sunny" and "It is sunny." agree but differ in METEOR. The contradictory "rainy" still receives BERTScore .999436 (rounded above). These are official all-reference scores; AG reference text is unavailable in the score files.

B. AG4 merges equivalents and retains the conflicting source.

Sunny group: three saved sources

Gemini: "It is sunny."
Qwen + transcript: "Sunny"
Qwen video payload: "It's sunny."

Submitted ranks and answers

1. It is sunny. *(kept; rank 1 fixed)*
3. Sunny *(kept)*
4. It's sunny. *(kept)*
6. The weather is sunny. *(new)*
8. Bright and sunny. *(new)*
10. Sunny weather. *(new)*

Rainy group: one saved source

Qwen3.5: "rainy"

Submitted ranks and answers

2. rainy *(kept)*
5. The weather is rainy. *(new)*
7. It is raining. *(new)*
9. Rainy weather. *(new)*

Figure 3: Recorded groups and all ten AG4 answers: four sources retained and six variants added. Sunny occupies six ranks and rainy four, interleaved as shown. Allocation and order are generated, not fixed quotas.

AG4 requires an unchanged first answer, an exact source per group, and normalized-distinct strings. It groups saved text without revisiting video; ten wordings need not mean ten interpretations or removal of wrong answers.

C. MC matches the saved answer or ranks from video.


All supplied choices: Sunny; Partly cloudy; Cloudy; Windy; Foggy; Rainy; Stormy; Snowy. Display order follows MC1's ranking.

Run	Method	First choice	Result	Rank of Sunny
MC1	Saved-answer match	Sunny	Correct	1
MC2	Targeted review	Sunny	Correct	1
MC3	Video, Gemini 3.7	Rainy	Incorrect	7
MC4	Video, Gemini 3.8	Sunny	Correct	1

MC1 maps AG3's "It is sunny." to "Sunny." MC3 selects "Rainy," while MC4 selects "Sunny"; neither receives saved AG answers or AG4 groups. This case was selected to illustrate all three panels: its MC pattern occurs in 20/2,428 questions, whereas MC3 gains 140 correct choices overall versus MC1. It does not establish a sampling cause or that text generally outperforms video.

4 Shared errors and equivalent answer choices

Our four MC runs share **271 failures**. We reviewed these to ask whether the models misunderstood the video or whether the answer choices themselves caused a mismatch. Two clear examples show the latter: **the same count appears as two different choices**.



Q_ID 2049; 50 s
`Archipelago-42.webm`

"How many people in the video are wearing a hat?"

Official choice: "One"

All four runs choose:
"One person is wearing a hat"

Same count; different scoring. Every run selects the longer answer and is marked wrong.

Figure 4: Both wordings are organizer-provided choices. The frame illustrates the clip; it is not a reconstructed model input.

"How many beds are in the house?"

Q_ID 1369; `Memphis-18.webm`

Official choice	All four runs choose
"One"	"One bed"

What this tells us. More video evidence cannot distinguish "One" from "One bed" as answers to a bed-count question. These are failures to select the designated wording, not disagreements about the count. They do not show that the count label itself is wrong.

We keep the official scores unchanged. This audit covers our runs only; question-level results for other teams were unavailable. Appendix B records the audit method and unresolved cases.

Drafting assistance. Codex assisted with writing, diagrams, and source checks. Author review and final model references remain to be completed.

References

[1] NIST. *TRECVID 2026: Video Question Answering guidelines.* https://www-nlpir.nist.gov/projects/tv2026/vqa.html.

[2] A. F. Smeaton, P. Over, and W. Kraaij. Evaluation campaigns and TRECVid. *MIR*, 2006, pp. 321–330. doi:10.1145/1178677.1178722.

[3] NIST. *TREC VQA 2026 evaluation results.* Participant release, September 2026. AG workbook and NP Labs MC scores; archived at repository revision `3efb5b19dbd6d8d59232986cc25ef049af24ba5e`.

A Development comparison

We compared Qwen3.5-4B on the same 30 labeled 2025 videos and questions, using either 12 uniformly sampled frames or those identical frames plus a quality-accepted Whisper large-v3 transcript. Rejected transcripts were replaced by null input. The selected panel contains six questions each on speech, sound/music, temporal actions, spatial/OCR/color, and visual controls.

Input to Qwen3.5-4B	Exact matches	Token F1	Speech F1
12 frames	9/30	.431	.431
Same frames + Whisper	11/30	.507	.700

Exact match compares normalized answer strings. Token F1 combines normalized token precision and recall; scores are averaged over questions. Speech F1 uses the six speech questions. Neither condition exactly answers any of the six sound/music questions. This exploratory development comparison motivated transcripts for speech; it does not estimate 2026 performance or isolate AG2's effect.

B Shared-error audit details

We joined the four official MC result files on question ID and checked all shared misses against the revised options and frozen rankings. Of 271 shared misses, 194 have the same first choice across runs and 77 have different choices. The runs are related: MC2 reuses MC1 or MC3 rankings.

We screened all shared question/reference/selected-answer pairs and inspected eight deliberately selected clips. The two count-equivalence examples in Section 4 both place the official wording second in every run. Their option sets contain further equivalent pairs, including "Two"/"Two beds" and "None"/"No one is wearing a hat."

The other inspected questions were Q14, Q351, Q1291, Q1538, Q1610, and Q1757. A bridge-description pair is a possible synonym; timing or visual detail remains unresolved in the others. These targeted inspections do not estimate label-error prevalence. We have no question-level results for competing teams and make no claim about shared errors with the leaderboard leader.