
Gene Finding

Nick Carter

Aug 28, 2026

CONTENTS:

1	API Reference	3
1.1	lib.dataloader.trainloader	3
	Python Module Index	5
	Index	7

Add your content using reStructuredText syntax. See the [reStructuredText](#) documentation for details.

API REFERENCE**1.1 lib.dataloader.trainloader**

`lib.dataloader.trainloader.fsmStateToOneHot(fsmState)`

Convert a character representing a state in the FSM to a one-hot training vector

Expects *fsmState* to be a single character string, in the set “0-9,A-E”. Returns a one-hot tensor of float32 values, with 1.0 in the position corresponding to the state, and 0.0 elsewhere Returns “None” if the input is not a valid state character

`lib.dataloader.trainloader.nucleotideToOneHot(nucleotide)`

Convert a character representing a nucleotide to a one-hot training vector

Expects *nucleotide* to be a single character string, in the set “ACGT”. Returns a one-hot tensor of float32 values, with 1.0 in the position corresponding to the nucleotide, and 0.0 elsewhere Returns “None” if the input is not a valid nucleotide character

PYTHON MODULE INDEX

|

`lib.dataloader.trainloader`, 3

INDEX

F

`fsmStateToOneHot()` (in *module*
lib.dataloader.trainloader), 3

L

`lib.dataloader.trainloader`
module, 3

M

module
lib.dataloader.trainloader, 3

N

`nucleotideToOneHot()` (in *module*
lib.dataloader.trainloader), 3