

```

/*
    lab5.c
    Nathan Christian Copyright (C) (nchristi@iu.edu) 2017
    ALL FUNCTIONS ARE LOCATED IN FUNCS.C
*/
#include <stdio.h>
#include <stdlib.h>
#include "fig.h"
#include "shape.h"
#define MAXBUF 1024
#define MAX      64

int main(int argc, char *argv[], char *env[])
{
    Polygon p;
    Polyline l;
    Circle c;
    Arc a;

    Point temp_low, temp_high, phigh, plow, lhigh, llow;
    Point chigh, clow, ahigh, alow, low, high, center;
    high.x=high.y=ahigh.x=ahigh.y=chigh.x=chigh.y=-1000000;
    lhigh.x=lhigh.y=phigh.x= phigh.y=-1000000;
    low.x=low.y=alow.x=alow.y=clow.x=clow.y= 10000000;
    llow.x=llow.y=plow.x=plow.y=1000000;
        //Initializes Points used to find high/low
boundaries

    int i;
    double dist, angle=90;
        //Initialize angle to default of 90
degrees

    char buffer[MAXBUF], command[MAX], filename[MAX], language[MAX];

    for(i=1;i<argc;i++){
        if (argv[i][0]=='-'){
            switch (argv[i][1]){
                case 'h': case 'H':
                    print_help();
                    //Help function
located in funcs.c

                    break;
                case 'A': case 'a':
                    if (argv[i+1] != NULL)
                        sscanf(argv[i+1],
"%lf", &angle);
                    //change angle when entered

                    break;
                case 'l': case 'L':
                    strcpy(language,argv[i+1]);

                    break;
                case 'v': case 'V':

```

```

5.0");

printf("The version is
break;
case 'O': case 'o':
    strcpy(filename,argv[i+1]);
    //User selects file to open
break;
}
}
angle=(angle*M_PI/180);
//convert degree to radians

FILE *fin, *fout;
fin = fopen(filename, "r");
if (fin == NULL) {
    fprintf(stderr, "Can't open file. Enter lab5 -h for help.");

    exit(1);
    //basic error statement for NULL file
}

if (!strcmp(language,"fig") ||!strcmp(language, "FIG")){
    fout=fopen("output.fig", "w");
    fig_open(fout);
    fig_userinfo(fout, 1, "ECE263L5P1", "Nathan Christian",
"6/27/2017");
}

//fig data prints on fig files
only

else if (!strcmp(language,"shape") ||!strcmp(language, "SHAPE"))
    fout=fopen("output.txt", "w");

else {
    printf("Error! Choose 'fig or 'shape'. Enter lab5 -h for
help.");
    exit(1);
    //Error statement for files not
shape or fig
}

while (fget_line(buffer, MAXBUF, fin)) {
    //Reads one line at a time

    if (!strcmp(language,"shape") ||!strcmp(language,
"SHAPE"))
    {
        for (i=0; buffer[i]!='\0';i++){
            if (buffer[i]=='#')
                buffer[i]='\0';
        }
    }
}

```

```

        fprintf(fout, "%s\n", buffer);
        //For shape files, prints the
clean output to output.txt
    }

    else{
        sscanf(buffer, "%s", command);
        //Scans the first line to
determine shape type

        if (!strcmp(command, "polygon")) {
            polygon_sscanf(buffer, &p);
            polygon_draw(fout, &p, NULL);
            polygon_boundary(&p, &temp_low,
&temp_high);
            //Finds high/low of all shapes on
each line.

            high_low(&plow, &phigh, &temp_low,
&temp_high);
            //Finds high/low of all shapes in
file. Located in funcs.c
        }

        else if (!strcmp(command, "polyline")) {
            polyline_sscanf(buffer, &l);
            polyline_draw(fout, &l, NULL);
            polyline_boundary(&l, &temp_low,
&temp_high);
            //Finds high/low of all shapes on
each line.

            high_low(&llow, &lhigh, &temp_low,
&temp_high);
            //Finds high/low of all shapes in
file. Located in funcs.c
        }

        else if (!strcmp(command, "circle")) {
            circle_sscanf(buffer, &c);
            circle_draw(fout, &c, NULL);
            circle_boundary(&c, &temp_low,
&temp_high);
            //Finds high/low of all
shapes on each line.

            high_low(&clow, &chigh, &temp_low,
&temp_high);
            //Finds high/low of all shapes in
file. Located in funcs.c
        }

        else if (!strcmp(command, "arc")) {

            arc_sscanf(buffer, &a);
            arc_draw(fout, &a, NULL);
            arc_boundary(&a, &temp_low,
&temp_high);
            //Finds high/low of all
shapes on each line.

            high_low(&alow, &ahigh, &temp_low,
&temp_high);
            //Finds high/low of all shapes in
file. Located in funcs.c
        }
    }

```

```

    }

    else
        fprintf(stderr, "Unknown shape:
[%s]\n", buffer);
        //Error for unknown shape
    }

    if (!strcmp(language,"fig") ||!strcmp(language, "FIG")){
        high_low(&low, &high, &alow, &ahigh);
        high_low(&low, &high, &clow, &chigh);
        high_low(&low, &high, &llow, &lhigh);
        high_low(&low, &high, &plow, &phigh);
        center.x=low.x+((high.x-low.x)/2);
        center.y=low.y+((high.y-low.y)/2);
        //Finds high/low of all points and center of
entire shape.

        rewind(fin);
        //Rewinds file so we can read it
again.
    }

    else
        exit(1);

    while (fget_line(buffer, MAXBUF, fin)) {
        //Now that centerpoint is known, file is read again
to rotate.

        if (!strcmp(language,"fig") ||!strcmp(language, "FIG")){

            sscanf(buffer, "%s", command);

            if (!strcmp(command, "polygon")) {
                polygon_sscanf(buffer, &p);

                for (i=0; i<p.npoints;i++){
                    polygon_move(&p, angle,
center);
                    p.vertex++;
                    //Move to the next
coordinate and rotate until n.points are reached
                }

                for (i=0; i<p.npoints;i++)
                    p.vertex--;
                //Rewind shape for
drawing/printing.

                polygon_draw(fout, &p,
"color=red;line_style=1");
                //draw the rotated shape
            }

```

```

else if (!strcmp(command, "polyline")) {
    polyline_sscanf(buffer, &l);

    for (i=0; i<l.npoints;i++){
        polyline_move(&l, angle,
//Rotates shape. function
center);
located in func.c
        l.vertex++;
//Move to the next
coordinate and rotate until n.points are reached
    }
    for (i=0; i<l.npoints;i++){
        l.vertex--;
//Rewind shape for
drawing/printing.

        polyline_draw(fout, &l,
"color=red;line_style=1");
    }

else if (!strcmp(command, "circle")) {
    circle_sscanf(buffer, &c);
    dist=distance(c.center, center);
//dist function using pythagorean
theorem

    circle_move(&c, angle, dist, center);
//Rotates shape. function located in
func.c

    circle_draw(fout, &c,
"color=red;line_style=1");
    }

else if (!strcmp(command, "arc")) {

    arc_sscanf(buffer, &a);
    dist=distance(a.center, center);
    arc_move(&a, angle, dist, center);
//Rotates shape. function located in
func.c

    arc_draw(fout, &a,
"color=red;line_style=1");
    }

    }

    fclose(fin);
    fclose(fout);

    // after use, close the files
}

```