

This script applies KF to the measurement data. There is a provision to apply estimate filtering to reject spurious estimates. This filtering using either innovation covariance or mixture model of the sensor.

```
In [16]: # -*- coding: utf-8 -*-
        """
        Created on Mon Nov 13 15:17:51 2017

        @author: Nishant
        """
        import math
        import csv
        import numpy as np
        import matplotlib.pyplot as plt

        # Calculates stats for given data
        def stats(reads):
            mu=sum(reads)/len(reads)
            sq=[x*x for x in reads]
            sig=sum(sq)/len(sq)-mu*mu
            return mu,sig

        # Returns value of Gaussian pdf of mixture for a passed measurement xs
        def sample_from_gaussian(pdf,x):
            pow=-1/2*(x-pdf[0])*(x-pdf[0])/(pdf[1])
            return (1/np.sqrt(2*math.pi*pdf[1]))*np.exp(pow)

        # Returns value of exp decay pdf of mixture for a passed measurement xs
        def sample_exp_decay(xs):
            return 0.05*np.exp(-0.05*xs)

        # Declaration of some global lists
        x_measures=[]
        x_measurescm=[]
        x_estimates=[]
        v_estimates=[]
        sigx=[]
        sigv=[]
        sigxv=[]
        T=[0]

        # Returns a list corresponding to proportion of xi belonging to different components
        def get_mixture_probs(xp,xs):
            return [0.8*sample_from_gaussian([xp[0][0],0.001],xs),0.2*sample_exp_decay(xs)]
```

```

In [17]: # Takes in system Markov model i.e. A,P,R,q, Current measurement xs, Prior xm
# Outputs updated state estimate and updated uncertainty
def KF(xm,xs,P,R,A,q,n,td):

    b=np.array([[+(td**3)*0.01*(0.1**3)-(0.1**3)*0.01*(0.1**3), (td**2)*0.01*(0.1**3),
    c=np.array([[0,(td-1)*0.1],[0,0]])

    A=np.array(A)-np.array(c)
    q=np.array(q)+np.array(b)

    x_predicted=A*xm
    Pn=np.dot(A,P*np.transpose(A))+q
    H=np.asmatrix([1,0])

    a=np.dot(H,(Pn*np.transpose(H))+R)
    K=Pn*np.transpose(H)/a
    #K=np.reshape(np.array([K[0][0],K[1][0]]),(2,1))

    if n==1:
        x_posterior=x_predicted+K*(xs-H*x_predicted)
        P_posterior=(np.identity(2)-K*H)*Pn

        T.append(T[-1]+0.1)
    elif n==2:
        x_temp=x_predicted+K*(xs-H*x_predicted)
        P_temp=(np.identity(2)-K*H)*Pn
        delta=xs-float(x_temp[0])
        inno=np.dot(H,(P_temp*np.transpose(H)))
        var=delta*delta/inno
        if var<9:
            x_posterior=x_predicted+K*(xs-H*x_predicted)
            P_posterior=(np.identity(2)-K*H)*Pn
            T.append(T[-1]+0.1*td)
            td=1

        else:
            td+=1
            return np.array([]),np.array([]),td

    elif n==3:
        x_temp=x_predicted+K*(xs-H*x_predicted)
        p=get_mixture_probs(x_temp,xs)

        if p[0]>p[1]:
            x_posterior=np.array(x_predicted)+np.array(K)*(xs-np.dot(H,x_predicted))
            P_posterior=(np.identity(2)-K*H)*Pn
            T.append(T[-1]+0.1*td)
            td=1
        else:
            td+=1
            return np.array([]),np.array([]),td

    return x_posterior,P_posterior,td

```

```

In [18]: # Iterates through measurement data, updates posteriors using KF and stores it to
def estimate(n):
    P0=np.array([[0.01, 0],[0, 0.01]])
    x0=np.asmatrix([25.30,.1]).T
    R=0.001
    Q=[[0.01*0.1*0.1*0.1, 0.01*0.1*0.1],[0.01*0.1*0.1,0.01*0.1]]
    A=[[1,-0.1],[0,1]]
    t=1

    for i in x_measures:
        xm=i
        xt,Pt,t=KF(x0,xm,P0,R,A,Q,n,t)
        if xt.tolist()!=[] and Pt.tolist()!=[]:
            x_estimates.append(float(xt[0])*100)
            v_estimates.append(float(xt[1])*100)
            sigx.append(np.sqrt(Pt.tolist()[0][0]*10000))
            sigv.append(np.sqrt(Pt.tolist()[1][1]*10000))
            sigxv.append(Pt.tolist()[0][1]*10000/np.sqrt(Pt.tolist()[0][0]*10000))
            x0=np.asmatrix(xt)
            P0=np.asmatrix(Pt)

```

KF without object rejection

```

In [19]: #Script starts from here
#Reading data file and queuing data
with open('RBE500-F17-100ms-Constant-Vel.csv', newline='') as csvfile:
    spamreader = csv.reader(csvfile, delimiter=' ', quotechar='|')
    spamreader=list(spamreader)
    for row in spamreader:
        x_measures.append(float(row[0])/100)
        x_measurescm.append(float(row[0]))

# Input the following numbers as arguments to estimate() for the corresponding pos.
# 1: Conventional KF    2: KF with object rejection (innovation)  3: KF with objec
estimate(1)

# Plot data
T.remove(0)
Ta=np.arange(0.0, 30.0, 0.1)

plt.scatter(Ta,x_measurescm,s=4,label='Raw')
plt.scatter(T,x_estimates,s=8,label='Estimates')
plt.xlabel('Time')
plt.legend()
plt.ylabel('Range estimates (cm)')
plt.show()




plt.scatter(T,v_estimates)
plt.xlabel('Time')
plt.ylabel('Velocity estimates (cm/s)')
plt.show()



plt.scatter(T,sigx)
plt.xlabel('Time')
plt.ylabel('Range Standard Deviation (sqcm)')
plt.show()

plt.scatter(T,sigv)
plt.xlabel('Time')
plt.ylabel('Velocity Standard Deviation (sq(cm/sec))')
plt.show()

plt.scatter(T,sigxv)
plt.xlabel('Time')
plt.ylabel('Position Velocity Correlation (sqcm/sec)')
plt.show()

```





Interpretation: It can be seen that KF doesn't handle the sudden variations in measurements due to external sources very well. If the data is not sufficient it may output wrong estimates. Also the velocity estimate can be seen to spike during external disturbance which may also affect the estimates in the case of insufficient data.