

CSCI 470/502 - Assignment 2 - Spring 2023

Write a console-based Java application to help an airline frequent flyer member find out good ways of redeeming their accumulated mileage into air tickets. Assume all trips depart from ORD. Different destinations need different mileage for redeeming tickets. If the person doesn't travel in a busy season, s/he may take advantage of the "supersaver" program that can get a ticket with fewer accumulated miles.

A list of destination cities and related ticket redeem information can be read from a file, which is formatted as one city per line, 5 fields are separated using ";" as below:

destination; normal mileage needed for an economy class ticket (this information is proportional to the actual travel distance); supersaver mileage needed for an economy class ticket; additional mileage needed for upgrading to first class; and the months of departure when supersaver mileage can be used.

For example:

```
Hyderabad;30000;20000;15000;2-4
Sydney;50000;30000;20000;5-6
Paris;20000;15000;10000;2-4
New York;10000;5000;8000;10-11
```

The name of the file (such as "miles.txt") should be passed to the program as a command line argument.

Your algorithm should 1) try to get tickets that travel the farthest. 2) Use supersaver whenever possible. 3) try to get as many as different tickets as possible; (at most 1 ticket is needed for 1 destination) 4) use the remaining mileage for upgrade, if possible (try to upgrade the longest trip first).

Your program should first print out a list of the cities for the user's information. It then loops for inputs and prints out tickets that can be redeemed. Here is a sample program output:

Sample program output:

```
-----
List of destination cities you can travel to:
Hyderabad
New York
Paris
Sydney
-----
```

Please input your total accumulated miles: 49600

Please input your month of departure (1-12): 4

Your accumulated miles can be used to redeem the following tickets:

- * A trip to Hyderabad, economy class
- * A trip to Paris, economy class
- * A trip to New York, economy class

Your remaining miles: 4600

Do you want to continue (y/n)? n

Another test case: With a total of 69000 miles and a planned departure in July, you can get an economy class ticket to Sydney and a first class ticket to New York, with 1000 miles remaining.

The classes

Write a class `Destination`. This class encapsulates information such as the name of the destination city; normal miles for a ticket; supersaver miles; additional miles for upgrading; start month of the supersaver program and end of the supersaver program. Private instance variables and access methods are written for this information. A constructor that takes in all these information is also needed.

Also write a class `MileRedeemer` to encapsulate the logic for redeeming mileage. This class should have private instance variables for an array of `Destination` objects, and an integer to represent the remaining miles after the user's miles have been redeemed. Initialize the remaining miles to 0.

You should also create methods in `MileRedeemer` such as:

```
public void readDestinations(Scanner fileScanner);
public String[] getCityNames();
public String[] redeemMiles(int miles, int month);
public int getRemainingMiles();
```

For the first method, we use a `Scanner` object as the input parameter for flexibility and reusability. For example, we could reuse the method to read files from a web URL. This method should use the `Scanner` object to read and parse the destination data into an array of `Destination` objects, which should then be sorted by their normal mileage (see below).

The second method should loop through the array of `Destination` objects and create an array of `String` objects from the city names. This array can be sorted in ascending order and returned (to be printed out by the main program).

For `redeemMiles()`, `miles` is the total available miles, and `month` is the desired month of departure. To avoid writing one huge method, you can (and probably should) have the `redeemMiles()` method call some other methods to accomplish subtasks as part of the larger overall algorithm. This method should return an array of `String` objects containing descriptions of redeemed tickets to be printed out by the main program. It should also save the miles remaining after the tickets have been redeemed.

The last method should return the saved remaining miles.

You should also write a main class, e.g. `MileRedemptionApp`, that will have the `main()` method, which contains the loop for user interaction. The `main()` method will get the command line argument, use the filename to create the `Scanner` object, create an instance of `MileRedeemer`, tell it to read in the destination data, get the city names and print them out, read the data input by the user, `redeemMiles()` to get the list of tickets that may be redeemed, and `getRemainingMiles()` to get the miles remaining. All of the normal I/O and interaction with the user should be done in methods of your main class, not in the `MileRedeemer` class.

Remember that only one class per source code module can be public. So if all classes for this project are placed in one source code file, only the `MileRedemptionApp` class that contains the `main()` method should be public. If each class is in its own separate source code file, each class should be designated as public.

A hint: if an user answers 'y' or 'Y', an additional method call to `scanner.nextLine()` will be needed before the program proceeds to the next iteration. This is for the scanner to pass the current line.

File IO and String parsing

The `Scanner` class can be used to read the lines from the file. Before reading the lines, a `java.util.ArrayList` should be created:

```
ArrayList<Destination> destinationList = new ArrayList<Destination>();
```

As lines are read from the input file, the lines need to be parsed (broken into fields) using `"` as the delimiter. Instances of `Destination` are created and added to the list. There are a variety of different ways to parse a `String` into fields. One easy way is to use the `split()` method of the `String` class.

After the whole file is read, the `ArrayList` can be converted to a normal array of objects:

```
Destination[] destinationArray = (Destination[]) destinationList.toArray(new  
Destination[destinationList.size()]);
```

This way we can take advantage of Java's built-in methods for sorting an array.

Sorting

The cities in the input text file might be listed in any order. The `redeemMiles()` method needs to sort the destinations in descending order based on their distances. The class `java.util.Arrays` has a static `sort()` method that takes an array and a `Comparator`. The latter is an object of a class that defines the ordering:

```
class MileageComparator implements Comparator<Destination> {  
  
    public int compare(Destination d1, Destination d2) {  
  
        return (d2.getNormalMiles() - d1.getNormalMiles());  
  
    }  
  
}
```

The array of city name strings created and returned by `getCityNames()` can also be sorted using a version of `Arrays.sort()`. There's no need to write a comparator in this case; the "natural ordering" of the strings will be sufficient.

Input verification and exception handling

The `main()` method should verify the number of command line arguments before taking in the file name.

If the program encounters problems in opening the file or input type errors during reading/parsing the file, the program prints out an error message, then exit.

If input type mismatch is thrown during getting console input, the program prints out an error message and then proceed directly to the question of "Do you want to continue (y/n)?".

IMPORTANT: Read the document "[Java Coding and Documentation Style Guidelines](#)" again before you submit your final program for inspection grading.

The assignment will be submitted through Blackboard as before. If you work in a group, only one submission is needed for the entire group. The same student should submit the assignments for the group throughout the semester.

A question for pondering (no need to submit): Think about the design of the classes in this assignment. Would you do it differently if you were not given the details of the classes and methods?