milestone

Specification Sheet

Husky XE 700R

July 21. 2025

1. Feature Overview

Husky XE 700R is a member of Milestone Husky portfolio optimized for BriefCam software. Husky XE 700R is a rack-mount unit designed to be running as (1) Database Server (2) Research Server.

The unit's performance in various scenarios have been analyzed and optimized and can be used as in other scenarios suggested by Milestone calculators, design charts, lookup tables and package finder toolsets.

1.1 Key Features

- Rack-mount unit – ideal for those with an existing IT infrastructure
- Only Windows variant is available
- Fully tested and optimized for BriefCam software compatibility

1.2 Recommended Usage

- As member of BriefCam portfolio, as (1) Database Server (2) Research Server

SKUs

- HXE700R-16TB-00WS

2. Hardware Information

- **Form Factor**
  - Rack mounted 1U
- **CPUs**
- Intel Xeon E-2436
- **GPU**
  - N/A
- **RAM**
  - 64 GB DDR5
- **Operating system (OS)**
  - Windows Server IoT Storage Standard 2022
- **Boot Drive Storage**
  - 2 x 960 GB (RAID1)
- **Number of hard drives**
  - 4 x 3,5" 4TB HDDs
- **Display ports**
  - 1 x DB-15 VGA
- **Network interface**
  - 6 x 1 GbE (RJ45) + 1 x 1 GbE iDRAC/Mgmt (RJ45)
- **Credential and key encription**
  - Trusted Platform Module (TPM 2.0)
- **Redundant power supply**
  - Yes
- **Remote management**
  - Yes

2.1 General Information

- **Hardware warranty**
  - 5 years full system warranty (incl. HDD) Onsite support next business day[1]
- **Dimensions**
  - 482 mm x 42,8 mm x 563,3 mm
  - 18,976" x 1,685" x 22,177"
- **Weight**
  - 13.23 kg (min)
  - 29.17 lb (min)
- **Power input**
  - 100~240V, 50/60 Hz
- **Power supply**
  - Dual, 600W hot-plug redundant
- **BTU rating**
  - 2250 BTU/h (max theoretical)

2.2 Environmental

This unit is intended for stationary server room and office use, according to the conditions stated below.

- **Operating temperature**
  - 10º – 35º C
  - 50º – 95º F
- **Storage temperature**
  - -40º – 65º C
  - -40º – 149º F
- **Humidity**
  - 10 – 85% relative humidity (non-condensing)

2.3 Regulatory

- **Regulatory Model and Type**
  - Model E77S, Type E77S002

[1] Onsite intervention dispatched following Milestone's support processes – hardware Service Tag information accuracy required. Subject to regional availability, dependent on Dell Technologies support network. Dell Technologies onsite support service will be given on a best effort basis conditioned upon the location of the Husky unit. Onsite support services like NBD or 4HR are being counted from the moment Dell Technologies' troubleshooting is finalized and conditioned upon the hour and the day of the week the troubleshooting finishes.

Milestone reserves the right to correct errors and typos in these data sheets. For the latest version of this document, always check our website

Previous revisions from the available stock may still be delivered during transition phases to refreshed revisions.



About Milestone Systems

Milestone Systems is a leading provider of data-driven video technology software in and beyond security that helps the world see how to ensure safety, protect assets, and increase business efficiency. Milestone enables an open platform community that drives collaboration and innovation in the development and use of network video technology, with reliable and scalable solutions that are proven in more than 500,000 customer sites worldwide. Founded in 1998, Milestone is a stand-alone company in the Canon Group.

www.milestonesystems.com