

Cambium ePMP 5 GHz Force 300-25 High-Gain Radio

Part Number / SKU: C050900C201A • 5 GHz 802.11ac Wave 2 High-Gain
Point-to-Point and Subscriber Station

Key System Highlights:

- High-gain 25 dBi parabolic dish antenna providing multi-kilometer connectivity
- Over 500 Mbps peak real TCP/IP throughput using 80 MHz channelization
- Proprietary ePMP TDD protocol provides high interference tolerance in noisy RF spectrum
- Gigabit Ethernet interface with 30V passive PoE input
- Configurable as long-range PtP bridge pair or subscriber to ePMP 3000 access points



WIRELESS & RADIO SPECIFICATIONS

Frequency Band	4910 to 5970 MHz (5 GHz UNII-1/2/3/ISM)
Max Throughput	500+ Mbps real TCP/IP throughput
Antenna Gain	25 dBi dish reflector
Channel Width	20 / 40 / 80 MHz
Modulation	256-QAM (802.11ac Wave 2 TDD)

HARDWARE & ENVIRONMENTAL

Interface	1x 10/100/1000Base-T RJ-45
Power Input	30V Passive PoE (Gigabit injector included)
Power Consumption	12W maximum
Dimensions / Weight	Dish Dia. 470 mm (18.5 in) / 2.4 kg (5.3 lbs)
Enclosure Rating	IP55 Weatherproof; -30°C to +60°C operating temperature

RECOMMENDED ACCESSORIES, MOUNTS & LICENSES

Category	Manufacturer SKU	Description	Est. MSRP
Surge Suppressor	C000000L065A	Cambium Outdoor Gigabit Surge Suppressor	\$75.00
Radome Cover	N000900L021A	Cambium 470mm Dish Snow/Wind Radome Cover	\$55.00