

Siklu MultiHaul TG Node N366 (360° Terragraph Mesh)

Part Number / SKU: MH-N366-CCP-PoE-B • 360-Degree Terragraph-Certified Multi-Gigabit Mesh Distribution Node

Key System Highlights:

- 4 independent beamforming antenna sectors providing 360° full horizontal coverage
- Up to 16 Gbps total system capacity (3.8 Gbps full duplex per sector)
- Self-healing L2 SDN Terragraph mesh architecture with sub-50ms failover switchover
- 10G SFP+ cage + 10GbE PoE-In + high-power PoE-Out (up to 67W) to power CCTV cameras
- Carrier-grade IP67 cast aluminum chassis engineered for harsh outdoor municipal environments



RF & WIRELESS SPECIFICATIONS

Frequency Band	57 to 66 GHz (V-Band Terragraph certified)
Capacity	16 Gbps total system capacity; 4.6 Gbps FD per link
Antennas	4x 90° Active phased-array beamforming sectors (360° Azimuth)
Range	Up to 800 meters node-to-node / node-to-TU mesh reach
Modulation	BPSK to 16-QAM with adaptive modulation and coding

INTERFACES & POWER

Ports	1x 10G SFP+, 1x 10GbE RJ-45 (PoE-In), 1x 1GbE RJ-45 (PoE-Out 67W)
Power Input	802.3bt Type 4 PoE or Direct 36-57VDC terminal block
Power Consumption	45W base, up to 110W with max 67W PoE-Out load
Dimensions / Weight	275 x 275 x 220 mm (10.8 x 10.8 x 8.6 in) / 4.2 kg (9.2 lbs)
Weather Rating	IP67 all-weather outdoor rating; -40°C to +55°C operating temp

RECOMMENDED ACCESSORIES, MOUNTS & LICENSES

Category	Manufacturer SKU	Description	Est. MSRP
Mounting Kit	AX-MK-1FT-B	Siklu Precision Fine-Tune Pole Mount Kit	\$280.00
PoE Injector	EH-POE-AC-60W	Siklu 60W Outdoor 802.3bt PoE Power Injector	\$145.00
Surge Protector	AX-SP-01	Siklu Outdoor Gigabit PoE Surge Protector	\$85.00