

Cambium cnWave 60 GHz V1000 Mid-Gain Client Node

Part Number / SKU: C060084A003A • Compact 60 GHz Terragraph
Subscriber Station for Enterprise & Smart City

Key System Highlights:

- Compact form factor with integrated beamforming antenna for fast aesthetic deployment
- Up to 2.0 Gbps symmetrical throughput connecting back to V5000 distribution nodes
- Autonomous electronic beam-steering simplifies installation without manual fine-aiming
- Standard 802.3af PoE powered (10W consumption) allows powering from existing PoE switches
- IP67 ruggedized housing designed for outdoor lighting poles, walls, and traffic signals



WIRELESS & RADIO SPECIFICATIONS

Frequency Band	57 to 66 GHz (802.11ay Terragraph certified)
Throughput	Up to 2.0 Gbps (1.0 Gbps DL / 1.0 Gbps UL)
Antenna Gain	22.5 dBi beamforming integrated phased array
Azimuth Beam Steering	±40° horizontal electronic scanning
Max Link Range	Up to 1.0 km (0.62 miles)

NETWORK, POWER & MECHANICAL

Interfaces	1x 100/1000Base-T RJ-45 Gigabit Ethernet (PoE-In)
Power Input	802.3af PoE (37-57V)
Power Consumption	10W maximum
Dimensions / Weight	140 x 85 x 40 mm (5.5 x 3.3 x 1.6 in) / 0.4 kg (0.88 lbs)
Mounting	Wall mount and pole clamp bracket included

RECOMMENDED ACCESSORIES, MOUNTS & LICENSES

Category	Manufacturer SKU	Description	Est. MSRP
Mount Bracket	N000000L125A	cnWave V1000 Adjustable Tilt Bracket Mount	\$49.00
Surge Suppressor	C000000L065A	Cambium Outdoor Gigabit 56V Surge Suppressor	\$75.00