

Cambium cnWave 60 GHz V3000 High-Gain Client / PtP

Part Number / SKU: C060084A001A • High-Gain Terragraph Millimeter Wave Radio for Long-Range PtP & PtMP

Key System Highlights:

- High-gain 44.5 dBi parabolic reflector dish delivering up to 4.0 km operational range
- Supports Point-to-Point (PtP) links up to 3.8 Gbps full duplex with sub-millisecond latency
- Operates as long-range client terminal unit back to cnWave V5000 distribution nodes
- 10G SFP+ cage allows high-speed fiber backhaul handoff directly to tower/rack switches
- Internal heating element prevents snow and ice accumulation on feedhorn



WIRELESS & RADIO SPECIFICATIONS

Frequency Band	57 to 66 GHz (V-Band, Channels 1 to 4)
Max Throughput	3.8 Gbps Full-Duplex (1.9 Gbps DL / 1.9 Gbps UL)
Antenna Gain	44.5 dBi (with included high-gain dish assembly)
Antenna Beamwidth	0.8° Pencil Beam (3 dB beamwidth)
Maximum Range	Up to 4.0 km (2.5 miles) depending on rain zone and link margin

NETWORK, POWER & MECHANICAL

Interfaces	1x 10G SFP+ optical port + 1x 1GbE RJ-45 (PoE-In)
Power Input	802.3at / 802.3bt PoE (54VDC passive)
Power Consumption	26W typical, 35W with active feedhorn heater enabled
Dimensions / Weight	Antenna Dia. 450 mm (17.7 in) / 3.4 kg (7.5 lbs)
Weather Rating	IP66 / IP67 all-weather outdoor enclosure

RECOMMENDED ACCESSORIES, MOUNTS & LICENSES

Category	Manufacturer SKU	Description	Est. MSRP
Precision Mount	N000045L002A	cnWave V3000 Precision Fine-Adjustment Bracket	\$165.00
PoE Injector	N000065L001C	Cambium 60W Gigabit Passive PoE Injector (54VDC)	\$85.00
Surge Suppressor	C000000L065A	Cambium Outdoor Gigabit 56V Surge Suppressor	\$75.00