

Cambium cnWave 60 GHz V5000 Distribution Node

Part Number / SKU: C060084A004A • Dual-Sector Terragraph-Certified
Multi-Gigabit Mesh Distribution Node

Key System Highlights:

- Dual-sector active phased-array beamforming providing up to 280° horizontal azimuth coverage
- Total raw aggregate throughput up to 7.2 Gbps (1.8 Gbps DL / 1.8 Gbps UL per sector)
- Connects up to 30 subscriber client nodes (V1000/V3000) plus 4 distribution node mesh links
- 10G SFP+ optical cage + 1x 100/1000/10000Base-T PoE-In + 1x GbE PoE-Out (up to 25W for CCTV camera)
- IP66 / IP67 environmental rating with carrier-grade surge protection



WIRELESS & RADIO SPECIFICATIONS

Frequency Band	57 to 66 GHz (V-Band, Channels 1 to 4)
Channel Bandwidth	2.16 GHz (supports channel bonding)
Modulation & Coding	MCS0 (BPSK) to MCS12 (16-QAM) with LDPC
EIRP (Combined)	Dual Sector, 38 dBm (EIRP compliant with FCC / ETSI)
Antenna Beamwidth	280° Azimuth scanning; ±14° Elevation scan range
Antenna Gain	22.5 dBi per sector integrated array

NETWORK, POWER & MECHANICAL

Interfaces	1x 10G SFP+, 1x 10GbE RJ-45 (PoE-In), 1x 1GbE RJ-45 (802.3at PoE-Out)
Power Input	802.3bt Type 3 PoE (54VDC passive supported)
Power Consumption	35W typical (base unit), up to 60W with max PoE-Out client
Dimensions / Weight	280 x 185 x 102 mm (11.0 x 7.3 x 4.0 in) / 4.0 kg (8.8 lbs)
Operating Temp	-40°C to +60°C (-40°F to 140°F); Wind Survival: 200 km/h (124 mph)

RECOMMENDED ACCESSORIES, MOUNTS & LICENSES

Category	Manufacturer SKU	Description	Est. MSRP
Mounting Kit	N000000L125A	cnWave V5000 Adjustable Tilt Bracket Mount	\$49.00
PoE Injector	N000065L001C	Cambium 60W Gigabit Passive PoE Injector (54VDC)	\$85.00
Surge Suppressor	C000000L065A	Cambium Outdoor Gigabit 56V Surge Suppressor	\$75.00
Optical Gland	N000065L003A	cnWave IP67 Weatherproof Optical SFP+ Cable Gland	\$25.00