

Wave Pro

Model: Wave-Pro

High-capacity 60 GHz radio that supports long-distance PtP (bridge) and PtMP links.



Mechanical

	Dia. 424.4 x 166.2 mm (Dia. 16.7 x 6.5")
	Without mount: 2.8 kg (6.2 lb) With mount: 4 kg (8.8 lb)
	Aluminum alloy, UV stabilized polycarbonate
	Stainless steel
	25 to 76.2 mm (1 to 3") (on pipe outer diameter)
	369 N at 200 km/h (83 lbf at 125 mph)
	IPX6

Hardware

	Quad-core ARM® Cortex®-A53 at 1.4 GHz
	512 MB
	(2) 2.5 GbE RJ45 ports (1) 10G SFP+ port
	26W
	Passive PoE 4-pairs (1, 2+; 3, 6-) (4, 5+; 7, 8-) Passive PoE 2-pairs (4, 5+; 7, 8-), for 44-54V DC only
	44-54V DC 22-27V DC
	48V DC, 0.65A, 2.5 GbE PoE adapter (Included)
	(1) Factory reset
	Flashing white: bootup in progress White: not connected to UISP application Blue: connected to UISP application Flashing blue: locate in progress Blue/white: firmware upgrade in progress
	(2) Flashing blue: Ethernet traffic detected
	Blue: receiving at least (4) GPS satellite signal
	White: 5 GHz link Blue: 60 GHz link
	(1) Flashing blue: SFP+ traffic detected
	-40 to 60° C (-40 to 140° F)
	5 to 95% noncondensing
	FCC, IC, CE

Software

	PtP PtMP Station
	(Requires FW 3.4.0 or later.)
	(Requires FW 3.3.0 or later.)
	(Requires FW 3.3.0 or later.)
	Bridge/Router mode (Router is available in PtMP station mode only.)
	Version 2.3.0 and later

System

	5.4 Gbps
	PtP: Up to 15 km (9.3 miles) PtMP: Up to 8 km (5 miles) (Wave AP), up to 6 km (3.7 miles) (Wave AP Micro, Wave AP Gen2)
	WPA2-PSK (AES)

Radio Frequency

	57-71 GHz (Depends on regulatory region.)
	2160, 1080, 540 MHz (540 MHz is supported with FW version 3.3.0 and later.)
	58320, 59400, 60480, 61560, 62640, 63720, 64800, 65880, 66960, 68040, 69120, 70200, 70560 MHz (70560 MHz is supported with FW version 3.3.0 and later.)
	16QAM, QPSK
	46 dBi
	Vertically-Linear
	Azimuth: 3 dB 1.3° Elevation: 3 dB 1.3°

Radio Frequency (Back-Up)

	802.11ax (WiFi 6)
	U-NII-1 5150 - 5250 MHz U-NII-2A 5250 - 5350 MHz U-NII-2C 5470 - 5725 MHz U-NII-3 5725 - 5850 MHz
	5150 - 5875 MHz (Depends on regulatory region.)
	20, 40, 80 MHz
	BPSK (1/2), QPSK (1/2), QPSK (3/4), 16QAM (1/2), 16QAM (3/4), 64QAM (2/3), 64QAM (3/4), 64QAM (5/6), 256QAM (3/4), 256QAM (5/6), 1024QAM (3/4), 1024QAM (5/6)
	22 dBi
	Dual-Linear
	Azimuth: 3 dB 8° Elevation: 3 dB 8°
	20 dB
	0°