


42U Rack Cabinet, 1,000 mm, Perforated Door

Model / SKU: UACC-Rack-42U-1000-P



OVERVIEW

Dimensions

Weight

Enclosure Material

Color

Packaging: 740 x 1,165 x 2,223 mm (29.1 x 45.9 x 87.5")
Rack with caster: 600 x 1,000 x 2,050 mm (23.6 x 39.4 x 80.7")
Rack without caster: 600 x 1,000 x 1,966 mm (23.6 x 39.4 x 77.4")

Packaging: 112.4 kg (247.8 lb)
Rack: 84.2 kg (185.6 lb)

SPCC steel
Door/side panels: 1.2 mm (0.05")
Main body: 1 mm (0.04")
Posts: 2 mm (0.08")

White

Treatment	Powder coating
U Height	42U
Rack Type	4 post, enclosed cabinet
Mounting Hole Type	Square
Adjustable Mounting Depth	Default 652.3 mm (25.7") Max. 877.3 mm (34.5") Adjustable pitch 15 mm (0.6")
Max. Weight Capacity	Static 800 kg (1764 lb) Rolling 320 kg (705 lb)
Front Door	Perforated Default left-hand outswing, reversible
Rear Door	Perforated Default left-hand outswing, reversible
Side Panels	(4) Solid, removable and lockable
Mounting	Floor stand
Lockable Casters	True
Leveling Stands	True
Cabinet Interconnect	True
Floor Anchor	True
Fan Module	(4) Pre-installed 120 x 120 x 38 mm AC fan units
Grounding Lugs	True
Vertical Cable Management	True
Cable Entry Opening	(2) Top: 335 x 52.5 mm (13.2 x 2.1") (2) Bottom: 335 x 52.5 mm (13.2 x 2.1")
Security	(1) Front door lock (1) Rear door lock (8) Side panel locks (3) Keys

Standard	CE; EIA/ECA-310-E; RoHS
NDAA Compliant	True