



UniFi   UISP   Branding

Q

Search UniFi products

Cloud Gateways   Switching   WiFi   Physical Security   Door Access   Integrations   Accessories

SFP & Fiber > CWDM Mux Demux 4



CWDM Mux Demux 4

UACC-CWDM-4

Datasheet

Marketing Images

Installation Guide

^ Overview

|                            |                                                                             |
|----------------------------|-----------------------------------------------------------------------------|
| Dimensions                 | 442 x 120 x 43.7 mm<br>(17.4 x 4.7 x 1.7")                                  |
| Enclosure Material         | SGCC steel                                                                  |
| Weight                     | 1.4 kg (3.2 lb)                                                             |
| Pigtail and Connector Type | 0.9 mm white LC/UPC                                                         |
| Connector                  | (1) COM (LC/UPC)<br>(1) MON (LC/UPC)<br>(4) 1270/1290/1310/1330 nm (LC/UPC) |
| Fiber                      |                                                                             |
| Type                       | SMF-28e                                                                     |
| Length                     | ≥0.5 to 1 m                                                                 |
| Isolation                  | Adjacent Channel: Max. 30 dB<br>Non-Adjacent Channel: Min. 40 dB            |



|                                   |                              |
|-----------------------------------|------------------------------|
| Channel Center Wavelength         | 1270/1290/1310/1330 nm       |
| Min. Channel Passband             | ±6.5 nm                      |
| Insertion Loss                    | <1.5 dB (Max.)               |
| Return Loss                       | 50 dB (Min.)                 |
| Max. Power Handling               | 500 mW                       |
| Max. Passband Ripple              | 0.3 dB                       |
| Max. Polarization Dependent Loss  | 0.1 dB                       |
| Max. Polarization Mode Dispersion | 0.1 ps                       |
| Min. Directivity                  | 55 dB                        |
| Ambient Storage Temperature       | -40 to 90° C (-40 to 194° F) |
| Ambient Operating Temperature     | -30 to 75° C (-22 to 167° F) |
| NDAA Compliant                    | ✓                            |

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.