

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Accessories

WiFi Integrated > Cloud Gateway Industrial



Cloud Gateway Industrial

UCG-Industrial


Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions

Device: 307.9 x 203.5 x 43.7 mm
(12.1 x 8 x 1.7")
Table stand: 203.5 x 100.2 x 21.9 mm
(8 x 3.9 x 0.9")

UniFi Application Suite

Network ⓘ	✓
Protect ⓘ	✓
Access ⓘ	✓
Talk ⓘ	✓

Managed UniFi Devices	50+
Managed Cameras	(15) HD (8) 2K (5) 4K
Managed Access Hubs ⓘ	50
Simultaneous Users Connected	500+
Max. WAN Port Count	5
Default WAN Ports	(1) 10G SFP+ (1) 10 GbE RJ45 (1) 2.5 GbE RJ45
Port Layout	
2.5 GbE RJ45	4 (2 PoE+++, 2 PoE+) (2.5G/1G/100M)
10 GbE RJ45	1 (PoE+++) (10G/5G/2.5G/1G/100M)
10G SFP+	1 (10G/1G)
IDS/IPS Throughput	5 Gbps
Form Factor	Wall-mounted Compact desktop (Table stand included) Rack mount (Accessory sold separately)
Coverage Area	115 m ² (1,250 ft ²)
^ Security	
Stateful Firewall	✓
Application-Aware Layer 7 Firewall	✓
DPI & Traffic Identification	✓
Zone-Based Firewall Advanced Filtering (Regions, Domains, Apps)	✓
Content Filtering	✓
Intrusion Prevention (IPS/IDS)	✓

IDS/IPS Signatures	55,000+ with CyberSecure
VLAN/Subnet-based Traffic Segmentation	✓
^ VPN & SD-WAN	
License-Free SD-WAN	✓
Site-to-Site VPN	
Site Magic	✓
IPsec	✓
OpenVPN	✓
VPN Server	
Identity Endpoint One-Click VPN	✓
Teleport Zero-Configuration VPN	✓
WireGuard	✓
OpenVPN	✓
L2TP	✓
VPN Client	
OpenVPN	✓
WireGuard	✓
^ Networking	
Multi-WAN Load Balancing	✓
Dynamic Routing	
OSPF	✓
BGP	✓
Advanced QoS	✓
Multicast DNS (mDNS)	✓

Integrated RADIUS Server	✓
RADIUS over TLS (RadSec)	✓
Additional Internet Failover with UniFi LTE Backup	✓
Internet Quality and Outage Reporting	✓
MAC Address Table Size	4,000
Virtual Network Override	✓

^ Integrated WiFi

WiFi Standard	802.11a/b/g/n/ac/ax/be (WiFi 6, WiFi 7)
Throughput	
5 GHz	4.3 Gbps
2.4 GHz	688 Mbps
MIMO	
5 GHz	2 x 2 (DL/UL MU-MIMO)
2.4 GHz	2 x 2 (DL/UL MU-MIMO)
Antenna Gain	
5 GHz	Stub antenna: 5 dBi Terminal (Omni) antenna: 6 dBi
2.4 GHz	Stub antenna: 3 dBi Terminal (Omni) antenna: 6 dBi
Max. TX Power	
5 GHz	26 dBm
2.4 GHz	23 dBm
Supported Data Rates	
802.11be (WiFi 7)	7.3 Mbps to 4.3 Gbps (MCS0 - MCS13 NSS1/2, EHT 20/40/80/160/240)
802.11ax (WiFi 6)	7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2, HE 20/40/80/160)

802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
^ Hardware	
NVR Storage	Pre-installed 128 GB microSD for NVR
Expansion Slot	MicroSD Card ⓘ
PoE Budget	DC input: 270W ATX power: 75W
Max. PoE Wattage per Port by PSE	
PoE+	30W
PoE+++	90W
Voltage Range PoE Mode	50-57V
Max. Power Consumption	28W (Excluding PoE output)
Power Method	(1) DC Input (350W PSU) (1) ATX power (48V)
Power Supply	54V DC, 350W (Adapter included) ATX power (48V)
Supported Voltage Range	100-240V AC
Heat Dissipation	95 BTU/hr (Excluding PoE output)
Processor	Quad-core ARM® Cortex®-A73 at 2.2 GHz
System Memory	3 GB
Weight	Device: 2.4 kg (5.3 lb) Table stand: 321 g (11.3 oz)
Enclosure Material	Device: Polycarbonate, aluminium alloy Table stand: Polycarbonate, galvanized steel, silicone rubber
Management	Ethernet Bluetooth

Ethernet	✓
SFP+	✓
System	✓
MicroSD	✓
SIM	✓
Button	(1) Factory reset (2) Handle release buttons
ESD/EMP Protection	Air: ± 8kV, contact: ± 4kV
Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity	5 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC
^ Software	
Application Requirements	
Mobile App	UniFi iOS™: Version 10.32.0 and later UniFi Android™: Version 10.35.0 and later

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.