

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Enterprise > Enterprise Campus 24S PoE



Enterprise Campus 24S PoE

ECS-24S-PoE




Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions

442.4 x 44 x 496 mm
(17.4 x 1.7 x 19.5")

Port Layout

1 GbE RJ45

1
(1G/100M/10M) ⓘ

2.5 GbE RJ45

8 (All PoE+++)
(2.5G/1G/100M/10M) ⓘ

10 GbE RJ45

16 (All PoE+++)
(10G/5G/2.5G/1G/100M/10M) ⓘ

100G QSFP28	2 (100G) ⓘ
Console	1
Max. PoE Output	Up to PoE+++ ⓘ 100-240V AC Shared Mode: 1,050W with (2) 600W modules 100-240V AC Redundant Mode: 450W with (2) 600W modules
Total PoE Availability	200-240V AC Shared Mode: 2,250W with (2) 1,200W modules 100-120V AC Shared Mode: 1,850W with (2) 1,200W modules 200-240V AC Redundant Mode: 1,050W with (2) 1,200W modules 100-120V AC Redundant Mode: 850W with (2) 1,200W modules ⓘ
Redundancy	Switch Stacking (2) Hot-Swappable PSUs (4) Hot-Swappable Fans
Layer 3	✓
Form Factor	Rack Mount (1U, Full-Depth) ⓘ
Etherlighting™	✓
^ Performance	
Switching Capacity	460 Gbps
Total Non-Blocking Throughput	230 Gbps
Forwarding Rate	342 Mpps
Supported VLANs	1,000
MAC Address Table Size	32,000
IPv4 Static Routes	512
Packet Buffer Size	8 MB
Access Lists	
IPv4	256
MAC	256

DHCP Server (Local Networks)	✓
DHCP Relay	✓
Inter-VLAN Routing (Local Networks)	✓
Static Routing (Local Networks)	✓
^ Layer 2 Features	
LACP Port Aggregation	✓
Stacking	✓ ⓘ
Cross-Stack LAG	✓ ⓘ
STP & RSTP	✓
QoS (DSCP)	✓
Pro AV Profiles (Play, Dante, Q-SYS, NDI, SDVoE, Shure, AES67, Crestron)	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓

LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
Virtual Network Override	✓
^ Hardware	
PoE Ports	
PoE+++	24
Max. PoE Wattage per Port by PSE	
PoE	15.4W
PoE+	30W
PoE++	60W
PoE+++	90W
Max. Power Consumption	
	150W (Excluding PoE Output) 2,400W (Including PoE Output)
Power Method	(2) Universal input, 100-240V AC, 50/60 Hz
Power Input Method	(2) AC input, Hot-swappable power modules
Power Supply	(2) Hot-swappable AC/DC 600W power modules
Supported Voltage Range	100-240V AC
Management	
	Ethernet OOB Management port Serial Console AR
Heat Dissipation	512 BTU/hr (Excluding PoE Output)
Weight	
	Without mounting brackets: 9.2 kg (20.3 lb) With mounting brackets: 9.3 kg (20.5 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel

LCM Display	1.3" touchscreen
Fan Method	(4) Hot-swappable fan modules ⓘ
ESD Protection	Air: ± 12kV, contact: ± 12kV
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
Etherlighting™	
Ethernet	✓
SFP28	✓
LEDs	
Ethernet	✓
SFP28	✓
System	✓
NDAA Compliant	✓
Certifications	CE, FCC, IC

^ **Software**

Application Requirements

UniFi Network	Version 10.6.101 and later
---------------	----------------------------

Stay in Touch

Email

Subscribe



