

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Enterprise > Enterprise Campus 48S



Enterprise Campus 48S




ECS-48S

Datasheet

In The Box

Marketing Images

Installation Guide



Overview

Dimensions

442.4 x 44 x 496 mm
(17.4 x 1.7 x 19.5")

Port Layout

1 GbE RJ45

1
(1G/100M/10M) ⓘ

2.5 GbE RJ45

32
(2.5G/1G/100M/10M) ⓘ

10 GbE RJ45

16
(10G/5G/2.5G/1G/100M/10M) ⓘ

100G QSFP28	2 (100G) ⓘ
Console	1
Redundancy	Switch Stacking (2) Hot-Swappable PSUs (4) Hot-Swappable Fans
Layer 3	✓
Form Factor	Rack Mount (1U, Full-Depth) ⓘ
Etherlighting™	✓
^ Performance	
Switching Capacity	680 Gbps
Total Non-Blocking Throughput	340 Gbps
Forwarding Rate	506 Mpps
Supported VLANs	1,000
MAC Address Table Size	32,000
IPv4 Static Routes	512
Packet Buffer Size	8 MB
Access Lists	
IPv4	256
MAC	256
^ Layer 3 Features	
DHCP Server (Local Networks)	✓
DHCP Relay	✓
Inter-VLAN Routing (Local Networks)	✓
Static Routing (Local Networks)	✓
^ Layer 2 Features	

Stacking	✓ ⓘ
Cross-Stack LAG	✓ ⓘ
STP & RSTP	✓
QoS (DSCP)	✓
Pro AV Profiles (Play, Dante, Q-SYS, NDI, SDVoE, Shure, AES67, Crestron)	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
Virtual Network Override	✓

^ Hardware

Power Method	(2) Universal input, 100–240V AC, 50/60 Hz
Power Input Method	(2) AC input, Hot-swappable power modules
Power Supply	(2) Hot-swappable AC/DC 550W power modules
Supported Voltage Range	100–240V AC
Management	Ethernet OOB Management port Serial Console AR
Heat Dissipation	853 BTU/hr
Weight	Without mounting brackets: 10.2 kg (22.5 lb) With mounting brackets: 10.3 kg (22.7 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
Supported Rack Depth	482.6 mm (19") four-post racks Posts depths ranging from 650 to 1,000 mm (25.6–39.4")
LCM Display	1.3" touchscreen
Fan Method	(4) Hot-swappable fan modules ⓘ
ESD Protection	Air: ± 12kV, contact: ± 8kV
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
Etherlighting™	
Ethernet	✓
SFP28	✓
LEDs	
Ethernet	✓
SFP28	✓
System	✓
NDAA Compliant	✓

^ **Software**

Application Requirements

UniFi Network

Version 10.6.101 and later

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.