

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Utility > [Lite 16 PoE](#)



Lite 16 PoE

USW-Lite-16-PoE



Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions	192 x 185 x 44 mm (7.6 x 7.3 x 1.7")
Port Layout	
1 GbE RJ45	16 (8 PoE+) (1G/100M/10M)
Max. PoE Output	Up to PoE+
Total PoE Availability	45W
Form Factor	Compact desktop, wall

Switching Capacity	32 Gbps
Total Non-Blocking Throughput	16 Gbps
Forwarding Rate	24 Mpps
Supported VLANs	1,000
MAC Address Table Size	8,000
Packet Buffer Size	0.5 MB
Access Lists	
IPv4	128
MAC	128
^ Layer 2 Features	
LACP Port Aggregation	✓
STP & RSTP	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓

Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
Virtual Network Override	✓

^ Hardware

PoE Ports

PoE+	8
------	---

Max. PoE Wattage per Port by PSE

PoE+	32W
------	-----

Max. Power Consumption	15W (Excluding PoE Output) 60W (Including PoE Output)
------------------------	--

Power Method	Universal input, 100-240V AC, 50/60 Hz
--------------	--

Power Input Method	AC input
--------------------	----------

Power Supply	AC/DC, internal, 60W
--------------	----------------------

Supported Voltage Range	100-240V AC
-------------------------	-------------

Management	Ethernet
------------	----------

Heat Dissipation	51.2 (Excluding PoE Output)
------------------	-----------------------------

Weight	1.2 kg (2.6 lb)
--------	-----------------

Enclosure Material	Polycarbonate
--------------------	---------------

Mount Material	Polycarbonate
----------------	---------------

Ambient Operating Temperature	-15 to 40° C (5 to 104° F)
-------------------------------	----------------------------

Ambient Operating Humidity	10 to 90% noncondensing
----------------------------	-------------------------

NDAA Compliant	✓
----------------	---

Certifications	CE, FCC, IC, Anatel: 04479-21-08356
----------------	-------------------------------------

^ Software



UniFi Network

Version 7.2.94 and later

Stay in Touch

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.