



UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

RJ45 & Copper > UniFi Premium Patch Cable



UniFi Premium Patch Cable

UACC-Cable-Patch-EL-C6A

Datasheet

Marketing Images

^ Overview

Available Lengths	End-to-end: 0.15, 0.3, 1, 2, 3, 5, 8, 12, 15 m (0.5, 1, 3.3, 6.6, 9.8, 16.4, 26.2, 39.8, 49.2 ft)
Available Colors	White
Pack Options	Single Unit (0.15, 0.3, 1, 2, 3, 5, 8, 12, 15 m) 10-Pack (0.15, 0.3, 1, 2, 3 m) 24-Pack (0.15, 0.3, 1, 2 m) 50-Pack (0.15, 0.3 m)
Supported Data Rate	10G
Supported PoE Type	Up to PoE+++
Connector	(2) Translucent booted and shielding RJ45
Operating Environment	Indoor
Cable	
Jacket Diameter	0.15-8 m: 3 mm (0.11") 12-15 m: 3.3 mm (0.13")



Shielding Type	UTP
Conductor Type	Stranded copper
Conductor Wire Gage	0.15-8 m (0.5-26 ft): 34 AWG 12-15 m (39-49 ft): 32 AWG
Bend Radius	0.15-8 m: Min. 24 mm (0.94 ") 12-15 m: Min. 27 mm (1.06 ")
Flame Rating	VW-1 (UL1581)
Standards	TIA/EIA-568-B.2 ISO/IEC 11801
Installation Temperature	-20 to 60°C (-4 to 140°F)
Ambient Storage Temperature	-20 to 75°C (-4 to 167°F)
Ambient Operating Temperature	-20 to 60°C (-4 to 140°F)

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.