

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Standard > [Standard 24](#)



Standard 24
USW-24



Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions

442 x 200 x 44 mm
(17.4 x 7.9 x 1.7")

Port Layout

1 GbE RJ45

24
(1G/100M/10M)

1G SFP

2
(1G)

Form Factor

Rack mount (1U)

Performance

Total Non-Blocking Throughput	26 Gbps
Forwarding Rate	39 Mpps
Supported VLANs	1,000
MAC Address Table Size	8,000
Packet Buffer Size	0.5 MB
Access Lists	
IPv4	128
MAC	128
^ Layer 2 Features	
LACP Port Aggregation	✓
STP & RSTP	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓

LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
Virtual Network Override	✓

^ **Hardware**

Max. Power Consumption	25W
Power Method	Universal input, 100-240V AC, 50/60 Hz
Power Input Method	AC input
Power Supply	AC/DC, internal, 36W
Supported Voltage Range	100-240V AC
Management	Ethernet AR
Heat Dissipation	85.3 BTU/hr
Weight	Without mounting brackets: 2.7 kg (6 lb) With mounting brackets: 2.8 kg (6.2 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
Supported Rack Depth	400~1200 mm (15.7-47.2")
LCM Display	1.3" touchscreen
Ambient Operating Temperature	-5 to 45° C (23 to 113° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 17193-20-08356

^ **Software**

Application Requirements	
UniFi Network	Version 7.2.94 and later



Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.