

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Utility > Ultra



Ultra
USW-Ultra


Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Download
image



Zoom
in



* With PoE++ input.

Overview

Dimensions

203 x 76 x 33 mm
(8 x 3 x 1.3")

Port Layout

1 GbE RJ45

8 (7 PoE+; 1 PoE++ input)
(1G/100M/10M) ⓘ

Max. PoE Output

Up to PoE+

Total PoE Availability

PoE++ input: 42W
PoE+ input: 16W
60W PoE adapter input: 42W

Form Factor	Compact desktop, wall, magnetic
-------------	---------------------------------

^ Performance

Switching Capacity	16 Gbps
--------------------	---------

Total Non-Blocking Throughput	8 Gbps
-------------------------------	--------

Forwarding Rate	12 Mpps
-----------------	---------

Supported VLANs	256
-----------------	-----

MAC Address Table Size	4,000
------------------------	-------

^ Layer 2 Features

STP & RSTP	✓
------------	---

Egress Rate Limit	✓
-------------------	---

Flow Control	✓
--------------	---

Storm Control	✓
---------------	---

Multicast & Broadcast Rate Limiting	✓
-------------------------------------	---

Port Isolation	✓
----------------	---

Port Mirroring	✓
----------------	---

Jumbo Frames	✓
--------------	---

Loop Protection	✓
-----------------	---

^ Hardware

PoE Ports	
-----------	--

PoE+	7
------	---

PoE++	1
-------	---

Max. PoE Wattage per Port by PSE	
----------------------------------	--

PoE+	30W
------	-----

Max. Power Consumption	9W (Excluding PoE Output) with PoE input 8W (Excluding PoE Output) with adapter input 210W (Including PoE Output) with 210W AC adapter input
------------------------	--

Power Input Method	DC Input PoE
Supported Voltage Range	50-57V DC/PoE
Management	Ethernet
Heat Dissipation	31 BTU/hr (Excluding PoE Output)
Weight	Device: 320 g (11.3 oz) Wall mount: 45 g (1.6 oz)
Enclosure Material	Polycarbonate
Mount Material	Polycarbonate
Ambient Operating Temperature	PoE++ input: -30 to 60° C (-22 to 140° F) 60W AC adapter input: -20 to 45° C (-4 to 113° F) 210W AC adapter input: -20 to 60° C (-4 to 140° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 06367-24-08356

^ **Software**

Application Requirements

UniFi Network	Version 8.0.28 and later
---------------	--------------------------

Stay in Touch

Email

Subscribe



