Advancis WinGuard PSIM, Mission Control & Building Automation Integrations

Engineering & Licensing Reference Guide — WinGuard PSIM SDK, Elevator Dispatch, Industrial IoT / OPC & Mission Control

1. Licensing & Part Number Matrix

Enterprise command-and-control, PSIM, building management (BMS/SCADA), and elevator destination dispatch integrations for Genetec Security Center 5.13 / 5.14.

Genetec Part Number	Integration / Module	MSRP (USD)	Connection Rule & Compatibility
GSC-1SDK (Advancis WinGuard)	Advancis WinGuard PSIM Adapter	.00	1 SDK connection license per Advancis WinGuard interface server / redundancy node connecting to Security Center Directory.
GSC-1POTIS-COMPASS / 1P-KONE / 1P-TKDISPATCH / 1P-MCESENTRY	Elevator Destination Dispatch	,000.00	1 plugin license per elevator dispatch system (Otis Compass 3.2.2, KONE Polaris 3.0.2, ThyssenKrupp 3.2.0, MCE Sentry 3.0.1, Schindler PORT 3.0).
GSC-1POPC-S / GSC-IIOT	OPC Server / Industrial IoT 6.0	,000 / ,000	OPC Server (,000) or Industrial IoT Site License (,000 for BACnet, Modbus TCP, OPC UA, SNMPv3, MQTT, HTTP; or /device via GSC-IIOT-1D).
ADV-MC-1OPP-1Y / 3Y / 5Y	Genetec Mission Control	,000 / ,200 / ,500	Licensed per concurrent Mission Control operator (1Y / 3Y / 5Y). Requires RabbitMQ and Incident Document Service.

2. Multi-Role Server Sizing & Co-Hosting Guidelines

Advancis WinGuard subscribes to global Directory entity states, alarms, and live/playback video streams via the Genetec SDK; account for +2 GB RAM and +10% event throughput on the Directory server.

Genetec Mission Control requires RabbitMQ 3.13+ and Document Service 1.8 (+8 GB RAM and +4 CPU cores); for >10 concurrent operators or failover deployments, host Incident Manager on a dedicated Expansion Server.