# BriefCam Video Synopsis & Corsight AI Facial Recognition — Genetec Integration

Engineering & Licensing Reference Guide — SDK Connection Formulas, RTSP Media Gateway Load & GPU Server Sizing

## 1. SDK Connection Licensing Rules

Third-party GPU video analytics platforms (BriefCam and Corsight AI) integrate with Genetec Security Center via the Genetec .NET SDK and RTSP/Media Gateway streams, embedding real-time alerts and forensic search directly inside Security Desk.

| Genetec Part Number | Integration Component | MSRP (USD) | Connection Formula & Sizing Rule |
|---|---|---|---|
| GSC-1SDK (BriefCam) | BriefCam Security Center Plugin | .00 | Requires 1 SDK license for VSServer + 1 per Fetching/Real-Time GPU Processing node + 1 per Security Desk Embedded Viewer workstation (+1 recommended spare). |
| GSC-1SDK-BAPS-SYFTYCORSIGHTAI | Corsight AI Facial Recognition | .00 | 1 SDK connection license per Corsight AI / SYFTY server bridge connecting to Security Center Directory & Alarm Monitoring. |

## 2. Server Isolation & Archiver / Media Gateway Bandwidth Rules

CRITICAL ISOLATION RULE: BriefCam (PostgreSQL, RabbitMQ, VSServer, CUDA GPU workers) and Corsight AI MUST be deployed on dedicated GPU Analytics Servers (e.g., Streamvault SVA-1000E or NVIDIA GPU servers). Never install BriefCam or Corsight GPU services on a Security Center Archiver or Directory server.

Archiver & Media Gateway Impact: Every concurrent real-time analyzed stream (BriefCam RESPOND or Corsight AI live face matching) pulls a continuous RTSP stream from the Archiver or Media Gateway. Size Media Gateway capacity (max 127 FHD streams on Recommended 16GB server, 170 FHD streams on High-Performance 64GB server) and keep Archiver playback/export under 100 Mbps per Archiver.