Streamvault SV-7000EX

Scalable storage system directory

Designed for applications combining large amounts of high resolution cameras, users and events, the Streamvault™ SV-7000EX security appliance is a turnkey solution that meets the most demanding needs. With server-side load balancing and scalable centralized storage, your system can scale seamlessly.

Guaranteed performance

- up to **2,500 Mbps** throughput
- up to **2,000** readers
- up to **75** ALPR cameras



Key features

- Turnkey appliance with Genetec™ Security Center pre-installed
- Archive to scalable centralized storage
- iDRAC9 Enterprise for local and remote server monitoring
- Machine learning endpoint protection
- 5-year hardware warranty with Keep Your Hard Drive and Genetec Assurance with next-business day on-

Benefits



Reduce your infrastructure footprint – Connect more devices per appliance and reduce the number of units you need to manage your unified security system.



Protect your security system – Streamvault appliances help you build a resilient security system that protects your data and operations. Our cyber security experts stay vigilant on evolving threats and help identify and address new vulnerabilities promptly.



Deploy and expand seamlessly – Combining high performance and SAN storage, the Streamvault SV-7000EX is designed to scale with your needs.

Applications

Transportation

The SV-7000EX delivers a unified system combing video, access control, intrusion and video analytics, so you can secure your entire airport or seaport efficiently.

Gaming

Record high-resolution footage from hundreds of cameras simultaneously and reduce your infrastructure footprint with the SV-7000EX.

Entertainment venues

Record and access high-resolution video instantly and resolve incidents without disrupting ongoing activities with the SV-7000EX.

Technical specifications

OS
Windows Server IoT 2025

Processor
2x Intel® Xeon® Silver 4416+
Passmark: 65,576

Memory
64 GB DDR5

Ethernet
2x 1GbE RJ45, 4x 10/25GbE SFP28

Peripherals
1x USB 3.0, 1x USB 2.0

Video output
1x VGA front, 1x VGA rear

Performance
SV-7041EX-R6S:
Up to 2500Mbps / 1000 cameras

Mechanical and environmental

Input power
100-240v input power

Operating temperature
50°F to 95°F (10°C to 35°C)

Operating humidity
8 - 80% (non-condensing)

Compliance standards
IEC 60950-1, European Norm EN 60950-1, CISPR 22/CISPR 24, EN55022/55024

Expansion
Up to 2x LP

Storage

Storage types
Storage area network (SAN)
Network-attached storage (NAS)

Drive type
Enterprise HDD

OS drive
2x 480GB SSD (hot-swappable)

RAID controller
SV-7041EX-R6S: H355

Cybersecurity

Endpoint protection
Arctic Wolf Aurora Protect machine learning antivirus

Hardened image
200+ security settings changed by default

Maintenance
Verified Windows updates
Connected services for Genetec software and device firmware updates

Warranty and support

Hardware warranty
5-year warranty with next business day on-site service and Keep Your Hard Drive

Security Center support
Current and two previous versions (N-2)

Models

Model	Purpose	Dimensions (W x D x H)	Max weight	Power supply
SV-7041EX-R6S	Directory	18.97” x 26.03” x 1.68” 482 mm x 661.37 mm x 42.8 mm	40.23 lbs (18.25 kg)	Redundant hot-swap 800W PSU

Genetec Inc.
genetec.com/locations
info@genetec.com
@genetec

*Hardware specifications are subject to change. Units provided will be equivalent or superior to what is shown in this document.

© Genetec Inc., 2026. Genetec, Streamvault and the Genetec Logo are trademarks of Genetec Inc., and may be registered or pending registration in several jurisdictions. Other trademarks used in this document may be trademarks of the manufacturers or vendors of the respective products.