Streamvault SVA-100E

Analytics-ready appliance

The Streamvault™ SVA-100E compact appliance lets you easily enhance your security system with KiwiVision™ Video Analytics. Its optimized design lets you apply more analytics streams to your video surveillance system, whether that is a single or multiple analytic stream per camera.

Guaranteed performance

- up to **20** KiwiVision Privacy Protector™ streams*
- up to **8** KiwiVision intrusion detector streams*
- up to **23** Security Analytics streams*



Key features

- Turnkey appliance optimized for video analytics applications
- Certified for a wide range of indoors and outdoors analytics scenarios
- Machine learning endpoint protection
- 3-year hardware warranty with 1-year advance replacement

Benefits



Optimize performance – Instead of running analytics on recording appliances, the SVA-100E is designed to provide more analytics streams, all in a single compact appliance.



Protect your operations – The Streamvault SVA-100E can be easily deployed as an expansion appliance to your current security system, preventing disruptions to day-to-day operations.



Design with confidence – Adding analytics to your system can be challenging. That's why SVA-100E includes the Streamvault performance guarantee, and is certified in a wide range of indoors and outdoors scenarios.

Applications

Perimeter protection

Enhance security with unified intrusion and camera integrity analytics. Detect potential threats and unusual camera behavior instantly to help your operators focus on incidents.

Public space monitoring

The SVA-100E can be deployed with KiwiVision Privacy Protector™ to help you protect everyone's privacy and comply with regulations by anonymizing video feeds of public areas.

Business intelligence

Gain new insights into your operations with business intelligence analytics. The SVA-100E is the ideal appliance for use with Genetec Retail Sense™ and Genetec Airport Sense™.

* Performance varies based on parameters such as camera resolution, framerate and scene. Please refer to the KiwiVision Analytics performance calculator for more information.

Technical specifications

OS
Windows 10 IoT Enterprise LTSC

Processor
Intel® Core™ i5
Passmark: 13,354

Memory
Up to 16 GB DDR4

OS drive
1x 256 GB SSD

Ethernet
1x GbE RJ45

Peripherals
4x USB 3.1
2x USB 2.0

Display
1x HDMI
1x DisplayPort
1x VGA

Mechanical and environmental

Power supply
External 65W

Energy efficiency
ENERGY STAR® qualified
EPEAT® Gold9 registered
Supports 24/7 operations

Operating temperature
50°F to 95°F (10°C to 35°C)

Operating humidity
8 - 90% (non-condensing)

Dimensions
1.4" x 7.0" x 7.2"
(36 mm x 178 mm x 182 mm)

Weight
2.6 lbs (1.2 kg)

Certifications
IEC 60950-1, European Norm EN 60950-1, CISPR 22/CISPR 24, EN55022/55024

Cybersecurity

Endpoint protection
BlackBerry protect machine learning antivirus

Hardened image
200+ security settings changed by default

Maintenance
Verified Windows updates
Connected services for Genetec software and device firmware updates

Warranty and support

Hardware warranty
3-year warranty with 1-year advance replacement and next business day on-site service

Security Center support
Current and two prevous versions (N-2)

Performance

The table below shows the maximum number of supported streams for every video analytics application.

Camera resolution	Privacy protection	Object detection & stopped vehicle detection	Perimeter protection, area protection & direction control
VGA	28	16	8
720p	14	6	3

The number of streams supported depends on scene information. These numbers represent typical use cases. Please refer to the KiwiVision hardware calculator for more information.



Genetec Inc.
genetec.com/locations
info@genetec.com
@genetec

© 2021 Genetec Inc. All rights reserved. Genetec and its respective logo are trademarks of Genetec Inc., and may be registered or pending registration in several jurisdictions. Other trademarks used in this document may be trademarks of the manufacturers or vendors of the respective products.

UPTD09/2019