EATON • Infrastructure Technical Submittal

SKU: 5PX1500RTG2

2U 19" EIA Rackmount / Tower

Eaton 5PX Gen2 1500VA 1440W 120V Rack/Tower UPS

Enterprise line-interactive UPS with pure sine wave output, unity power factor (1440W @ 1500VA), and energy metering down to outlet groups. Ideal for enterprise networking, edge computing, and distributed AV/security systems. Supports up to 4 external battery modules for scalable runtime.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	1500 VA / 1440 Watts	**Nominal Input Voltage**	120V AC (89V – 151V AVR)
Input Connection (Plug)	NEMA 5-15P (10 ft attached cord)	**Output Receptacles**	8x NEMA 5-15R (8 Outlets Total)
Output Waveform	Pure Sine Wave (<5% THD linear)	**Switchable Outlet Groups**	2x Independently managed outlet groups
Input Circuit Breaker	15A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz ±0.1 Hz auto-sensing

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) with ABM	**Full Load Runtime (1440W)**	4.8 Minutes (Internal Battery)
Half Load Runtime (720W)	14.5 Minutes (Internal Battery)	**Extended Battery Module**	Supports up to 4x 5PXEBM48RTG2
Expansion Card Slot	Open slot for Network-M2 Card	**Local Interface**	Graphical LCD with multi-color backlight
Communication Ports	1x USB, 1x RS-232 DB9, 1x RPO/ROO	**Environmental Sensor**	Supports EMPDT1H1C2 via Network-M2

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.4" (86mm) x 17.2" (438mm) x 17.6" (448mm)
Net Weight	42.8 lbs (19.4 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	cULus Listed, UL 1778, FCC Class B	**Warranty**	3-Year Limited Warranty (inc. batteries)
Operating Temp	0°C to 40°C (32°F to 104°F)	**Audible Noise**	<45 dBA at 1 meter

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
5PXEBM48RTG2	Eaton 5PX Gen2 48V External Battery Module (2U)	Scalable Extended Battery Module
NETWORK-M2	Eaton Gigabit Network Card (Cybersecure Web/SNMP)	Network Management Expansion Card
EMPDT1H1C2	Eaton Environmental Monitoring Probe (EMP Gen 2)	Temperature, Humidity & 2 Contact Inputs
MBP1500	Eaton HotSwap MBP Maintenance Bypass PDU (15A)	Zero-downtime UPS servicing