EATON • Infrastructure Technical Submittal

SKU: 5PX3000RTNG2

2U 19" EIA Rackmount / Tower

Eaton 5PX Gen2 3000VA 3000W 120V UPS with Network-M2

Unity power factor 3000VA / 3000W line-interactive UPS with NEMA L5-30P locking input plug and pre-installed Gigabit Network Card (Network-M2). Provides maximum wattage output in a compact 2U chassis, ideal for virtualized server stacks, PoE switch clusters, and SAN storage.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	3000 VA / 3000 Watts (1.0 Unity PF)	**Nominal Input Voltage**	120V AC (89V – 151V AVR)
Input Connection (Plug)	NEMA L5-30P Twist-Lock (10 ft cord)	**Output Receptacles**	6x NEMA 5-20R, 1x NEMA L5-30R (7 Total)
Output Waveform	Pure Sine Wave (<5% THD linear)	**Switchable Outlet Groups**	2x Independently managed outlet groups
Input Circuit Breaker	30A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz ±0.1 Hz auto-sensing

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) with ABM	**Full Load Runtime (3000W)**	3.8 Minutes (Internal Battery)
Half Load Runtime (1500W)	11.5 Minutes (Internal Battery)	**Extended Battery Module**	Supports up to 4x 5PXEBM72RTG2
Pre-Installed Network Card	Network-M2 Gigabit Card Included	**Protocols**	HTTPS, SNMPv1/v3, SSH, MQTT, BACnet/IP
Local Interface	Graphical LCD with multi-color backlight	**Environmental Sensor**	Supports EMPDT1H1C2 probe

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.4" (86mm) x 17.2" (438mm) x 23.8" (603mm)
Net Weight	61.7 lbs (28.0 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	cULus Listed, UL 1778, UL 2900-1	**Warranty**	3-Year Limited Warranty (inc. batteries)
Operating Temp	0°C to 40°C (32°F to 104°F)	**Audible Noise**	<45 dBA at 1 meter

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
5PXEBM72RTG2	Eaton 5PX Gen2 72V External Battery Module (2U)	Scalable Extended Battery Module
EMPDT1H1C2	Eaton Environmental Monitoring Probe (EMP Gen 2)	Temperature, Humidity & 2 Contact Inputs
MBP3000	Eaton HotSwap MBP Maintenance Bypass PDU (30A)	Zero-downtime UPS servicing
RK2PC	Eaton 2-Post Telco Relay Rack Mounting Kit	2-Post Open Frame Rack Installation