EATON • Infrastructure Technical Submittal

SKU: 5PXEBM48RTG2

Eaton 5PX Gen2 48V External Battery Module (2U)

2U 19" EIA Rackmount / Tower

Extended Battery Module for Eaton 5PX Gen2 1500VA and 2000VA UPS models. Connect up to 4 modules for hours of scalable emergency battery backup runtime.

Electrical Specifications & Power Distribution

DC Bus Voltage	48V DC Industrial Battery Bus	**Battery Chemistry**	Sealed Lead Acid (VRLA) with ABM
Compatible UPS Models	5PX1500RTG2, 5PX1500RTNG2, 5PX2000RTNG2	**Daisy-Chain Capability**	Supports up to 4 EBMs in parallel
Connection Cable	Heavy-duty polarized DC connector included	**Hot-Swappable**	Yes, hot-swap connection during live UPS operation
Warranty	3-Year Limited Warranty (inc. batteries)	**Service Life**	3 to 5 Years typical

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.4" (86mm) x 17.2" (438mm) x 17.6" (448mm)
Net Weight	65.7 lbs (29.8 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	cULus Listed, UL 1778, FCC Class B	**Operating Temp**	0°C to 40°C (32°F to 104°F)