EATON • Infrastructure Technical Submittal

SKU: 9PX3000GRT-L

Eaton 9PX 3000VA 2700W Lithium-Ion 208/230V UPS

2U 19" EIA Rackmount / Tower

Next-generation Lithium-Ion online double-conversion UPS offering 2x to 3x longer battery life, 50% lighter weight, and 3x faster recharge compared to standard VRLA units. Features pre-installed Gigabit Network Card (Network-M2) and 200V-240V high-voltage IEC C13/C19 distribution.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	3000 VA / 2700 Watts (0.90 PF)	**Nominal Input Voltage**	208V / 230V / 240V AC
Input Connection (Plug)	IEC C20 (16A 208-240V)	**Output Receptacles**	8x IEC C13, 2x IEC C19 (10 Outlets Total)
Topology / Transfer Time	Online Double-Conversion (0 ms)	**Switchable Outlet Groups**	2x Independently managed outlet groups
Efficiency Rating	Up to 94% Online Mode / 98% ESS	**Output Frequency**	50/60 Hz ±0.1 Hz auto-sensing

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Lithium-Iron Phosphate (LiFePO4)	**Full Load Runtime (2700W)**	5.5 Minutes (Internal Lithium Pack)
Half Load Runtime (1350W)	14.5 Minutes (Internal Lithium Pack)	**Extended Battery Module**	Supports up to 4x 9PXEBM72RT-L
Pre-Installed Network Card	Network-M2 Gigabit Card Included	**Battery Lifespan**	8 to 10 Years Expected Service Life
Local Interface	Graphical LCD rotatable display	**Environmental Sensor**	Supports EMPDT1H1C2 probe

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.4" (86.5mm) x 17.3" (440mm) x 23.8" (605mm)
Net Weight	41.9 lbs (19.0 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	cULus Listed, UL 1778, UL 1973, CE	**Warranty**	5-Year Full Warranty (inc. lithium battery)
Operating Temp	0°C to 40°C (32°F to 104°F)	**Audible Noise**	<45 dBA at 1 meter

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
9PXEBM72RT-L	Eaton 9PX 72V Lithium-Ion External Battery Module (2U)	Lithium-Ion Extended Battery Module
EMPDT1H1C2	Eaton Environmental Monitoring Probe (EMP Gen 2)	Temperature, Humidity & 2 Contact Inputs
MBP3000HV	Eaton HotSwap MBP Maintenance Bypass PDU (208/240V)	Zero-downtime UPS servicing