EATON • Infrastructure Technical Submittal

SKU: 9PX3000RT

2U 19" EIA Rackmount / Tower

Eaton 9PX 3000VA 2700W 120V Online Double-Conversion UPS

Heavy-duty 3000VA online double-conversion UPS with NEMA L5-30P locking plug, zero transfer time, and full isolation from mains utility power abnormalities. Powers high-draw data storage racks, server blades, and high-density security headends with maximum protection.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	3000 VA / 2700 Watts (0.90 PF)	**Topology / Transfer Time**	Online Double-Conversion (0 ms)
Nominal Input Voltage	120V AC (100V – 144V Full Load)	**Output Receptacles**	6x NEMA 5-20R, 1x NEMA L5-30R (7 Total)
Input Connection (Plug)	NEMA L5-30P Twist-Lock (10 ft cord)	**Switchable Outlet Groups**	2x Independently managed outlet groups
Input Circuit Breaker	30A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz ±0.1 Hz auto-sensing

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) with ABM	**Full Load Runtime (2700W)**	3.5 Minutes (Internal Battery)
Half Load Runtime (1350W)	11.0 Minutes (Internal Battery)	**Extended Battery Module**	Supports up to 4x 9PXEBM72RT
Expansion Card Slot	Open slot for Network-M2 Card	**Local Interface**	Graphical LCD rotatable display
Communication Ports	1x USB, 1x RS-232 DB9, 1x RPO/ROO	**Environmental Sensor**	Supports EMPDT1H1C2 via Network-M2

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.4" (86.5mm) x 17.3" (440mm) x 23.8" (605mm)
Net Weight	60.4 lbs (27.4 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	cULus Listed, UL 1778, FCC Class B	**Warranty**	2-Year Limited Warranty (inc. batteries)
Operating Temp	0°C to 40°C (32°F to 104°F)	**Audible Noise**	<45 dBA at 1 meter

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
9PXEBM72RT	Eaton 9PX 72V External Battery Module (2U)	Scalable Extended Battery Module
NETWORK-M2	Eaton Gigabit Network Card (Cybersecure Web/SNMP)	Network Management Expansion Card
EMPDT1H1C2	Eaton Environmental Monitoring Probe (EMP Gen 2)	Temperature, Humidity & 2 Contact Inputs
MBP3000	Eaton HotSwap MBP Maintenance Bypass PDU (30A)	Zero-downtime UPS servicing