Eaton eATS Monitored Automatic Transfer Switch 1U 15A

The Eaton eATS 115 provides dual redundant power sources for single-corded switches, routers, and firewalls. Features seamless microsecond transfer (<10 ms) between primary and secondary sources, built-in network monitoring, and local LCD status screen.

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 15A (12A Derated)	**Dual Input Plugs**	2x NEMA 5-15P (Source A and Source B cords)
Output Receptacles	10x NEMA 5-15R Outlets	**Transfer Time**	<10 ms seamless break-before-make transfer
Power Capacity	1.44 kW Continuous Load	**Metering Accuracy**	±1% ISO/IEC billing-grade input metering
Switching Mechanism	High-reliability electromechanical relay	**Preferred Source**	User-selectable Source A or Source B priority

Physical Dimensions, Mounting & Compliance

Form Factor	1U 19" Rackmount	**Dimensions (H x W x D)**	1.7" (43mm) x 17.2" (438mm) x 9.8" (250mm)
Net Weight	9.5 lbs (4.3 kg)	**Local Display**	LED source indicators and digital ammeter
Network Protocols	HTTPS, SNMPv1/v3, SSH, Modbus-TCP	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	cULus Listed, UL 60950-1, FCC Class A	**Warranty**	3-Year Limited Warranty