EATON • Infrastructure Technical Submittal

SKU: EATS120

1U 19" EIA Rackmount

Eaton eATS Monitored Automatic Transfer Switch 1U 20A

Heavy-duty 20A Automatic Transfer Switch providing dual-source power redundancy for high-draw network switches and NVR servers. Seamlessly auto-switches between redundant utility feeds or UPS circuits to eliminate single points of failure.

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 20A (16A Derated)	**Dual Input Plugs**	2x NEMA 5-20P (Source A and Source B cords)
Output Receptacles	10x NEMA 5-20R Outlets	**Transfer Time**	<10 ms seamless break-before-make transfer
Power Capacity	1.92 kW Continuous Load	**Metering Accuracy**	±1% ISO/IEC billing-grade input metering
Switching Mechanism	High-reliability electromechanical relay	**Preferred Source**	User-selectable Source A or Source B priority

Physical Dimensions, Mounting & Compliance

Form Factor	1U 19" Rackmount	**Dimensions (H x W x D)**	1.7" (43mm) x 17.2" (438mm) x 9.8" (250mm)
Net Weight	10.2 lbs (4.6 kg)	**Local Display**	LED source indicators and digital ammeter
Network Protocols	HTTPS, SNMPv1/v3, SSH, Modbus-TCP	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	cULus Listed, UL 60950-1, FCC Class A	**Warranty**	3-Year Limited Warranty