Eaton ePDU G3 Basic 0U Vertical 20A 120V (24) 5-20R

SKU: EBA001
0U Vertical Rackmount (66" Length)

Eaton ePDU G3 Basic provides highly reliable, cost-effective unmanaged power distribution for IT and network equipment. Built with an ultra-low-profile chassis, toolless button mounting, and high-temperature rating (up to 60°C).

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 20A (16A Derated)	**Input Connection (Plug)**	NEMA 5-20P (10 ft attached cord)
Output Receptacles	24x NEMA 5-20R Outlets	**Power Capacity**	1.92 kW Continuous Load
Circuit Protection	Thermal circuit breaker protection	**Frequency**	50/60 Hz auto-sensing
Outlet Spacing	Optimized spacing for clean cable dress	**Construction**	Rugged aluminum extrusion chassis

Physical Dimensions, Mounting & Compliance

Form Factor	0U Vertical (Toolless button mount)	**Dimensions (H x W x D)**	66.5" (1689mm) x 2.05" (52mm) x 2.09" (53mm)
Net Weight	12.1 lbs (5.5 kg)	**Operating Temp**	0°C to 60°C (32°F to 140°F) high ambient
Mounting Options	Rear and side toolless mounting buttons	**Chassis Finish**	Durable black industrial powder coat
Certifications	cULus Listed, UL 60950-1, RoHS	**Warranty**	3-Year Limited Warranty