EATON • Infrastructure Technical Submittal

SKU: EMA004

Eaton ePDU G3 Managed 0U Vertical 20A 120V (24) 5-20R

0U Vertical Rackmount (66" Length)

Eaton ePDU G3 Managed provides individual outlet switching, outlet-level power metering (±1% billing-grade accuracy), and hot-swap network management module. Ideal for enterprise data center racks, allowing remote outlet reboot, load shedding, and equipment power sequencing.

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 20A (16A Derated)	**Input Connection (Plug)**	NEMA 5-20P (10 ft attached cord)
Output Receptacles	24x NEMA 5-20R Outlets	**Outlet Switching Capability**	Individual remote on/off/reboot per outlet
Metering Accuracy	±1% ISO/IEC billing grade metering	**Metering Points**	Input phase, branch circuit, and individual outlet
Power Capacity	1.92 kW Continuous Load	**Circuit Protection**	Integrated thermal overload breakers

Physical Dimensions, Mounting & Compliance

Form Factor	0U Vertical (Toolless button mount)	**Dimensions (H x W x D)**	66.5" (1689mm) x 2.05" (52mm) x 2.09" (53mm)
Net Weight	15.4 lbs (7.0 kg)	**Management Module**	Hot-swap network card with LCD pixel display
Network Protocols	HTTPS, SNMPv1/v3, SSH, Telnet, Modbus	**Daisy-Chaining**	Daisy-chain up to 8 ePDUs on 1 IP address
Certifications	cULus Listed, UL 60950-1, FCC Class A	**Warranty**	3-Year Limited Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
EMP001	Eaton Environmental Monitoring Probe (EMP)	Temperature & Humidity sensor module
EMPDT1H1C2	Eaton EMP Gen 2 Environmental Probe	Temp, humidity and 2 contact closures