Eaton ePDU G3 Metered Input 0U Vertical 20A 120V (24) 5-20R

SKU: EMI001
0U Vertical Rackmount (66" Length)

Eaton ePDU G3 Metered Input enables IT and facilities managers to accurately track power consumption at the PDU and branch level. Features high-density 24x NEMA 5-20R outlets with color-coded outlet sections and hot-swap LCD network module.

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 20A (16A Derated)	**Input Connection (Plug)**	NEMA 5-20P (10 ft attached cord)
Output Receptacles	24x NEMA 5-20R Outlets	**Metering Accuracy**	±1% ISO/IEC billing grade input metering
Power Capacity	1.92 kW Continuous Load	**Circuit Protection**	Integrated thermal overload breakers
Local Display	Multi-color graphical pixel LCD display	**Frequency**	50/60 Hz auto-sensing

Physical Dimensions, Mounting & Compliance

Form Factor	0U Vertical (Toolless button mount)	**Dimensions (H x W x D)**	66.5" (1689mm) x 2.05" (52mm) x 2.09" (53mm)
Net Weight	14.2 lbs (6.4 kg)	**Operating Temp**	0°C to 60°C (32°F to 140°F) high ambient
Network Protocols	HTTPS, SNMPv1/v3, SSH, Telnet, Modbus	**Daisy-Chaining**	Daisy-chain up to 8 ePDUs on 1 IP address
Certifications	cULus Listed, UL 60950-1, FCC Class A	**Warranty**	3-Year Limited Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
EMP001	Eaton Environmental Monitoring Probe (EMP)	Temperature & Humidity sensor module