Eaton Gigabit Network Card (Network-M2)

SKU: NETWORK-M2
Internal Expansion Slot

Cybersecurity-certified (UL 2900-1 and IEC 62443-4-2) Gigabit Ethernet network card for Eaton 5PX, 9PX, 9SX, and 9PXM UPS systems. Features modern HTTPS web server, SNMPv1/v3, MQTT IoT telemetry, and automated VM migration support via Eaton IPM.

Electrical Specifications & Power Distribution

Interface Speed	10/100/1000 Mbps Gigabit Ethernet (RJ45)	**Power Supply**	Powered directly from UPS internal expansion slot
Supported Protocols	HTTPS, SNMPv1/v3, SSH, MQTT, BACnet/IP	**Security Standards**	UL 2900-1, IEC 62443-4-2 Certified
Firmware Updates	Encrypted signed firmware updates	**Compatible Software**	Eaton IPM, Brightlayer Data Centers Suite
Environmental Probe	Supports up to 3 daisy-chained EMPDT1H1C2 probes	**Real-Time Clock**	NTP synchronization support

Physical Dimensions, Mounting & Compliance

Form Factor	Internal Mini-Slot Expansion Card	**Dimensions (H x W x D)**	1.7" (43mm) x 2.6" (66mm) x 5.2" (132mm)
Net Weight	0.2 lbs (0.1 kg)	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	cULus, CE, FCC Class B, RoHS	**Warranty**	2-Year Limited Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
EMPDT1H1C2	Eaton Environmental Monitoring Probe (EMP Gen 2)	Temperature, Humidity & Contact Sensor