TRIPP LITE • Infrastructure Technical Submittal

SKU: AVRX550UA

Desktop / Wall-Mount

Tripp Lite AVR 550VA 300W Ultra-Compact Desktop UPS

Ultra-compact 550VA / 300W line-interactive desktop UPS with Automatic Voltage Regulation (AVR) and USB communication port. Ideal for point-of-sale terminals, security camera power supplies, and access control edge gateways.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	550 VA / 300 Watts	**Topology**	Line-Interactive with AVR
Nominal Input Voltage	120V AC (NEMA 5-15P, 6 ft cord)	**Output Receptacles**	8x NEMA 5-15R (4 battery + 4 surge only)
Voltage Regulation	Maintains 120V nominal during voltage sags to 83V	**Surge Energy Rating**	316 Joules AC surge suppression

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA)	**Full Load Runtime (300W)**	3.0 Minutes
Half Load Runtime (150W)	9.0 Minutes	**Recharge Time**	Typically 8 hours to 90%
Communication Interface	USB HID-compliant port	**Status Indicators**	Front panel LED diagnostic indicators

Physical Dimensions, Mounting & Compliance

Form Factor	Compact Desktop / Wall-mount keyholes	**Dimensions (H x W x D)**	3.5" (89mm) x 11.0" (279mm) x 5.8" (147mm)
Net Weight	9.7 lbs (4.4 kg)	**Housing**	Ultra-compact fire-retardant plastic
Certifications	UL 1778, CSA, RoHS compliant	**Warranty**	3-Year Limited Product Warranty