TRIPP LITE • Infrastructure Technical Submittal

SKU: AVRX750UA

Desktop / Wall-Mount

Tripp Lite AVR 750VA 450W Ultra-Compact Desktop UPS

Ultra-compact 750VA / 450W line-interactive desktop UPS with Automatic Voltage Regulation (AVR) and USB communication port. Protects security NVRs, desktop PCs, and sensitive IoT controllers from blackouts and voltage fluctuations.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	750 VA / 450 Watts	**Topology**	Line-Interactive with AVR
Nominal Input Voltage	120V AC (NEMA 5-15P, 6 ft cord)	**Output Receptacles**	8x NEMA 5-15R (4 battery + 4 surge only)
Voltage Regulation	Corrects brownouts as low as 83V without using battery	**Surge Energy Rating**	316 Joules AC surge suppression

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA)	**Full Load Runtime (450W)**	2.5 Minutes
Half Load Runtime (225W)	8.6 Minutes	**Recharge Time**	Typically 8 hours to 90%
Communication Interface	USB HID-compliant port	**Status Indicators**	Front panel LED diagnostic indicators

Physical Dimensions, Mounting & Compliance

Form Factor	Compact Desktop / Wall-mount keyholes	**Dimensions (H x W x D)**	3.5" (89mm) x 11.0" (279mm) x 5.8" (147mm)
Net Weight	11.2 lbs (5.1 kg)	**Housing**	Ultra-compact fire-retardant plastic
Certifications	UL 1778, CSA, RoHS compliant	**Warranty**	3-Year Limited Product Warranty