TRIPP LITE • Infrastructure Technical Submittal

SKU: BP192V12-3U

3U 19" EIA Rackmount / Tower

Tripp Lite BP192V12-3U External 192V Rack/Tower Battery Pack

Heavy-duty 192VDC 3U external battery pack for Tripp Lite SmartOnline 3-phase and split-phase UPS systems including SU5000RT, SU6000RT, and SU8000RT. Features rugged daisy-chain DC connectors and heavy-duty cabling for extended backup runtime.

Electrical Specifications & Power Distribution

DC System Voltage	192V DC	**Battery Chemistry**	Sealed Lead Acid (VRLA) AGM
Compatibility	SU5000RT, SU6000RT, SU8000RT	**DC Connector**	Hardwired heavy-gauge DC connector cable
Daisy-Chain Capable	Yes, supports multiple external packs	**DC Bus Circuit Breaker**	Internal 40A / 192VDC fused isolation

Battery Runtime, Extended Packs & Communications

Internal Battery Quantity	16x 12V 9Ah sealed batteries	**Battery Lifespan**	3-5 years under normal float charge
Runtime Extension (SU5000RT)	+45 min @ half load, +18 min @ full load	**Runtime Extension (SU6000RT)**	+38 min @ half load, +15 min @ full load
Hot-Swappable	Yes, field serviceable tray design	**Recharge Time**	Typically 8 hours to 90% capacity

Physical Dimensions, Mounting & Compliance

Form Factor	3U Rackmount / Tower	**Dimensions (H x W x D)**	5.2" (132mm) x 17.5" (444mm) x 26.0" (660mm)
Net Weight	154.0 lbs (69.9 kg)	**Included Rails**	4-Post adjustable heavy-duty rack rail kit included
Enclosure	All-steel rugged chassis	**Warranty**	2-Year Limited Product Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
SU5000RT	Tripp Lite 5000VA Online Double-Conversion UPS	Host UPS System
SU6000RT	Tripp Lite 6000VA Online Double-Conversion UPS	Host UPS System