TRIPP LITE • Infrastructure Technical Submittal

SKU: BP48V24-2U

2U 19" EIA Rackmount / Tower

Tripp Lite BP48V24-2U 48VDC 2U External Battery Pack

Tripp Lite 48VDC 2U rack/tower external battery pack. Extends runtime for compatible Tripp Lite SmartPro and SmartOnline UPS systems (SMART2200RMXL2U, SU1500RTXLCD2U, etc.).

Electrical Specifications & Power Distribution

DC Bus Voltage	48V DC Industrial Battery Bus	**Battery Chemistry**	Sealed Lead Acid (VRLA)
Compatible UPS Models	SMART2200RMXL2U, SU1500RTXLCD2U, SU2200RMXL2U	**Daisy-Chain Capability**	Supports multiple battery packs in daisy-chain
Connection Cable	Attached heavy-duty DC connection cable	**Hot-Swappable**	Yes, hot-swappable during live UPS operation
Warranty	2-Year Limited Product Warranty	**Service Life**	3 to 5 Years typical

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 19.0" (483mm)
Net Weight	67.0 lbs (30.4 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	Tested to UL 1778, CSA, RoHS	**Operating Temp**	0°C to 40°C (32°F to 104°F)